

KOALA Components, S. A.
 Ctra. Masia del Juez, Km. 1, n° 27
 46909 TORRENT (VALENCIA)
 SPANIEN

Frankfurt am Main, 5.07.2021

**Declaration of manufacturer according to DIN EN 10204 (2005)
 For Art. no. 013.660.161**

Dear ladies and gentlemen,
 this manufacturer's declaration is valid only for devices / systems / components from Reutlinger GmbH.
 Incorporated customer items are excluded from this.

Safety notice: Sufficient strength of coupling to ceiling, floor, wall, etc. is under sole responsibility of the user.

Product Name	Fluoroplastic s Wire	Standard	Customer Specific	Serial number	2.1
Type	0.75mm ²	Rated Temperature	200°C	Rated Voltage	300V
Fluoroplastics Wire				Size	0.75mm ²
Specification					
Item		Unit	Standard		
Customer Material No.		-	013660161		
Conductor	Material	-	Tinned Copper		
	Structure	N/mm	19/0.23		
	Diameter	mm	0.23±0.01		
	Direction	-	Right handed(Z) One time twist		
Insulation	Color	-	Trans		
	Material	-	FEP		
	Overall Diameter	mm	1.60- (1.55~1.60)		
Electrical Properties					
Conductor Resistance (20°C)		26.7 Ω/km(Max)	PASS		
Dielectric Tests		1 min. in water ac	1500V		
Spark Tests		AC	2000V		

Z. Zmisa
 Qualitätswesen / quality department



E-Mail: z.zmisa@reutlinger.de