

SPECIFICATION

Description	220-240V 1-10V Dimming LED Driver, Constant Voltage Driver
Electrical Characteristics	Ta = 25°C, 100-240Vrms input, standard reference load; unless otherwise specified
Class I, IP67, thermally protected 110, independent driver	

Product Name		Q8H-150-24A
---------------------	--	-------------

Input Parameters		
Rated Input Voltage	Uin	220-240VAC
Input Current (Full load)	Iin	0.9A
Input Frequency	fin	50/60Hz
Maximum Input Power	Pin	169W
Power Factor (Full load)	λ	≥0.95
THD(Full load)		≤15%
Efficiency (Full load)	η	≥91%
No-load power		≤0.5W
Inrush current		≤65A
Turn on time		≤500ms

Output Parameters		
Output Voltage	Vout	24V±5%
Output Current (Full load)	Iout	6.25A
Output Power (Full load)	Pout	150W
Operating Frequency(Full load)	Fout	90~115KHz
Ripple & Noise		≤800mV
Load Regulation		≤5%
Line Regulation		≤5%

Ambient		
Storage Temperature	ts	-20 ... + 70°C
Operating Ambient Temperature	ta	-20 ... + 50°C
Case Temperature at tc Point	tc	90°C
Relative humidity		5 ... 85%



Protection		
No Load		Auto-recovery if fault is removed
Over Load		Auto-recovery if fault is removed
Short Circuit		Auto-recovery if fault is removed

System Parameters		
Withstand voltage		3.75KVAC, Ileakage<5.0mA, 60S
Expected Life		50,000Hours

Compliances and approvals		
Safety		EN 61347-2-13
RFI		EN 55015
Harmonics		EN 61000-3-2 Class C
Immunity		EN 61547

1. All parameters NOT specially mentioned are measured at 240VAC input, rated load and 25 of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.
3. Expected Life:tc=80°C,0.2%/1000h failure rate.

Physical Parameter

<p>Dimensions(LxWxH): 210x67x34mm</p> <p>Housing Material::PC Plastic</p> <p>Captured Terminal Screw for 0.75~2.5mm2</p>		
--	--	---