

**WOYR8.E208316****Switches, Appliance and Special Use Certified for Canada - Component**For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)**Switches, Appliance and Special Use Certified for Canada - Component**[See General Information for Switches, Appliance and Special Use Certified for Canada - Component](#)**NINGBO YINXIAN LIHE SWITCH FACTORY**

E208316

DAJIA CUN

GULIN TOWN

YIN COUNTY

NINGBO, ZHEJIANG 315177 CHINA

Cat. No.	Amps	Volts	Hz	Load	Endurance	Temp C	POL/THR	Per Pole/Circuit Code	SPCOA
<b>M2B MB-0700</b>	13	125	60	GP	10K	85	2/1	-/C	3
	8	250	60	GP	10K				
<b>RL1</b>	15	125	60	GP	6K	85	1/1,1/2	-/-	-
	7.5	250	60	GP	6K				
<b>RL1-3</b>	15	125	60	GP	6K	85	1/1,1/2	-/-	-
	7.5	250	60	GP	6K				
<b>RL1-5</b>	15	125	60	GP	6K	105	1/1,1/2	-/-	-
	-	125	60	3/4hp	6K				
	20	125	60	GP	6K				
	-	-	-	GP	-				
<b>RL1-8</b>	16	125	60	GP	6K	105	2/1	PP/-	-
	-	125	60	1/2hp	6K				
	-	250	60	1/2hp	6K				
<b>RL2 (P)</b>	16	125	60	GP	6K	80	2/1,2	-/B	2, A2
	10	250	60	GP	6K				
	-	250	60	3/4hp	6K				
	-	125	60	3/4hp	6K				
<b>RL2, RL2-5</b>	16	125	60	GP	6K	85	2/1, 2/2	-/-	2, 3
	8	250	60	GP	6K				
<b>RL2F</b>	16	125	60	GP	6K	85	2/1,2	-/-	-
	8	250	60	GP	6K				
<b>RL3,RL3-6</b>	16	125	60	GP	6K	105	1/1,1/2	-/-	-
	10	125	60	GP	6K				
	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
<b>RL3-10</b>	10	125	60	GP	6K	105	2/1,2	-/-	-
<b>RL3-10(S)</b>	10	125	60	GP	6K	105	1/4	-/A	-
<b>RL3-2</b>	10	125	60	GP	6K	105	2/1,2/2	-/-	-
	10	250	60	GP	6K				

	16	125	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
<b>RL3-3</b>	10	125	60	GP	6K	105	1/1	-/-	-
	10	250	60	GP	6K				
	16	125	60	GP	6K				
	-	250	60	1/3hp	6K				
	-	125	60	1/3hp	6K				
<b>RL3-4, RL3-4R, RL3-4S</b>									
	10	125	60	GP	6K	105	1/1,2/1	-/-	-
	10	250	60	GP	6K				
	16	125	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
<b>RL3-5</b>	16	125	60	GP	6K	105	1/1, 1/2	-/-	-
	10	125	60	GP	6K				
	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
<b>RL3-5(X) F</b>	10	125	60	GP	6K	105	2/2	-/-	-
	10	250	60	GP	6K				
	15	125	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
<b>RL3-5(X)D, RL3-5(X)E</b>									
	10	125	60	GP	6K	105	2/1	-/-	-
	10	250	60	GP	6K				
	15	125	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
<b>RL3-7</b>	10	125	60	GP	6K	85	1/1	-/-	3
<b>RL3-8</b>	6	125	60	GP	6K	80	1/1,1/2	-/-	3
<b>RL4</b>	6.5	125	60	GP	6K	105	2/2	PP/C	A1
	13	250	60	GP	6K				
<b>RL4-2</b>	6.5	125	60	GP	6K	105	2/3	PP/C	A1
	13	250	60	GP	6K				
<b>RL4-3</b>	6.5	125	60	GP	6K	105	2/4	PP/C	A1
	13	250	60	GP	6K				
<b>RL5</b>	16	125	60	GP	6K	105	2/2	-/-	2
	-	250	60	3/4hp	6K				
	-	125	60	1/2hp	6K				
<b>RL5-2</b>	16	125	60	GP	6K	85	1/2	-/A	-
	10	125	60	GP	6K				
	10	250	60	GP	6K				
	6	250	60	GP	6K				
<b>RL5-4</b>	6	125	60	GP	6K	85	1/2	-/A	3
	6	250	60	GP	6K				

	-	250	60	1/4hp	6K				
<b>RL6</b>	16	125	60	GP	6K	105	1/1	-/A	-
	16	250	60	GP	6K				
	6	125	60	GP	6K				
	6	250	60	GP	6K				
<b>RL6 (1E4)</b>	6	125	60	GP	10K	105	1/M	-/A	-
<b>RL6-2</b>	10	125	60	GP	6K	85	1/M	-/A	-
	6	250	60	GP	6K				
	6	125	60	GP	6K				
	-	125	60	1/4hp	6K				
<b>RL7 (T105)</b>	16	125	60	GP	6K	105	1/1	-/A	-
	8	250	60	GP	6K				
<b>RL7 (T65)</b>	16	125	60	GP	6K	65	1/1	-/A	-
	8	250	60	GP	6K				
<b>RL8</b>	8	125	60	GP	10K	85	2/1	-/C	3
	8	250	60	GP	10K				
<b>RL8 (D)</b>	13	125	60	GP	10K	85	2/1	-/C	3
	8	250	60	GP	10K				

A1 - Model RL4 - All materials employed for insulating material supporting opposite polarity fixed contacts have a Comparative Tracking Index (CTI) rating of 2 or better and a flammability rating of V-1 or better.

Note A2 - The waterproof covering for this switch was not tested during WOYR testing evaluation and must be evaluated during end product testing for acceptability.

Marking: Markings on the switch body consist of at least items (a) and (b) or (c) as noted below (other markings shall be on the smallest shipping package):



- (a) Manufacturer's identifier (such as name or trademark **RLEIL** , as described in the UL file)
- (b) Electrical ratings
- (c) Catalog or model number (or equivalent)
- (d) Factory code (as described in the UL Report, if more than one location)



- (e) Recognized Component Mark for Canada, **UL**

Last Updated on 2013-05-07

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".