



Ref. Certif. No.

DE 2-041124

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

LED Driver

Name and address of the applicant

Xiamen AcTEC Electronics Co., Ltd.  
No. 4, Tongfu Road, Tong'an Industrial Center, Tong'an District, Xiamen, 361100 Fujian, P.R. China

Name and address of the manufacturer

Xiamen AcTEC Electronics Co., Ltd.  
No. 4, Tongfu Road, Tong'an Industrial Center, Tong'an District, Xiamen, 361100 Fujian, P.R. China

Name and address of the factory

Xiamen AcTEC Electronics Co., Ltd.  
No. 4, Tongfu Road, Tong'an Industrial Center, Tong'an District, Xiamen, 361100 Fujian, P.R. China

Ratings and principal characteristics

Input: 220-240VAC, 50/60Hz or 176-280VDC; Class II  
For other ratings, Refer to page 2 of 2 of this certificate.

Trademark (if any)

AcTEC

Customer's Testing Facility (CTF) Stage used

CTF Stage 1

Model / Type Ref.

PW-xxx-yy  
(xxx = 40, 60, 100 or 150; yy = 12, 24 or 48)

Additional information (if necessary may also be reported on page 2)

For model differences, refer to the test report.

A sample of the product was tested and found to be in conformity with

IEC 61347-2-13:2014+A1  
IEC 61347-1:2015+A1  
See Test Report for National Differences

As shown in the Test Report Ref. No. which forms part of this Certificate

CN23AS20 001

This CB Test Certificate is issued by the National Certification Body



TÜV Rheinland LGA Products GmbH  
Tillystr. 2, 90431 Nürnberg, Germany  
Phone + 49 221 806-1371  
Fax + 49 221 806-3935  
Mail: cert-validity@de.tuv.com  
Web : www.tuv.com


Date: 2024-01-23

Signature:

Dipl.-Ing. Th. Illing

**Additional information :**

Model	Rate Input Voltage (V)	Rate Input Current (A)	Output Voltage (VDC)	Output Current (A)	Max. Output Power (W)	Ta (°C)	Tc (°C)
PW-40-12	220-240V AC. 176-280V DC.	0.25A for AC. 0.27A for DC.	12	3.33	40	45	90
PW-40-24			24	1.67			
PW-40-48			48	0.83			
PW-60-12	220-240V AC. 176-280V DC.	0.35A for AC. 0.38A for DC.	12	5	60	50	85
PW-60-24			24	2.5			
PW-60-48			48	1.25			
PW-100-24	220-240V AC. 176-280V DC.	0.6A for AC. 0.63A for DC.	24	4.17	100	45	90
PW-100-48			48	2.08			
PW-150-24	220-240V AC. 176-280V DC.	0.9A for AC. 0.93A for DC.	24	6.25	150	50	85
PW-150-48			48	3.13			

Date: 2024-01-23

Signature: Dipl.-Ing. Th. Illing