








Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Fiber Glass Terminal Blocks**  
 Subfamily **Fiberglass-24A 2.5 mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR17		1	0,2453 €
	Terminal block OK431-FV 2.5mm 2 poles high		50	0,2188 €
	temperature		100	0,1749 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel		3000	0,1590 €
		Length (mm): 14,5 Width (mm): 16,5 High (mm): 14,7 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
	Reference: 4140217			




Subfamily **Fiberglass-24A 2.5 mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR18		1	0,3669 €
	Terminal block OK431-FV 2.5mm 3 poles high temperature		50	0,3270 €
			100	0,2617 €
			2500	0,2379 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 22,5 Width (mm): 16,5 High (mm): 14,7 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4140317			
				
				

	491MR19		1	1,47 €
	Terminal block OK431-FV 2.5mm 12 poles high temperature		20	1,31 €
			100	1,08 €
			1200	0,95 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 94,3 Width (mm): 16,5 High (mm): 14,7 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4140090			
				
				

Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Fiber Glass Terminal Blocks**  
 Subfamily **Fiberglass-32A 4mm2 terminal block**


Picture	Article	Description	Lot	Price/Unit
	491MR14		1	0,3383 €
	Terminal block OK433-FV 4mm 2 poles for high temperature		50	0,3015 €
			100	0,2412 €
			3000	0,2192 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel  Length (mm): 17 Width (mm): 20,5 High (mm): 17,9 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw  Reference: 4136217			



Subfamily **Fiberglass-32A 4mm2 terminal block**






Picture	Article	Description	Lot	Price/Unit
	491MR15		1	0,5060 €
	Terminal block OK433-FV 4mm 3 poles high		50	0,4511 €
	temperature		100	0,3609 €
			2000	0,3281 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 27 Width (mm): 20,5 High (mm): 17,9 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw			
	Reference: 4136317			
				
				
	491MRH4		1	0,3384 €
	Terminal block OK433/2 FV-H		50	0,3016 €
			100	0,2412 €
			3000	0,2194 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 19,65 Width (mm): 20,5 High (mm): 19,4 Section (mm2): 4 Colour: Tile Voltage In (V): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw			
	Reference: 41422.17			
				
				

Subfamily **Fiberglass-32A 4mm2 terminal block**



Picture	Article	Description	Lot	Price/Unit
	491MRM4		1	0,3524 €
		Terminal block OK433-FV 4mm 2 poles marking L.N	50	0,3141 €
		high temperature	100	0,2510 €
		Polyamide PA 6-6 with 25% fiber	3000	0,2283 €
		glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel		
		Length (mm): 17 Width (mm): 20,5 High (mm): 17,4 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw		
		Reference: 4503017		





Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Fiber Glass Terminal Blocks**  
 Subfamily **Fiberglass Plug-in Power Strips**


Picture	Article	Description	Lot	Price/Unit
	B3RE802F		1	0,3173 €
	Terminal block female OK431 FV-SPF 2 poles 2,5mm2.		10	0,2115 €
			100	0,1763 €
			1500	0,1677 €
		Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)		
		Length (mm): 16 Width (mm): 16,3 High (mm): 15 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
		Reference: 4170228		
				
	B3RE802M		1	0,68 €
	Terminal block male OK431 FV-SPM 2 poles 2,5mm2.		10	0,4529 €
			100	0,3774 €
			1500	0,3595 €
		Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)		
		Length (mm): 16 Width (mm): 16,3 High (mm): 15 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
		Reference: 4170227		

Subfamily **Fiberglass Plug-in Power Strips**


Picture	Article	Description	Lot	Price/Unit
	B3RE803		1	1,72 €
	Terminal block male-female OK431 FV-SP 3 poles		10	1,14 €
	2.5mm <sup>2</sup>		100	0,95 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		1500	0,91 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
		Length (mm): 23,1 Width (mm): 32,8 High (mm): 14,7 Section (mm <sup>2</sup> ): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
				

	B3RE804		1	2,34 €
	Terminal block male-female OK431 FV-SP 4 poles		10	1,57 €
	2.5mm <sup>2</sup>		50	1,31 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		750	1,22 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
		Length (mm): 31,1 Width (mm): 32,8 High (mm): 14,7 Section (mm <sup>2</sup> ): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
				

Subfamily **Fiberglass Plug-in Power Strips**

Picture	Article	Description	Lot	Price/Unit
	B3RE902		1	1,43 €
	Terminal block male-female OK433 FV-SP 2 poles		10	0,95 €
	4mm2		100	0,79 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		1000	0,75 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 17,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			




	B3RE903		1	2,18 €
	Terminal block male-female OK433 FV-SP 3 poles		10	1,46 €
	4mm2		100	1,21 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		700	1,13 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 27,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			





ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Fiber Glass Terminal Blocks

Subfamily **Fiberglass Plug-in Power Strips**

Picture	Article	Description	Lot	Price/Unit
	B3RE904		1	2,86 €
	Terminal block male-female OK433 FV-SP 4 poles		10	1,90 €
	4mm2		100	1,57 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		500	1,52 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 37,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			

