


Catalogue **LED TECHNOLOGY**Line **Led modules**FAMILY **Led Lumens Modules**Subfamily **EggDrop G-series**

COB modules mains voltage 120V (UL) and 230V (EC) potencias 4 to 40W. CRI 80 and 90. T Color from 2700K to 600K. With automatic connectors .compatible with most existing TRIAC dimmer in the market .Optionally with LED Holder (Zhaga compliant) and Thermal pad connectors to distribute heat over the entire surface..

see manual application [aquí.](#)

see manual product [aquí.](#)

Picture	Article	Description	Lot	Price/Unit
	LUETT57		1	0,72 €
	Thermal Tape for EDC/57C		5	0,60 €
	UNTIL END OF STOCKS. Distributes the heat on the surface of the module. It should measure 6mm more in diameter than the module		50	0,55 €
	Diameter (mm): 63		100	0,52 €


Catalogue **LED TECHNOLOGY**

Line **Led modules**

FAMILY **Led Lumens Modules**


Subfamily **EggDrop F2-series Flicker Free**

COB Modules mains voltage. ECO desing according to ERP directives. Powers from 4 to 20W. Automatic connectors. Dimmable with leading and trailing edge dimmers.

Picture	Article	Description	Lot	Price/Unit
	LUE47049272F2		1	14,87 €
	Led Cob EDC/47C/4W/927/230V/F201		9	12,39 €
		ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers.	90	11,26 €
			180	10,73 €
		High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 316 Angle (°): 120 Energy efficiency: G CRI (≥): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		




Subfamily **EggDrop F2-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUE47049302F2		1	14,87 €
	Led Cob EDC / 47C / 4W / 930 / 230V / F201		9	12,39 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers.		90	11,26 €
			180	10,73 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 344 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			




LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUE47069272F2		1	14,98 €
	Led Cob EDC / 47C / 6W / 927 / 230V / F201		9	12,48 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers.		90	11,35 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 475 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95		180	10,80 €




	LUE47069302F2		1	14,98 €
	Led Cob EDC / 47C / 6W / 930 / 230V / F201		9	12,48 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers.		90	11,35 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 516 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95		180	10,80 €




LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUE47069402F2		1	14,98 €
	Led Cob EDC / 47C / 6W / 940 / 230V / F201		9	12,48 €
			90	11,35 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		180	10,80 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 537 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




	LUE47089272F2		1	15,07 €
	Led Cob EDC / 47C / 8W / 927 / 230V / F201		9	12,56 €
			90	11,41 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		180	10,87 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 665 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE47089302F2		1	15,07 €
	Led Cob EDC / 47C / 8W / 930 / 230V / F201		9	12,56 €
			90	11,41 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		180	10,87 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 722 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




	LUE47109272F2		1	15,20 €
	Led Cob EDC / 47C / 10W / 927 / 230V / F201		9	12,66 €
			90	11,51 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers.		180	10,96 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 831 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			



Subfamily **EggDrop F2-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE47109302F2		1	15,20 €
	Led Cob EDC / 47C / 10W / 930 / 230V / F201		9	12,66 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		90	11,51 €
			180	10,96 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 903 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




	LUE47109402F2		1	15,20 €
	Led Cob EDC / 47C / 10W / 940 / 230V / F201		9	12,66 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		90	11,51 €
			180	10,96 €
	High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 939 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			



Subfamily **EggDrop F2-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUE57089272F2		1	15,44 €
	Led Cob EDC / 57C / 8W / 927 / 230V / F201		5	12,87 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	11,70 €
			100	11,14 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 696 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			



	LUE57089302F2		1	15,44 €
	Led Cob EDC / 57C / 8W / 930 / 230V / F201		5	12,87 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	11,70 €
			100	11,14 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 757 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




Subfamily **EggDrop F2-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE57109272F2		1	15,56 €
	Led Cob EDC / 57C / 10W / 927 / 230V / F201		5	12,97 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	11,79 €
			100	11,23 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 870 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			
	LUE57109302F2		1	15,56 €
	Led Cob EDC / 57C / 10W / 930 / 230V / F201		5	12,97 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	11,79 €
			100	11,23 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 946 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			



Subfamily **EggDrop F2-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE57129272F2		1	15,68 €
	Led Cob EDC / 57C / 12W / 927 / 230V / F201		5	13,07 €
			50	11,88 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		100	11,31 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 12 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 997 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




	LUE57129302F2		1	15,68 €
	Led Cob EDC / 57C / 12W / 930 / 230V / F201		5	13,07 €
			50	11,88 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		100	11,31 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 12 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 1084 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			



Subfamily **EggDrop F2-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE57129402F2		1	15,68 €
	Led Cob EDC / 57C / 12W / 940 / 230V / F201		5	13,07 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	11,88 €
			100	11,31 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 12 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 1127 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




	LUE57159272F2		1	15,83 €
	Led Cob EDC / 57C / 15W / 927 / 230V / F201		5	13,20 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	12,00 €
			100	11,43 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 15 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 1246 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			



Subfamily **EggDrop F2-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUE57159302F2		1	15,83 €
	Led Cob EDC / 57C / 15W / 930 / 230V / F201		5	13,20 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	12,00 €
			100	11,43 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 15 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 1355 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




	LUE57159402F2		1	15,83 €
	Led Cob EDC / 57C / 15W / 940 / 230V / F201		5	13,20 €
	ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard		50	12,00 €
			100	11,43 €
	High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 15 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 1409 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95			




LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUEHL47F2		1	1,01 €
	Holder D47 for EDC/47C F201 white		5	0,85 €
	Holder for EggDrop modules direct to the network of 47 mm in diameter series F201		50	0,77 €
			100	0,73 €
	High (mm): 8,4 Diameter (mm): 47 Colour: White			









	LUEHL57F2		1	1,07 €
	Holder D60 for EDG/57C F201 white		5	0,88 €
	Zhaga standard. 5.5mm diameter fixing holes 35mm apart between centers.		50	0,81 €
			100	0,77 €
	High (mm): 9 Diameter (mm): 60 Colour: White			



LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUETT47F2		1	0,72 €
	Thermal Tape for EDC/47C F201		5	0,60 €
	Distributes the heat on the surface of the module. It should measure 6mm more in diameter than the module		50	0,55 €
	Diameter (mm): 53		100	0,52 €
	 			

	LUETT57		1	0,72 €
	Thermal Tape for EDC/57C		5	0,60 €
	UNTIL END OF STOCKS. Distributes the heat on the surface of the module. It should measure 6mm more in diameter than the module		50	0,55 €
	Diameter (mm): 63		100	0,52 €
				

Catalogue **LED TECHNOLOGY**


Line **Led modules**

FAMILY **Led Lumens Modules**

Subfamily **EggDrop F3-series Flicker Free**















COB Modules mains voltage. ECO desing according to ERP directives. Diameter 38mm. Powers 4, 6, 8W.

Automatic connectors. Dimmable with leading and trailing edge dimmers.


Picture	Article	Description	Lot	Price/Unit
	LUE38049272F3		1	15,11 €
	Led Cob EDC/38C/4W/927/230V/F302		10	12,58 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		80	11,44 €
			160	10,89 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 365 Angle (°): 120 Energy efficiency: F CRI (≥): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			




Subfamily **EggDrop F3-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUE38049302F3	Led Cob EDC/38C/4W/930/230V/F302	1	15,11 €
			10	12,58 €
			80	11,44 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	10,89 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 370 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				
	LUE38049402F3	Led Cob EDC/38C/4W/940/230V/F302	1	15,11 €
			10	12,58 €
			80	11,44 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	10,89 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 395 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				

Subfamily **EggDrop F3-series Flicker Free**















Picture	Article	Description	Lot	Price/Unit
	LUE38069272F3		1	15,28 €
	Led Cob EDC/38C/6W/927/230V/F302		10	12,73 €
			100	11,57 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		200	11,02 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 560 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			







	LUE38069302F3		1	15,28 €
	Led Cob EDC/38C/6W/930/230V/F302		10	12,73 €
			80	11,57 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		160	11,02 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 570 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			



Subfamily **EggDrop F3-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE38069402F3		1	15,28 €
	Led Cob EDC/38C/6W/940/230V/F302		10	12,73 €
			80	11,57 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		160	11,02 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 595 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			
     				
	LUE38089272F3		1	15,42 €
	Led Cob EDC/38C/8W/927/230V/F302		10	12,84 €
			80	11,67 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		160	11,12 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 745 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			
     				

Subfamily **EggDrop F3-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE38089302F3	Led Cob EDC/38C/8W/930/230V/F302	1	15,42 €
			10	12,84 €
			80	11,67 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	11,12 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 760 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
				
	LUE38089402F3	Led Cob EDC/38C/8W/940/230V/F302	1	15,42 €
			10	12,84 €
			80	11,67 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	11,12 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 790 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
				

LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F3-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUEHL38F3		1	1,07 €
	Holder for EDC/38C F302		5	0,88 €
			50	0,81 €
	High (mm): 8,3 Diameter (mm): 40,7		100	0,77 €



	LUETT38F3		1	0,69 €
	Thermal Tape for EDC/38C F302		50	0,57 €
	Distributes the heat on the surface of the module. It must measure 6mm more in diameter than the module		100	0,52 €
	Diameter (mm): 44 Colour: Black		200	0,49 €




Catalogue **LED TECHNOLOGY**

Line **Led modules**

FAMILY **Led Lumens Modules**

Subfamily **Downlight Module Series F**



Led module 100mm Diameter. ECO desing according to ERP directives

Picture	Article	Description	Lot	Price/Unit
	LUD100169272		1	16,95 €
	Led Module DLM100C/16W/927/230V/ F201		12	15,41 €
	ECO design according to ERP directives. Automatic connectors. Dimmables by leading or trailing edge dimmers. No cover. Cover code LUD100CV to be ordered separately		120	14,01 €
			240	13,34 €
	<p>Diameter (mm): 100 Voltage In (Vac): 230 Intensidad In (A): 0.063 Frecuency (Hz): 50~60 Power (W): 16 Temperature (°C): -40~+85 Room Temperature (°C): -40~+85 Colour Temperature (°K): 2700 Lumen: 1520 Angle (°): 120 CRI (≥): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95</p>			



LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **Downlight Module Series F**

Picture	Article	Description	Lot	Price/Unit
	LUD100169302		1	16,95 €
	Led Module DLM100C/16W/930/230V/ F201		12	15,41 €
	ECO design according to ERP directives. Automatic connectors. Dimmables by leading or trailing edge dimmers. No cover. Cover code LUD100CV to be ordered separately		120	14,01 €
			240	13,34 €
	Diameter (mm): 100 Voltage In (Vac): 230 Intensidad In (A): 0.063 Frecuency (Hz): 50~60 Power (W): 16 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Colour Temperature (°K): 3000 Lumen: 1616 Angle (°): 120 CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			
	LUD100CV		1	1,51 €
	DLM100C F201 Led Module Cover		12	1,26 €
	Transparent plastic cover for DLM 100C F201		120	1,20 €
			240	1,16 €
	Diameter (mm): 100 Colour: Transparent			

