











Catalogue **HALOTEC HARDWARE**
 Line **Halotec Small Installation Material**
 Family **PLP Terminal Block for Installation**
 Subfamily **PLP Installation terminal blocks**




Picture	Article	Description	Lot	Price/Unit
	SK04101K	Terminal Block 432- PLP 4mm2. 12 Holes	10 (Pedido mínimo)	1,11 €
		Polypropylene auto-extinguishable UL94V2 homologated for working temperature 85 °C	50	1,00 €
		Section (mm2): 4 Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 85 Reference: 4017510	100	0,96 €
				
	SK04102K	Terminal Block 433-PLP 6mm2. 12 Holes	10 (Pedido mínimo)	1,24 €
		Polypropylene auto-extinguishable UL94V2 homologated for working temperature 85 °C	50	1,13 €
		Section (mm2): 6 Voltage In (Vac): 450 Intensidad In (A): 41 Temperature (°C): 85 Reference: 4011510	300	1,08 €
				

Subfamily **PLP Installation terminal blocks**



Picture	Article	Description	Lot	Price/Unit
	SK04103K	Terminal Block 434-PLP 10mm2. 12 Holes	10 (Pedido mínimo)	1,50 €
		Polypropylene auto-extinguishable UL94V2 homologated for working temperature 85°C	50	1,38 €
		Section (mm2): 10 Voltage In (Vac): 450 Intensidad In (A): 57 Temperature (°C): 85	260	1,30 €
		Reference: 4013010		
	SK04104K	Terminal Block 435- PLP 16mm2. 12 Holes	10 (Pedido mínimo)	3,25 €
	Polypropylene self-extinguishing UL94V2 approved for working temperature of 85 ° C		50	2,94 €
	Section (mm2): 16 Voltage In (Vac): 450 Intensidad In (A): 76 Temperature (°C): 85		130	2,82 €
	Reference: 4014510			




Subfamily **PLP Installation terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	SK04105K	Terminal Block 438-PLP 25mm2. 12 Holes	3 (Pedido mínimo)	7,31 €
		Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C	30	6,63 €
		Section (mm2): 25 Voltage In (Vac): 450 Intensidad In (A): 101 Temperature (°C): 85	54	6,32 €
		Reference: 4016010		
				




	SK04106K	Connection strip 432-PLP 4mm2.Black, 12 pole	10 (Pedido mínimo)	1,11 €
		Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C	160	1,01 €
		Section (mm2): 4 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 85	320	0,96 €
		Reference: 4017501		
				


Subfamily **PLP Installation terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	SK04107K	Connection strip 433-PLP 6mm2.Black, 12 pole	10 (Pedido mínimo)	1,24 €
		Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C	50	1,13 €
		Section (mm2): 6 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 41 Temperature (°C): 85	300	1,08 €
		Reference: 4011501		
				

	SK04108K	Connection strip 434-PLP 10mm2.Black, 12 pole	10 (Pedido mínimo)	1,50 €
		Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C	50	1,38 €
		Section (mm2): 10 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 57 Temperature (°C): 85	260	1,30 €
		Reference: 4013001		
				

Subfamily **PLP Installation terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	SK04109K	Connection strip 435-PLP 16mm2.Black, 12 pole	10 (Pedido mínimo)	3,25 €
		Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C	50	2,94 €
		Section (mm2): 16 Voltage In (Vac): 450 Intensidad In (A): 76 Temperature (°C): 85	130	2,82 €
		Reference: 4014501		
				

	SK04110K	Connection strip 438-PLP 25mm2.Black, 12 pole	3 (Pedido mínimo)	7,25 €
		Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C	30	6,59 €
		Section (mm2): 25 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 101 Temperature (°C): 85	54	6,28 €
		Reference: 4016001		
