










Catalogue **HALOTEC HARDWARE**
 Line **Halotec Small Installation Material**
 Family **PLP Terminal Block for Installation**
 Subfamily **PLP Installation terminal blocks**




| Picture | Article | Description | Lot | Price/Unit |
|---|----------|--|--------------------|------------|
|  | SK04101K | Terminal Block 432- PLP 4mm2. 12 Holes | 10 (Pedido mínimo) | 1,11 € |
| | | Polypropylene auto-extinguishable UL94V2 homologated for working temperature 85 °C | 50 | 1,00 € |
| | | Section (mm2): 4 Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 85 Reference: 4017510 | 100 | 0,96 € |
|  | | | | |
|  | SK04102K | Terminal Block 433-PLP 6mm2. 12 Holes | 10 (Pedido mínimo) | 1,24 € |
| | | Polypropylene auto-extinguishable UL94V2 homologated for working temperature 85 °C | 50 | 1,13 € |
| | | Section (mm2): 6 Voltage In (Vac): 450 Intensidad In (A): 41 Temperature (°C): 85 Reference: 4011510 | 300 | 1,08 € |
|  | | | | |

Subfamily **PLP Installation terminal blocks**



| Picture | Article | Description | Lot | Price/Unit |
|---|----------|---|--------------------|------------|
|  | SK04103K | Terminal Block 434-PLP 10mm2. 12 Holes | 10 (Pedido mínimo) | 1,50 € |
| | | Polypropylene auto-extinguishable UL94V2 homologated for working temperature 85°C | 50 | 1,38 € |
| | | Section (mm2): 10 Voltage In (Vac): 450 Intensidad In (A): 57 Temperature (°C): 85 | 260 | 1,30 € |
| | | Reference: 4013010 | | |
|  | SK04104K | Terminal Block 435- PLP 16mm2. 12 Holes | 10 (Pedido mínimo) | 3,25 € |
| | | Polypropylene self-extinguishing UL94V2 approved for working temperature of 85 ° C | 50 | 2,94 € |
| | | Section (mm2): 16 Voltage In (Vac): 450 Intensidad In (A): 76 Temperature (°C): 85 | 130 | 2,82 € |
| | | Reference: 4014510 | | |




Subfamily **PLP Installation terminal blocks**

| Picture | Article | Description | Lot | Price/Unit |
|---|---|---|-------------------|------------|
|  | SK04105K | Terminal Block 438-PLP 25mm2. 12 Holes | 3 (Pedido mínimo) | 7,31 € |
| | | Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C | 30 | 6,63 € |
| | | Section (mm2): 25 Voltage In (Vac): 450 Intensidad In (A): 101 Temperature (°C): 85 | 54 | 6,32 € |
| | | Reference: 4016010 | | |
|  |  | <hr/> | | |







| | | | | |
|---|---|---|--------------------|--------|
|  | SK04106K | Connection strip 432-PLP 4mm2.Black, 12 pole | 10 (Pedido mínimo) | 1,11 € |
| | | Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C | 160 | 1,01 € |
| | | Section (mm2): 4 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 85 | 320 | 0,96 € |
| | | Reference: 4017501 | | |
|  |  | <hr/> | | |

Subfamily **PLP Installation terminal blocks**

| Picture | Article | Description | Lot | Price/Unit |
|---|---|---|--------------------|------------|
|  | SK04107K | Connection strip 433-PLP 6mm2.Black, 12 pole | 10 (Pedido mínimo) | 1,24 € |
| | | Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C | 50 | 1,13 € |
| | | Section (mm2): 6 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 41 Temperature (°C): 85 | 300 | 1,08 € |
| | | Reference: 4011501 | | |
|  |  | | | |

| | | | | |
|---|---|--|--------------------|--------|
|  | SK04108K | Connection strip 434-PLP 10mm2.Black, 12 pole | 10 (Pedido mínimo) | 1,50 € |
| | | Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C | 50 | 1,38 € |
| | | Section (mm2): 10 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 57 Temperature (°C): 85 | 260 | 1,30 € |
| | | Reference: 4013001 | | |
|  |  | | | |

Subfamily **PLP Installation terminal blocks**

| Picture | Article | Description | Lot | Price/Unit |
|---|---|---|--------------------|------------|
|  | SK04109K | Connection strip 435-PLP 16mm2.Black, 12 pole | 10 (Pedido mínimo) | 3,25 € |
| | | Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C | 50 | 2,94 € |
| | | Section (mm2): 16 Voltage In (Vac): 450 Intensidad In (A): 76 Temperature (°C): 85 | 130 | 2,82 € |
| | | Reference: 4014501 | | |
|  |  | <hr/> | | |
|  | SK04110K | Connection strip 438-PLP 25mm2.Black, 12 pole | 3 (Pedido mínimo) | 7,25 € |
| | | Polypropylene self-extinguishing UL94V2, approved for working temperature of 85 ° C | 30 | 6,59 € |
| | | Section (mm2): 25 Colour: Black Voltage In (Vac): 450 Intensidad In (A): 101 Temperature (°C): 85 | 54 | 6,28 € |
| | | Reference: 4016001 | | |
|  |  | <hr/> | | |