












Catalogue **SMART LIGHTING**  
 Line **Lighting control by Nexta Tech**  
 FAmily **Receivers**  
 Subfamily **230V On-Off / Dimmer**  
**Download Nexta Tech catalogue [here.](#)**

Picture	Article	Description	Lot	Price/Unit
 	15LOGIC400ONE	Control unit LOGIC 400/ONE 6000W-230V	1	132,87 €
		For the control of 4 lighting outputs. Remote control via AppOneSmart	10	126,54 €
 	15MCUL1ONE	Control Unit MCU-L1/ONE 1000W/110-240V	1	58,27 €
 		Remote control via AppOneSmart	10	46,77 €
 		Length (mm): 140 Width (mm): 90 High (mm): 45 Voltage In (Vac): 230 Power (W): 6000 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
 		Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Power (W): 250 Room Temperature (°C): -25~+55 Ingress Protection: IP20		

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **230V On-Off / Dimmer**

Picture	Article	Description	Lot	Price/Unit
	15TOPL1ONE		1	102,53 €
		Control unit TOP-L1/ONE 3000W 110-240V	10	97,64 €

Remote control via AppOneSmart



Length (mm): 174 Width (mm): 46 High (mm): 35  
Voltage In (Vac): 110~240 Power (W): 3000  
Room Temperature (°C): -20~+55  
Ingress Protection: IP20








Catalogue **SMART LIGHTING**  
Line **Lighting control by Nexta Tech**  
FAMILY **Receivers**


Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

**Download Nexta Tech catalogue [here](#).**












Picture	Article	Description	Lot	Price/Unit
	15MCU1224P		1	63,32 €
	Control unit MCU-1224P 12-24V	For dimmable drivers with PUSH. Normally open dry contact output max 1A.  Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vdc/ac): 12~24 Intensidad Out (A): 1 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	60,31 €
	15MCUDMONE		1	57,47 €
	Control unit MCU-DM/ONE 4-150W 110-240V	Remote control via AppOneSmart  Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Power (W): 4~150 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	54,73 €

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**







Picture	Article	Description	Lot	Price/Unit
	15MCUPUSH		1	63,32 €
	Control unit Interface radio MCU-PUSH exit Push-Dim. 110-240V. 5A.		10	60,31 €
		Radio frequency interface for the control of Led drivers with "push dim" input  Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Intensidad In (A): 5 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		



	15TOP0110		1	86,68 €
	Control unit interface TOP-0110 for drivers 0-1/10V 2000W		10	82,55 €
		Receiver for RF regulation or cable of devices with input 0-1 / 10V max 2000W  Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Power (W): 2000 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**



Picture	Article	Description	Lot	Price/Unit
	15TOP0110ONE		1	100,40 €
	Control unit interface TOP-0110/ONE for drivers 0-1/10V 2000W		10	95,62 €
		For control of 0 / 1-10V Drivers		
		Length (mm): 176 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~230 Power (W): 2000 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		 		
	15TOPDL20		1	91,87 €
	Control unit interface TOP-DL20 for Drivers DALI		10	87,49 €
		Interphase receiver with dimmer function and DALI output for the control of up to 20 devices with DALI input. Power 110-240Vac. Departure BUS DALI		
		Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		


Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15TOPDL20ONE		1	114,66 €
	Control unit interface TOP-DL20/ONE for Drivers DALI		10	109,20 €
		Interface for controlling DALI Drivers. Max 20 drivers		
		Length (mm): 176 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
			 	

	15WITOP100		1	16,41 €
	Connection wire 1 m. RJ11 for TOP extender		10	15,63 €
		1 meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series		
		Length (mm): 1000		
				

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15WITOP1000		1	26,17 €
	Connection wire 10 m. RJ11 for TOP extender		10	24,92 €
		10-meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 10000		
				

	15WITOP30		1	13,10 €
	Connection wire 30 cm. RJ11 for TOP extender		10	12,48 €
		30 cm RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 300		
				

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15WITOP500		1	21,02 €
		Connection wire 5 m. RJ11 for TOP extender	10	20,02 €

5-meter RJ11 connection cable with mounted connectors for the connection of the master control panel with the extension of the TOP series.

Length (mm): 5000















Catalogue **SMART LIGHTING**  
Line **Lighting control by Nexta Tech**  
FAMILY **Receivers**

Subfamily **Constant current control, Dimmer, RGB**




**Download Nexta Tech catalogue [here.](#)**




Picture	Article	Description	Lot	Price/Unit
 	15TOPA03073	Control unit dimmer TOP-A0307/3 CC 350-700mA	1	97,66 €
		Intensity regulator for LED modules with constant current at 350mA or 700mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc  Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Ingress Protection: IP20	10	93,00 €
		  		
 	15TOPA0307RGB	Control unit dimmer TOP-A0307/RGB for led RGB CC 350-700mA	1	97,66 €
		Intensity regulator for RGB LED modules with constant current at 350mA or 700mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc  Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	93,00 €
		  		

Subfamily **Constant current control, Dimmer, RGB**



Picture	Article	Description	Lot	Price/Unit
	15TOPA05093		1	97,66 €
	Control unit dimmer TOP-A0509/3 for led CC 500-900mA	Intensity regulator for RGB LED modules with constant current at 500mA or 900mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc  Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12-36 Ingress Protection: IP20	10	93,00 €
	15TOPA0509RGB		1	98,28 €
	Control unit dimmer TOP-A0509/RGB for led RGB CC 500-900mA	Intensity regulator for RGB LED modules with constant current at 500mA or 900mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc  Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12-36 Ingress Protection: IP20	10	93,60 €



Subfamily **Constant current control, Dimmer, RGB**

Picture	Article	Description	Lot	Price/Unit
	15WITOP100		1	16,41 €
	Connection wire 1 m. RJ11 for TOP extender		10	15,63 €
		1 meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series		
		Length (mm): 1000		
				

	15WITOP1000		1	26,17 €
	Connection wire 10 m. RJ11 for TOP extender		10	24,92 €
		10-meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 10000		
				

Subfamily **Constant current control, Dimmer, RGB**

Picture	Article	Description	Lot	Price/Unit
	15WITOP30		1	13,10 €
	Connection wire 30 cm. RJ11 for TOP extender		10	12,48 €
		30 cm RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 300		
				

	15WITOP500		1	21,02 €
	Connection wire 5 m. RJ11 for TOP extender		10	20,02 €
		5-meter RJ11 connection cable with mounted connectors for the connection of the master control panel with the extension of the TOP series.		
		Length (mm): 5000		
				









Catalogue **SMART LIGHTING**

Line **Lighting control by Nexta Tech**






FAMILY **Receivers**





Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

**Download Nexta Tech catalogue [here.](#)**




Picture	Article	Description	Lot	Price/Unit
	15PLANOMASTER		1	62,28 €
	PLANO-MASTER 12-24V DC LED		10	59,32 €
		Universal controller for led 12-24Vdc. Dimmer, RGB, RGBW, CCT  Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+50 Ingress Protection: IP20		
		 		
	15PLANOONE		1	69,62 €
	PLANO-ONE 12-24V DC LED		10	66,30 €
		Universal controller for led 12-24Vdc. Dimmer, RGB, RGBW, CCT  Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+50 Ingress Protection: IP20		
		 		




Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15PLANOV5		1	42,04 €
	PLANO-V5 1 channel dimmer receiver monochromatic CV 12-24V		10	40,04 €
		Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Intensidad In (A): 5 Power (W): 60~120 Room Temperature (°C): -20~+50 Ingress Protection: IP20		
		  		

	15PLANOV54BLE		1	70,66 €
	Control unit PLANO-V5/4BLE		10	67,29 €
		4xLed 12-24Vdc. Max 3A por salida. 36W a12V; 72W a 24V por cada salida. Max total 5A. 60W a 12V; 120W a 24V.  Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		 		

Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15PLANOV54CH		1	57,47 €
	PLANO-V5 4CH dimmer receiver 4 channels single color CV CV 12-24V		10	54,73 €
 		Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Intensidad In (A): 5 Power (W): 60~120 Room Temperature (°C): -20~+50 Ingress Protection: IP20		

	15PLANOV5RGBW		1	58,11 €
	PLANO-V5 RGBW dimmer receiver for RGB and RGBW CV 12-24V LED		10	45,24 €
 		Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Intensidad In (A): 5 Power (W): 60~120 Room Temperature (°C): -20~+50 Ingress Protection: IP20		






Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15PLANOV5RGBWBL		1	70,66 €
	Control unit PLANO-V5 RGBW/BLE		10	67,29 €
		Function: Mode 1: RGB. Mode 2: RGBW (W-W), Mode 3: RGBW (W-W + RGB)  Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		

	15TOPV84		1	98,25 €
	Control unit dimmer TOP-V8/4 for led monocolor CV 12-24-36V.		10	93,57 €
		Dimmer for leds at constant voltage 12-24-36 Vdc 4 outputs max 8A per output (max 24A total) With 3 cable entries and input to extend  Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		










Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15TOPV8CCT2		1	107,12 €
	Control unit TOP-V8/CCT2 dimmer and Tcolor for led a CV 12-24-36V.		10	102,05 €
		<p>Dimmer for LEDs at constant voltage 12-24-36 Vdc with warm and cold LED. 4 outputs max 8A per output (max 24A total) With 3 cable entries and input to extend</p> <p>Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Room Temperature (°C): -20~+55 Ingress Protection: IP20</p>		
		<p>CE</p> <p> </p>		

	15TOPV8EXT4		1	68,25 €
	Control unit dimmer slave TOP-V8/EXT4 for led monocolor CV 12-24-36V.		10	65,00 €
		<p>Slave dimmer for led to constant tension compatible with master stations TOP-V8 / 4 monocolor</p> <p>Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+55 Ingress Protection: IP20</p>		
		<p>CE</p> <p> </p>		



Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**


Picture	Article	Description	Lot	Price/Unit
	15TOPV8RGBW		1	98,25 €
	Control unit dimmer TOP-V8/RGBW for led RGB and RGBW CV 12-24-36V		10	93,57 €
		<p>Dimmer for LEDs with constant voltage 12-24-36 Vdc of RGB and RGBW LEDs. 4 outputs max 8A per output (max 24A total) With 3 cable entries and input to extend</p> <p>Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Room Temperature (°C): -20~+55 Ingress Protection: IP20</p>		
		  		

	15WITOP100		1	16,41 €
	Connection wire 1 m. RJ11 for TOP extender		10	15,63 €
		<p>1 meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series</p> <p>Length (mm): 1000</p>		
				

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15WITOP1000		1	26,17 €
	Connection wire 10 m. RJ11 for TOP extender		10	24,92 €
		10-meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 10000		
				

	15WITOP30		1	13,10 €
	Connection wire 30 cm. RJ11 for TOP extender		10	12,48 €
		30 cm RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 300		
				

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15WITOP500		1	21,02 €
		Connection wire 5 m. RJ11 for TOP extender	10	20,02 €

5-meter RJ11 connection cable with mounted connectors for the connection of the master control panel with the extension of the TOP series.

Length (mm): 5000





Catalogue **SMART LIGHTING**

Line **Lighting control by Nexta Tech**

FAMILY **Receivers**

Subfamily **Motors control**

**Download Nexta Tech catalogue [here.](#)**

Picture	Article	Description	Lot	Price/Unit
---------	---------	-------------	-----	------------