




Catalogue **SMART LIGHTING**
 Line **Lighting control by Nexta Tech**
 FAmily **Receivers**
 Subfamily **230V On-Off / Dimmer**
Download Nexta Tech catalogue [here.](#)

Picture	Article	Description	Lot	Price/Unit
	15LOGIC400ONE		1	132,87 €
	Control unit LOGIC 400/ONE 6000W-230V	For the control of 4 lighting outputs. Remote control via AppOneSmart	10	126,54 €
	15MCUL1ONE		1	58,27 €
	Control Unit MCU-L1/ONE 1000W/110-240V	Remote control via AppOneSmart	10	46,77 €



For the control of 4 lighting outputs. Remote control via AppOneSmart

Length (mm): 140 Width (mm): 90 High (mm): 45
 Voltage In (Vac): 230 Power (W): 6000
 Room Temperature (°C): -20~+55
 Ingress Protection: IP20








Remote control via AppOneSmart

Length (mm): 52 Width (mm): 43 High (mm): 21
 Voltage In (Vac): 110~240 Power (W): 250
 Room Temperature (°C): -25~+55
 Ingress Protection: IP20



Subfamily **230V On-Off / Dimmer**

Picture	Article	Description	Lot	Price/Unit
	15MCUL2		1	50,44 €
	Control Unit MCU-L2 2x500W/110-240V		10	43,42 €
		Receiver control 2 device max 500W each with ON OFF and timed functionality.		
		Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Power (W): 1000 Ingress Protection: IP20		
		  		

	15MCUSIM1		1	50,44 €
	Control Unit MCU-SIM1 1000W/110-240V-presence simulator		10	47,97 €
		Receiver with On / Off or timed functionality and presence simulator. 1 exit Maximum power 1000W (230V).		
		Length (mm): 52 Width (mm): 42 High (mm): 21 Voltage In (Vac): 110~240 Power (W): 1000 Ingress Protection: IP20		
		  		

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **230V On-Off / Dimmer**

Picture	Article	Description	Lot	Price/Unit
	15TOPL1ONE		1	102,53 €
		Control unit TOP-L1/ONE 3000W 110-240V	10	97,64 €

Remote control via AppOneSmart



Length (mm): 174 Width (mm): 46 High (mm): 35
Voltage In (Vac): 110~240 Power (W): 3000
Room Temperature (°C): -20~+55
Ingress Protection: IP20








Catalogue **SMART LIGHTING**
Line **Lighting control by Nexta Tech**
FAMILY **Receivers**


Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Download Nexta Tech catalogue [here](#).





Picture	Article	Description	Lot	Price/Unit
	15MCU1224P		1	63,32 €
	Control unit MCU-1224P 12-24V	For dimmable drivers with PUSH. Normally open dry contact output max 1A. Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vdc/ac): 12~24 Intensidad Out (A): 1 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	60,31 €
	15MCUDMONE		1	57,47 €
	Control unit MCU-DM/ONE 4-150W 110-240V	Remote control via AppOneSmart Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Power (W): 4~150 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	54,73 €



Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15MCUPUSH		1	63,32 €
	Control unit Interface radio MCU-PUSH exit Push-Dim. 110-240V. 5A.		10	60,31 €
		Radio frequency interface for the control of Led drivers with "push dim" input		
		Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Intensidad In (A): 5 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		







	15TOP0110		1	86,68 €
	Control unit interface TOP-0110 for drivers 0-1/10V 2000W		10	82,55 €
		Receiver for RF regulation or cable of devices with input 0-1 / 10V max 2000W		
		Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Power (W): 2000 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		



Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15TOP0110ONE		1	100,40 €
	Control unit interface TOP-0110/ONE for drivers 0-1/10V 2000W		10	95,62 €
		For control of 0 / 1-10V Drivers Length (mm): 176 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~230 Power (W): 2000 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		 		

	15TOPDL20		1	91,87 €
	Control unit interface TOP-DL20 for Drivers DALI		10	87,49 €
		Interphase receiver with dimmer function and DALI output for the control of up to 20 devices with DALI input. Power 110-240Vac. Departure BUS DALI Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		




Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**


Picture	Article	Description	Lot	Price/Unit
	15TOPDL20ONE		1	114,66 €
	Control unit interface TOP-DL20/ONE for Drivers DALI		10	109,20 €
		Interface for controlling DALI Drivers. Max 20 drivers Length (mm): 176 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		 	 	

	15WITOP100		1	16,41 €
	Connection wire 1 m. RJ11 for TOP extender		10	15,63 €
		1 meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series Length (mm): 1000		
				

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15WITOP1000		1	26,17 €
	Connection wire 10 m. RJ11 for TOP extender		10	24,92 €
		10-meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 10000		
				

	15WITOP30		1	13,10 €
	Connection wire 30 cm. RJ11 for TOP extender		10	12,48 €
		30 cm RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 300		
				

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15WITOP500		1	21,02 €
		Connection wire 5 m. RJ11 for TOP extender	10	20,02 €











5-meter RJ11 connection cable with mounted connectors for the connection of the master control panel with the extension of the TOP series.
Length (mm): 5000




Catalogue **SMART LIGHTING**
Line **Lighting control by Nexta Tech**
FAMILY **Receivers**

Subfamily **Constant current control, Dimmer, RGB**

Download Nexta Tech catalogue [here.](#)

Picture	Article	Description	Lot	Price/Unit
 	15TOPA03073	Control unit dimmer TOP-A0307/3 CC 350-700mA	1	97,66 €
		Intensity regulator for LED modules with constant current at 350mA or 700mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Ingress Protection: IP20	10	93,00 €
		  		
 	15TOPA0307EXT3	Control unit dimmer slave TOP-A0307/EXT3 for CC 350-700mA	1	68,58 €
		Slave intensity regulator for LED modules with constant current at 350mA or 700mA selectable with jumper. Power supply with special cable for master-extender connection Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Ingress Protection: IP20	10	65,31 €
		  		

Subfamily **Constant current control, Dimmer, RGB**




Picture	Article	Description	Lot	Price/Unit
	15TOPA0307RGB		1	97,66 €
	Control unit dimmer TOP-A0307/RGB for led RGB CC 350-700mA	Intensity regulator for RGB LED modules with constant current at 350mA or 700mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12-36 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	93,00 €
				



	15TOPA05093		1	97,66 €
	Control unit dimmer TOP-A0509/3 for led CC 500-900mA	Intensity regulator for RGB LED modules with constant current at 500mA or 900mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12-36 Ingress Protection: IP20	10	93,00 €
				









Subfamily **Constant current control, Dimmer, RGB**

Picture	Article	Description	Lot	Price/Unit
	15TOPA0509EXT3		1	68,58 €
	Control unit dimmer slave TOP-A0509/EXT3 for led CC 500-900mA	Slave intensity regulator for LED modules with constant current at 500mA or 900mA selectable with jumper. Power supply with special cable for master-extender connection	10	65,31 €
	15TOPA0509RGB		1	98,28 €
	Control unit dimmer TOP-A0509/RGB for led RGB CC 500-900mA	Intensity regulator for RGB LED modules with constant current at 500mA or 900mA selectable with jumper. Low voltage power supply 12-24 or 36Vdc	10	93,60 €







Subfamily **Constant current control, Dimmer, RGB**

Picture	Article	Description	Lot	Price/Unit
	15WITOP100		1	16,41 €
	Connection wire 1 m. RJ11 for TOP extender		10	15,63 €
		1 meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series		
		Length (mm): 1000		
				

	15WITOP1000		1	26,17 €
	Connection wire 10 m. RJ11 for TOP extender		10	24,92 €
		10-meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 10000		
				

Subfamily **Constant current control, Dimmer, RGB**



Picture	Article	Description	Lot	Price/Unit
	15WITOP30		1	13,10 €
	Connection wire 30 cm. RJ11 for TOP extender		10	12,48 €
		30 cm RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 300		
				

	15WITOP500		1	21,02 €
	Connection wire 5 m. RJ11 for TOP extender		10	20,02 €
		5-meter RJ11 connection cable with mounted connectors for the connection of the master control panel with the extension of the TOP series.		
		Length (mm): 5000		
				

Catalogue **SMART LIGHTING**
Line **Lighting control by Nexta Tech**
FAMILY **Receivers**






Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**






Download Nexta Tech catalogue [here](#).

Picture	Article	Description	Lot	Price/Unit
	15MCUDMW	Control Unit dimmer MCU-DMW with function Dim to warm CV 12-24V.	1	66,99 €
		Intensity regulator for LEDs of constant tension to 12-24Vdc Max 4A with "Dim to warm" function Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vdc/ac): 12~24 Ingress Protection: IP20	10	63,80 €
	15MCUV3RGB	Control Unit dimmer MCU-V3/RGB for led RGB CV 12-24V.	1	63,96 €
		Current regulator for RGB led at constant voltage 12-24Vdc max 2,5A per output. Length (mm): 52 Width (mm): 42 High (mm): 21 Voltage In (Vdc): 12~24 Ingress Protection: IP20	10	47,19 €

SMART LIGHTING > Lighting control by Nexta Tech > Receivers






Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15MCUV4CCT		1	67,34 €
	Control Unit MCU-V4/CCT dimmer and Tcolor for led CV 12-24V.		10	46,15 €
		<p>Intensity regulator for warm led + cold led at constant voltage 12-24Vdc. Control of Tcolor CCT (dynamic white) 2 outputs max 4A per output.</p> <p>Length (mm): 52 Width (mm): 42 High (mm): 21 Voltage In (Vdc): 12-24 Ingress Protection: IP20</p>		
		 		

	15MCUV5		1	63,96 €
	Control Unit dimmer MCU-V5 for led monocolor CV 12-24V.		10	45,24 €
		<p>Intensity regulator for leds at constant tension 12-24Vcc max 5A. With 1 cable entry</p> <p>Length (mm): 52 Width (mm): 42 High (mm): 21 Voltage In (Vdc): 12-24 Ingress Protection: IP20</p>		
		 		



SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**






Picture	Article	Description	Lot	Price/Unit
	15MCUV5C		1	55,77 €
		Control Unit dimmer MCU-V5/C no radio for led monocolor CV 12-24V	10	52,91 €
		Intensity regulator for leds at constant tension 12-24Vcc max 5A. Control for 1 cable entry. Without RF Length (mm): 52 Width (mm): 42 High (mm): 21 Voltage In (Vdc): 12~24 Ingress Protection: IP20		
		  		





	15PLANO1224ONE		1	62,01 €
		Control unit PLANO-1224/ONE	10	52,78 €
		Remote control via AppOneSmart Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vdc/ac): 12~24 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		

Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**




Picture	Article	Description	Lot	Price/Unit
	15PLANOMASTER		1	62,28 €
	PLANO-MASTER 12-24V DC LED	Universal controller for led 12-24Vdc. Dimmer, RGB, RGBW, CCT Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+50 Ingress Protection: IP20	10	59,32 €
	15PLANOONE		1	69,62 €
	PLANO-ONE 12-24V DC LED	Universal controller for led 12-24Vdc. Dimmer, RGB, RGBW, CCT Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+50 Ingress Protection: IP20	10	66,30 €




Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15PLANOV5		1	42,04 €
	PLANO-V5 1 channel dimmer receiver monochromatic CV 12-24V		10	40,04 €
		Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Intensidad In (A): 5 Power (W): 60~120 Room Temperature (°C): -20~+50 Ingress Protection: IP20		
			  	




	15PLANOV54BLE		1	70,66 €
	Control unit PLANO-V5/4BLE		10	67,29 €
		4xLed 12-24Vdc. Max 3A por salida. 36W a12V; 72W a 24V por cada salida. Max total 5A. 60W a 12V; 120W a 24V. Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
			 	






Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15PLANOV54CH		1	57,47 €
	PLANO-V5 4CH dimmer receiver 4 channels single color CV CV 12-24V		10	54,73 €
 		Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Intensidad In (A): 5 Power (W): 60~120 Room Temperature (°C): -20~+50 Ingress Protection: IP20		






	15PLANOV5RGBW		1	58,11 €
	PLANO-V5 RGBW dimmer receiver for RGB and RGBW CV 12-24V LED		10	45,24 €
 		Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Intensidad In (A): 5 Power (W): 60~120 Room Temperature (°C): -20~+50 Ingress Protection: IP20		

Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15PLANOV5RGBWBL		1	70,66 €
	Control unit PLANO-V5 RGBW/BLE		10	67,29 €
		Function: Mode 1: RGB. Mode 2: RGBW (W-W), Mode 3: RGBW (W-W + RGB) Length (mm): 80 Width (mm): 80 High (mm): 16 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		






	15TOPV84		1	98,25 €
	Control unit dimmer TOP-V8/4 for led monocolor CV 12-24-36V.		10	93,57 €
		Dimmer for leds at constant voltage 12-24-36 Vdc 4 outputs max 8A per output (max 24A total) With 3 cable entries and input to extend Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		



Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15TOPV8CCT2		1	107,12 €
	Control unit TOP-V8/CCT2 dimmer and Tcolor for led a CV 12-24-36V.		10	102,05 €
		<p>Dimmer for LEDs at constant voltage 12-24-36 Vdc with warm and cold LED. 4 outputs max 8A per output (max 24A total) With 3 cable entries and input to extend</p> <p>Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Room Temperature (°C): -20~+55 Ingress Protection: IP20</p>		
		<p>CE</p> <p> </p>		



	15TOPV8EXT4		1	68,25 €
	Control unit dimmer slave TOP-V8/EXT4 for led monocolor CV 12-24-36V.		10	65,00 €
		<p>Slave dimmer for led to constant tension compatible with master stations TOP-V8 / 4 monocolor</p> <p>Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~24 Room Temperature (°C): -20~+55 Ingress Protection: IP20</p>		
		<p>CE</p> <p> </p>		


Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15TOPV8RGBW		1	98,25 €
	Control unit dimmer TOP-V8/RGBW for led RGB and RGBW CV 12-24-36V		10	93,57 €
		<p>Dimmer for LEDs with constant voltage 12-24-36 Vdc of RGB and RGBW LEDs. 4 outputs max 8A per output (max 24A total) With 3 cable entries and input to extend</p> <p>Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vdc): 12~36 Room Temperature (°C): -20~+55 Ingress Protection: IP20</p>		
		  		

	15WITOP100		1	16,41 €
	Connection wire 1 m. RJ11 for TOP extender		10	15,63 €
		<p>1 meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series</p> <p>Length (mm): 1000</p>		
				


Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15WITOP1000		1	26,17 €
	Connection wire 10 m. RJ11 for TOP extender		10	24,92 €
		10-meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 10000		
				

	15WITOP30		1	13,10 €
	Connection wire 30 cm. RJ11 for TOP extender		10	12,48 €
		30 cm RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 300		
				

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Constant voltage control, Dimmer, RGBW, CCT, DTW**

Picture	Article	Description	Lot	Price/Unit
	15WITOP500		1	21,02 €
		Connection wire 5 m. RJ11 for TOP extender	10	20,02 €



5-meter RJ11 connection cable with mounted connectors for the connection of the master control panel with the extension of the TOP series.

Length (mm): 5000




Catalogue **SMART LIGHTING**
Line **Lighting control by Nexta Tech**
FAMILY **Receivers**
Subfamily **Motors control**

Download Nexta Tech catalogue [here](#).

Picture	Article	Description	Lot	Price/Unit
	15MCU1224		1	42,25 €
	Control unit MCU-1224 12-24Vdc/ac	<p>Single-channel receiver with low voltage power 12-24Vdc / ac. Dry contact output normally open max 1A. Simple programming via dip-switch.</p> <p>Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vdc/ac): 12~24 Intensidad Out (A): 1 Ingress Protection: IP20</p>	10	40,17 €
	15MCUM500		1	50,18 €
	Control Unit MCU-M500 for 1 motor max 500W	<p>Receiver control by RF and cable of 1 motor with power 500W max</p> <p>Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Power (W): 500 Ingress Protection: IP20</p>	10	47,58 €

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Motors control**

Picture	Article	Description	Lot	Price/Unit
	15MCUMONE		1	62,27 €
		Control Unit MCU-M/ONE for 1 motor max 500W	10	50,96 €

Remote control via AppOneSmart

Length (mm): 52 Width (mm): 43 High (mm): 21
Voltage In (Vac): 110~240 Power (W): 500
Room Temperature (°C): -20~+55
Ingress Protection: IP20

