


Catalogue **SMART LIGHTING**
 Line **Casambi Lighting control**
 FAmily **Casambi Dimmer 230V**
 Subfamily **Casambi Dimmer 230V**


Download CASAMBI Bluetooth catalogue [here](#).
Watch CASAMBI video tutorials on [our YouTube channel](#).

Picture	Article	Description	Lot	Price/Unit
	G50541253		1	122,16 €
	Smart Lampholder CASAMBI A800 NIP 230V 25W		5	111,06 €
	Black		10	100,92 €
			20	96,14 €
	M10x1. Use with cable section H03VVH2-F 2x1mm / H03VV-F 2x0.75mm .. With Casambi BLE 4.0 regulation integrated by intelligent device. Type of load: Incandescent / Halogen / LED Retrofit 			
	High (mm): 98,2 Diameter (mm): 33,6 Colour: Black Voltage In (Vac): 220~240 Frecuency (Hz): 50~60 Power (W): 4~25 Room Temperature (°C): +35			
	Reference: 039162			




SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V

Subfamily **Casambi Dimmer 230V**

Picture	Article	Description	Lot	Price/Unit
	G50541254		1	122,16 €
	Smart Lampholder CASAMBI A801 NIP 230V 25W		5	111,06 €
	Black		10	100,92 €
			20	96,14 €
	M10x1. Use with cable section H03VVH2-F 2x1mm / H03VV-F 2x0.75mm .. With Casambi BLE 4.0 regulation integrated by intelligent device. Type of load: Incandescent / Halogen / LED Retrofit 			
	High (mm): 98,2 Diameter (mm): 33,6 Colour: Black Voltage In (Vac): 220~240 Frecuency (Hz): 50~60 Power (W): 4~25 Room Temperature (°C): +35			
	Reference: 040047			




	G50541255		1	122,40 €
	Smart Lampholder CASAMBI A802 NIP 230V 25W		5	111,27 €
	Black		10	101,11 €
			20	96,33 €
	M10x1. Use with cable section H03VVH2-F 2x1mm / H03VV-F 2x0.75mm .. With Casambi BLE 4.0 regulation integrated by intelligent device. Type of load: Incandescent / Halogen / LED Retrofit 			
	High (mm): 98,2 Diameter (mm): 33,6 Colour: Black Voltage In (Vac): 220~240 Frecuency (Hz): 50~60 Power (W): 4~25 Room Temperature (°C): +35			
	Reference: 040048			



SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V

Subfamily **Casambi Dimmer 230V**


Picture	Article	Description	Lot	Price/Unit
	G5031180		1	125,96 €
	Dimable CC-CV plug-in LED power supply CASAMBI		5	114,50 €
	multi-pin 18W black		10	104,10 €
	Dimmable with CASAMBI App and Push. Output 12 or 24Vdc or current from 200mA to 950mA in steps of 50mA programmable by Dip-Switch. Interchangeable plug EU, US, UK, CN, AU, KR and JP. Not included		50	97,31 €
	Length (mm): 122 Width (mm): 59 High (mm): 32 Colour: Black Voltage In (Vac): 100~240 Frecuency (Hz): 50~60 Power (W): 18 Room Temperature (°C): -20~+40 Critical Temperature (°C): 75 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: Push Power factor: >0.95			

Reference: 040645




SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V

Subfamily **Casambi Dimmer 230V**

Picture	Article	Description	Lot	Price/Unit
	AD800820		1	102,00 €
	Casambi Dimmer 85-240V 100W IP30 for independent use		5	92,73 €
			10	88,28 €
	<p>Dimmer to regulate light bulbs and LED modules at mains voltage and dimmable LED power supplies by end-of-phase cutting.</p> <p>Length (mm): 75 Width (mm): 38 High (mm): 22 Colour: White Voltage In (Vac): 85~240 Frecuency (Hz): 50~60 Power (W): 1~100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 75 Ingress Protection: IP30</p>			




	AD800838		1	99,23 €
	Casambi Dimmer 85-240V 100W IP20 to incorporate		5	90,22 €
			10	85,92 €
	<p>Length (mm): 40,4 Width (mm): 36,3 High (mm): 14 Colour: White Voltage In (Vac): 85~240 Frecuency (Hz): 50~60 Power (W): 1~100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 75 Ingress Protection: IP20</p>			




SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V

Subfamily **Casambi Dimmer 230V**

Picture	Article	Description	Lot	Price/Unit
	AD808945		1	235,24 €
	Casambi Dimmer 230V 300W IP20 to incorporate		5	213,85 €
	Casambi Dimmer to regulate dimmable LED bulbs and modules and dimmable LED power supplies by phase cutting.		10	203,66 €
		Length (mm): 51,5 Width (mm): 47,5 High (mm): 31 Colour: White Voltage In (Vac): 220~240 Frequency (Hz): 50~60 Power (W): 3~300 Room Temperature (°C): 0~+50 Critical Temperature (°C): 70 Ingress Protection: IP20		




	G503913		1	78,07 €
	Dimmer Casambi D300IBC 230V 2-300W to incorporate		5	70,98 €
	Casambi dimmer to regulate light bulbs. LED modules and LED power supplies adjustable by phase cutting.		10	67,60 €
		Length (mm): 45 Width (mm): 45 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Intensidad In (A): 1.36 Frequency (Hz): 50~60 Power (W): 2~300 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 50000 Ingress Protection: IP20		



SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V

Subfamily **Casambi Dimmer 230V**

Picture	Article	Description	Lot	Price/Unit
	AD808946		1	265,32 €
	Casambi Dimmer 230V 380W IP20 independent use		5	241,19 €
	Casambi Dimmer to regulate dimmable LED bulbs and modules and dimmable LED power supplies by phase cutting.		10	229,70 €
		Length (mm): 101,5 Width (mm): 51 High (mm): 30 Colour: White Voltage In (Vac): 220~240 Frecuency (Hz): 50~60 Power (W): 3~380 Room Temperature (°C): 0~+28 Critical Temperature (°C): 70 Ingress Protection: IP20		




Catalogue **SMART LIGHTING**
Line **Casambi Lighting control**
FAMily **Dimmer Led for Casambi Interface**
Subfamily **Dimmers Led for Casambi Interface**

Watch CASAMBI video tutorials on [our YouTube channel](#).

Picture	Article	Description	Lot	Price/Unit
	AD800650		1	74,05 €
	Dimmer led CV 12-24V 4 channels DALI control		5	67,33 €
	4x60W(12V) 4x120W(24V)		10	64,13 €

Led regulator at constant voltage 12-24Vdc 4 channels controllable by DALI. 4x60W (12Vdc) 4x120W (24Vdc). Adapted for control by CASAMBI interfaces


Length (mm): 178 Width (mm): 46 High (mm): 20
Colour: White Voltage In (Vdc): 12~24
Frecuency (Hz): 50~60 Power (W): 240~480
Critical Temperature (°C): 75




	AD800651		1	89,06 €
	Dimmer led CV 12-24V 4 channels DALI control		5	77,42 €
	4x96W(12V) 4x192W(24V)		10	73,80 €


Regulador Led constant voltage 12-24Vdc 4 channels controllable by DALI. 4x96W (12Vdc) 4x192W (24Vdc). Adapted for the control of CASAMBI interfaces

Length (mm): 170 Width (mm): 59 High (mm): 29
Colour: White Voltage In (Vdc): 12~24
Frecuency (Hz): 50~60 Power (W): 384~768
Critical Temperature (°C): 75




Catalogue **SMART LIGHTING**
 Line **Casambi Lighting control**
 FAmily **Casambi integrated Led Drivers and Dimmers**
 Subfamily **Casambi integrated Led Drivers**

Picture	Article	Description	Lot	Price/Unit
	AD800578		1	161,15 €
	Casambi Bluetooth DIP Switch DC / CV 25W power supply independent use		5	146,50 €
			10	139,53 €
		350mA (1,8..15W) / 500mA (2,5..22W) / 700mA (3,5..25W) / 12V (1..10W) / 24V 12V (3,1..20W)		
		Length (mm): 149 Width (mm): 68 High (mm): 24 Colour: White Voltage In (Vac): 220~240 Frecuency (Hz): 50~60 Power (W): 1.8~2.5 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Ingress Protection: IP20		



Catalogue **SMART LIGHTING**
 Line **Casambi Lighting control**
 FAmily **Casambi integrated Led Drivers and Dimmers**
 Subfamily **Casambi integrated Led Dimmers**


Picture	Article	Description	Lot	Price/Unit
	AD808948		1	236,57 €
	Dimmer Casambi 10-24V 4 channels CTT/ RGB+W		5	205,73 €
	Led Dimmer with integrated Casambi. Maximum intensity 4.4 A per channel.		10	195,90 €
		Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6 Colour: White Voltage In (Vdc): 10~24 Intensidad Out (A): 4.4 Power (W): 422 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Ingress Protection: IP20		



Catalogue **SMART LIGHTING**
Line **Casambi Lighting control**
FAMILY **Casambi Interface 230V 0-10V**

Subfamily **Casambi Interface 230V 0-10V**

Download **CASAMBI Bluetooth catalogue** [here](#).
Watch **CASAMBI video tutorials** on [our YouTube channel](#).


Picture	Article	Description	Lot	Price/Unit
	AD800670		1	111,36 €
	Casambi Bluetooth Interface 0-10V independent use		5	101,23 €
	Casambi interface for control of feeders with 0-10V input.		10	96,41 €
		Length (mm): 75 Width (mm): 38 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 0~10 Intensidad Out (A): 0.007 Frequency (Hz): 50 Room Temperature (°C): -20~+40 Critical Temperature (°C): 70		



SELV


SMART LIGHTING > Casambi Lighting control > Casambi Interface 230V 0-10V

Subfamily **Casambi Interface 230V 0-10V**

Picture	Article	Description	Lot	Price/Unit
	AD800589		1	95,51 €
	Interface Bluetooth 1-10V to control LED systems		5	86,81 €
			10	82,71 €

To control dimmable LED from tablet or smartphone via Bluetooth, integrated antenna 2,4-2,483GHz

Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Voltage Out (Vdc): 0~10 Intensidad Out (A): 0.007
 Frecuency (Hz): 50 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70 Ingress Protection: IP20



SELV

Catalogue **SMART LIGHTING**


Line **Casambi Lighting control**

FAMILY **Casambi Dimmer 230V DALI**

Subfamily **Casambi Interface DALI monocolor 1 to 4 channels**

Download **CASAMBI Bluetooth catalogue** [here](#).

Watch **CASAMBI video tutorials** on [our YouTube channel](#).

Picture	Article	Description	Lot	Price/Unit
	AD800661		1	111,14 €
	Casambi Bluetooth Interface DALI-4 channels		5	101,04 €
	monocolor independent use		10	96,23 €


For the control of dimmers with DALI input and 4 mono-color output channels.

Length (mm): 75 Width (mm): 38 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70




SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V DALI


Subfamily **Casambi Interface DALI monocolor 1 to 4 channels**

Picture	Article	Description	Lot	Price/Unit
	AD800662		1	106,09 €
	Casambi Bluetooth Interface DALI-2 channels		5	96,42 €
	monocolor independent use		10	91,82 €

For the control of dimmers with DALI input and 2 output channels


Length (mm): 75 Width (mm): 38 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70



	AD800663		1	111,36 €
	Casambi Bluetooth Interface DALI-3 channels		5	101,23 €
	monocolor independent use		10	96,41 €


For the control of dimmers with DALI input and 3 mono-color output channels.

Length (mm): 75 Width (mm): 38 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70




SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V DALI


Subfamily **Casambi Interface DALI monocolor 1 to 4 channels**

Picture	Article	Description	Lot	Price/Unit
	AD800667		1	111,36 €
	Casambi Bluetooth Interface DALI-1 channel independent use		5	101,23 €
			10	96,41 €

For control of feeders with DALI input and 1 output channel.


Length (mm): 75 Width (mm): 38 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70



	AD800681		1	105,00 €
	Casambi Bluetooth Interface DALI-4 channels monocolor built-in housing		5	95,45 €
			10	90,92 €


For the control of dimmers with DALI input and 4 mono-color output channels.

Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70




SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V DALI


Subfamily **Casambi Interface DALI monocolor 1 to 4 channels**

Picture	Article	Description	Lot	Price/Unit
	AD800682		1	105,00 €
	Casambi Bluetooth Interface DALI-2 channels		5	95,45 €
	monocolor built-in housing		10	90,92 €

For the control of dimmers with DALI input and 2 mono-color output channels.


Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70




	AD800683		1	105,00 €
	Casambi Bluetooth Interface DALI-3 channels		5	95,45 €
	monocolor built-in housing		10	90,92 €

For the control of dimmers with DALI input and 4 mono-color output channels.

Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70




Subfamily **Casambi Interface DALI monocolor 1 to 4 channels**


Picture	Article	Description	Lot	Price/Unit
	AD800687		1	94,15 €
	Casambi Bluetooth Interface DALI-1 channel built-in housing		5	85,57 €
			10	81,52 €

For control of feeders with DALI input and 1 output channel.

Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70

Reference: 800687



	AD801590		1	101,63 €
	Casambi DALI 0-10V interface to incorporate configurable		5	92,39 €
			10	87,98 €

Casambi interface for controlling a DALI dimmable LED power supply and a possible combination with a relay or up to two 0-10V dimmable LED power supplies

Length (mm): 76 Width (mm): 26 High (mm): 23
 Voltage In (Vac): 100~240 Voltage Out (Vdc): 0~10
 Intensidad Out (A): 0.007 Frecuency (Hz): 50~60
 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 70 Ingress Protection: IP20



Catalogue **SMART LIGHTING**


Line **Casambi Lighting control**

FAMILY **Casambi Dimmer 230V DALI**

Subfamily **Casambi Interface DALI CCT, RGB, RGB+W**

Download **CASAMBI Bluetooth catalogue** [here](#).


Watch **CASAMBI video tutorials** on [our YouTube channel](#).

Picture	Article	Description	Lot	Price/Unit
	AD800665		1	105,74 €
	Casambi Bluetooth Interface 0-10V DALI independent use configurable		5	96,16 €
		Configurable for 1-4 channels monocolour and CCT,RGC and RGB+W		10
		Length (mm): 75 Width (mm): 38 High (mm): 22 Colour: White Voltage In (V): 220~240 Room Temperature (°C): -20~+40 Critical Temperature (°C): 70 Ingress Protection: IP30		



SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V DALI


Subfamily **Casambi Interface DALI CCT, RGB, RGB+W**

Picture	Article	Description	Lot	Price/Unit
	AD800666		1	100,53 €
	Casambi Bluetooth Interface DALI-4 channels RGB+W independent use		5	91,39 €
			10	87,04 €


For the RGB control with feeders with DALI input

Length (mm): 75 Width (mm): 38 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70

Reference: 800666




SELV

	AD800668		1	111,36 €
	Casambi Bluetooth Interface DALI-2 channels CCT independent use		5	101,23 €
			10	96,41 €

For CCT control, warm and cold light with feeders with DALI input


Length (mm): 75 Width (mm): 38 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70



SELV


SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V DALI

Subfamily **Casambi Interface DALI CCT, RGB, RGB+W**

Picture	Article	Description	Lot	Price/Unit
	AD800669		1	111,36 €
	Casambi Bluetooth Interface DALI-3 channels RGB independent use		5	101,23 €
			10	96,41 €

For the RGB control with feeders with DALI input

Length (mm): 75 Width (mm): 38 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70



SELV

	AD800685		1	96,56 €
	Casambi 0-10V DALI interface to incorporate configurable		5	87,76 €
			10	83,59 €

Configurable for 1-4 channels monocolor and CCT,RGC and RGB+W


Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (V): 220~240
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70 Ingress Protection: IP20



SELV


SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V DALI

Subfamily **Casambi Interface DALI CCT, RGB, RGB+W**


Picture	Article	Description	Lot	Price/Unit
	AD800686		1	105,00 €
	Casambi Bluetooth Interface DALI-4 channels RGB+W built-in housing		5	95,45 €
			10	90,92 €

Para el control RGB con alimentadores con entrada DALI

Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70




SELV

	AD800688		1	105,00 €
	Casambi Bluetooth Interface DALI-2 channels CCT built-in housing		5	95,45 €
			10	90,92 €

For CCT control, warm and cold light with feeders with DALI input


Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70



SELV


SMART LIGHTING > Casambi Lighting control > Casambi Dimmer 230V DALI


Subfamily **Casambi Interface DALI CCT, RGB, RGB+W**

Picture	Article	Description	Lot	Price/Unit
	AD800689		1	105,00 €
	Casambi Bluetooth Interface DALI-3 channels RGB built-in housing		5	95,45 €
			10	90,92 €

For the RGB control with feeders with DALI input


Length (mm): 56,6 Width (mm): 35,8 High (mm): 22,6
 Colour: White Voltage In (Vac): 220~240
 Intensidad Out (A): 0.007 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70



	AD808685		1	124,36 €
	Casambi Bluetooth DALI 230V IP65 interface configurable		5	113,06 €
			10	107,68 €

Casambi interface with IP65 Signal input: Bluetooth 4.0 lite. 0-10V or DALI output

Length (mm): 100 Width (mm): 37 Colour: Black
 Voltage In (Vac): 220~240 Frecuency (Hz): 50
 Room Temperature (°C): -20~+40
 Critical Temperature (°C): 70 Ingress Protection: IP65



Catalogue **SMART LIGHTING**


Line **Casambi Lighting control**

FAMILY **Casambi Dimmer 12V-24V LED Strips**

Subfamily **Casambi Dimmer 12-24V monocolor led stripes 1 to 4 channels**


Download CASAMBI Bluetooth catalogue [here](#).

Watch CASAMBI video tutorials on [our YouTube channel](#).


Picture	Article	Description	Lot	Price/Unit
	AD800382		1	110,88 €
	Casambi Bluetooth Dimmer 12-24V 2 channels		5	100,79 €
	monocolor		10	96,01 €

Control of led strips and LED modules at constant voltage at 12 or 24V

Length (mm): 72,6 Width (mm): 30 High (mm): 18
 Colour: White Voltage In (Vdc): 12~24
 Power (W): 72~144
 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 75





Subfamily **Casambi Dimmer 12-24V monocolor led stripes 1 to 4 channels**

Picture	Article	Description	Lot	Price/Unit
	AD800383		1	110,88 €
	Casambi Bluetooth Dimmer 12-24V 3 channels monocolor		5	100,79 €
			10	96,01 €

Control of led strips and LED modules at constant voltage at 12 or 24V


Length (mm): 72,6 Width (mm): 30 High (mm): 18
 Colour: White Voltage In (Vdc): 12~24
 Power (W): 72~144 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 75



	AD800387		1	120,24 €
	Casambi Bluetooth Dimmer 12-24V 1 channel monocolor		5	109,30 €
			10	104,12 €

Control of led strips and LED modules at constant voltage at 12 or 24V

Length (mm): 72,6 Width (mm): 30 High (mm): 18
 Colour: White Voltage In (Vdc): 12~24
 Power (W): 72~144 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 75



Catalogue **SMART LIGHTING**


Line **Casambi Lighting control**

FAMILY **Casambi Dimmer 12V-24V LED Strips**

Subfamily **Casambi Dimmer 12-24V CCT, RGB, RGB+W led stripes**


Download CASAMBI Bluetooth catalogue [here](#).

Watch CASAMBI video tutorials on [our YouTube channel](#).

Picture	Article	Description	Lot	Price/Unit
	AD800385		1	110,88 €
	Casambi Dimmer 12-24V 4 channels Configurable		5	100,79 €
	Control of led strips and LED modules at constant voltage at 12 or 24V		10	96,01 €
		Length (mm): 72,6 Width (mm): 30 High (mm): 18 Colour: White Voltage In (Vdc): 12~24 Power (W): 72~144 Room Temperature (°C): -20~+45 Critical Temperature (°C): 75		





Subfamily **Casambi Dimmer 12-24V CCT, RGB, RGB+W led stripes**

Picture	Article	Description	Lot	Price/Unit
	AD800386		1	110,88 €
	Casambi Bluetooth Dimmer 12-24V 4 channels RGB+W		5	100,79 €
			10	96,01 €

For the control of RGB + W LED strips and modules


Length (mm): 72,6 Width (mm): 30 High (mm): 18
 Colour: White Voltage In (Vdc): 12~24
 Power (W): 72~144 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 75




	AD800388		1	110,88 €
	Casambi Bluetooth Dimmer 12-24V 2 channels CCT		5	100,79 €
			10	96,01 €

For the control of strips and modules CCT led warm and cold light


Length (mm): 72,6 Width (mm): 30 High (mm): 18
 Colour: White Voltage In (Vdc): 12~24
 Power (W): 72~144 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 75




Subfamily **Casambi Dimmer 12-24V CCT, RGB, RGB+W led stripes**

Picture	Article	Description	Lot	Price/Unit
	AD800389		1	110,88 €
	Casambi Bluetooth Dimmer 12-24V 3 channels RGB		5	100,79 €
	For the control of strips and RGB led modules		10	96,01 €

Length (mm): 72,6 Width (mm): 30 High (mm): 18
 Colour: White Voltage In (Vdc): 12~24
 Power (W): 72~144 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 75



	AD808885		1	136,12 €
	Dimmer Casambi Bluetooth 12-24V 4 chanel multifuntion CCT, RGB, RGB+W		5	123,73 €
	Control of led strips and Led modules at constant voltage at 12 or 24V		10	117,86 €

Control of led strips and Led modules at constant voltage at 12 or 24V

Length (mm): 100 Width (mm): 37 Colour: Black
 Voltage In (Vdc): 12~24 Frecuency (Hz): 400
 Power (W): 72~144 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 75 Ingress Protection: IP65

