


Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Terminal Blocks Nylon**  
 Subfamily **Nylon 2,5mm2-24A terminal blocks**





Picture	Article	Description	Lot	Price/Unit
	491MRS3		1	0,1167 €
	Terminal block OK431-NY 2.5mm 1 pole		50	0,1041 €
		Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel	100	0,0832 €
		Length (mm): 7,25 Width (mm): 16,4 High (mm): 14,5 Section (mm2): 2,5 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw	7000	0,0757 €
	Reference: 4110107			






Subfamily **Nylon 2,5mm<sup>2</sup>-24A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MRS7		1	0,2339 €
	Terminal block OK431-NY 2.5mm 2 poles		50	0,2084 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	0,1667 €
			3000	0,1516 €
		Length (mm): 14,5 Width (mm): 16,4 High (mm): 14,5 Section (mm <sup>2</sup> ): 2,5 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw  Reference: 4110207		
				
				
	491MRS8		1	0,3501 €
	Terminal block OK431-NY 2.5mm 3 poles		50	0,31 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	0,2497 €
			2500	0,2267 €
		Length (mm): 22,5 Width (mm): 16,4 High (mm): 14,5 Section (mm <sup>2</sup> ): 2,5 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw  Reference: 4110307		
				
				


Subfamily **Nylon 2,5mm2-24A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MRS9		1	1,39 €
	Terminal block OK431-NY 2.5mm 12 poles		20	1,26 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	1,01 €
	Length (mm): 94 Width (mm): 16,4 High (mm): 14,5 Section (mm2): 2,5 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw  Reference: 4110007		1200	0,91 €
				
	491MRSC		1	0,2313 €
	Terminal block OK431-NY-F 2.5mm 2 poles		50	0,2062 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	0,1650 €
	Length (mm): 14,5 Width (mm): 16,4 High (mm): 12,3 Section (mm2): 2,5 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw  Reference: 4108407		3000	0,15 €
				

Subfamily **Nylon 2,5mm2-24A terminal blocks**


Picture	Article	Description	Lot	Price/Unit
	491MRT7		1	0,2538 €
	Terminal block OK431-NY 2.5mm 2 poles marking L.N		50	0,2261 €
			100	0,1808 €
			3000	0,1646 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel  Length (mm): 14,5 Width (mm): 16,4 High (mm): 14,5 Section (mm2): 2,5 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw  Reference: 4506907			
				
				
	491MRT8		1	0,3857 €
	Terminal block OK431-NY 2.5mm 3 poles marking L.TT.N		50	0,3439 €
			100	0,2752 €
			2500	0,2503 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel  Length (mm): 22,5 Width (mm): 16,4 High (mm): 14,5 Section (mm2): 2,5 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw  Reference: 4504407			
				
				

Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Terminal Blocks Nylon**  
 Subfamily **Nylon 4mm2-32A terminal blocks**


Picture	Article	Description	Lot	Price/Unit
	491MRS4		1	0,3114 €
	Terminal block OK433-NY 4mm 2 poles		50	0,2774 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	0,2219 €
			3000	0,2018 €
		Length (mm): 17 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw		
	Reference: 4111707			



Subfamily **Nylon 4mm2-32A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MRS5		1	0,4667 €
	Terminal block OK433-NY 4mm 3 poles		50	0,4161 €
			100	0,3328 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		2000	0,3028 €
	Length (mm): 27 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw			
	Reference: 4111807			




	491MRS6		1	1,87 €
	Terminal block OK433-NY 4mm 12 poles		20	1,66 €
			100	1,37 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		450	1,21 €
	Length (mm): 116,7 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw			
	Reference: 4111590			




ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Terminal Blocks Nylon

Subfamily **Nylon 4mm2-32A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MRT4		1	0,3271 €
	Terminal block OK433-NY 4mm 2 poles marking L.N		50	0,2915 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2.		100	0,2332 €
	Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		3000	0,2120 €
		Length (mm): 17 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw		
	Reference: 4503007			




Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Terminal Blocks Nylon**  
 Subfamily **Nylon 10mm2-57A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MR12		1	2,25 €
		Terminal block OK434-NY 10mm 12 poles	20	2,00 €
		Natural polyamide 6-6, Auto-extinguishing UL94V2.	100	1,64 €
		Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel	450	1,42 €
		Length (mm): 139,6 Width (mm): 23,1 High (mm): 20 Section (mm2): 10 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 57 Temperature (°C): 110 Connection: Screw		
		Reference: 4114590		






Subfamily **Nylon 10mm2-57A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MRTA		1	0,3506 €
	Terminal block OK434-NY 10mm 2 poles marking L.N		50	0,3127 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2.		100	0,2503 €
	Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		2300	0,2276 €
		Length (mm): 20,5 Width (mm): 23,1 High (mm): 20 Section (mm2): 10 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 57 Temperature (°C): 110 Connection: Screw		
	Reference: 4504507			






	491MRTB		1	0,5442 €
	Terminal block OK434-NY 10mm 3 poles marking L.TT.N		50	0,4852 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2.		100	0,3881 €
	Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		1400	0,3527 €
		Length (mm): 32,5 Width (mm): 23,1 High (mm): 20 Section (mm2): 10 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 57 Temperature (°C): 110 Connection: Screw		
	Reference: 4504007			







Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Terminal Blocks Nylon**  
 Subfamily **Nylon Plug in connectors**

Picture	Article	Description	Lot	Price/Unit
	B3EN802M		1	0,65 €
	Terminal block male OK431 NY-SPM 2-pole strip		10	0,4364 €
	2,5mm2		100	0,3637 €
			1500	0,3463 €
	Polyamide 6-6 natural.Autoextinguible UL94V2 T110C. T125c x OK431 GWIT775 C (EN60695-2-13)			
	Length (mm): 15 Width (mm): 32,6 High (mm): 15 Section (mm2): 2,5 Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw  Reference: 4161727			
	 			





	B3EN803		1	1,68 €
	Terminal block male-female OK431 NY-SP 3 poles		10	1,13 €
	2.5mm2		100	0,95 €
			1100	0,90 €
	Polyamide 6-6 natural.Autoextinguible UL94V2 T110C. T125c x OK431 GWIT775 C (EN60695-2-13)			
	Length (mm): 23,1 Width (mm): 32,8 High (mm): 14,7 Section (mm2): 2,5 Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw			
				

Subfamily **Nylon Plug in connectors**


Picture	Article	Description	Lot	Price/Unit
	B3EN804		1	2,24 €
	Terminal block male-female OK431 NY-SP 4 poles		10	1,50 €
	2.5mm <sup>2</sup>		50	1,24 €
			750	1,20 €
	Polyamide 6-6 natural.Autoextinguible UL94V2 T110C. T125c x OK431 GWIT775 C (EN60695-2-13)			
	Length (mm): 31,1 Width (mm): 32,8 High (mm): 14,7 Section (mm <sup>2</sup> ): 2,5 Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 110 Connection: Screw			
				

	B3EN902		1	1,46 €
	Terminal block male-female OK433 NY-SP 2 poles		10	0,95 €
	4mm <sup>2</sup>		100	0,81 €
			2000	0,76 €
	Polyamide 6-6 natural.Autoextinguible UL94V2 T110C. T125c x OK431 GWIT775 C (EN60695-2-13)			
	Length (mm): 17,7 Width (mm): 40,2 High (mm): 16,6 Section (mm <sup>2</sup> ): 4 Voltage In (Vac): 450 Intensidad In (A): 28 Temperature (°C): 110 Connection: Screw			
				


Subfamily **Nylon Plug in connectors**

Picture	Article	Description	Lot	Price/Unit
	B3EN903		1	2,18 €
	Terminal block male-female OK433 NY-SP 3 poles		10	1,47 €
	4mm2		50	1,22 €
			700	1,16 €
	Polyamide 6-6 natural.Autoextinguible UL94V2 T110C. T125c x OK431 GWIT775 C (EN60695-2-13)			
	Length (mm): 27,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Voltage In (Vac): 450 Intensidad In (A): 28 Temperature (°C): 110 Connection: Screw			
				
	B3EN904		1	2,91 €
	Terminal block male-female OK433 NY-SP 4 poles		10	1,95 €
	4mm2		100	1,63 €
			500	1,53 €
	Polyamide 6-6 natural.Autoextinguible UL94V2 T110C. T125c x OK431 GWIT775 C (EN60695-2-13)			
	Length (mm): 37,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Voltage In (Vac): 450 Intensidad In (A): 28 Temperature (°C): 110 Connection: Screw			
				

Subfamily **Nylon Plug in connectors**


Picture	Article	Description	Lot	Price/Unit
	B3EN9M3		1	0,92 €
		Terminal block male OK433 NY-SPM 3 poles 4mm	10	0,62 €
		Polyamide 6-6 natural.Autoextinguible UL94V2	100	0,5121 €
		T110C. T125c x OK431 GWIT775 C (EN60695-2-13)	1000	0,4949 €
		Length (mm): 17,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 28 Temperature (°C): 110		




	B3EP902		1	0,88 €
		Terminal block male-female OK433 PLP-SP 3 poles 4mm	100	0,85 €
			1000	0,82 €
		Length (mm): 23,1 Width (mm): 32,9 High (mm): 8 Section (mm2): 4 Voltage In (Vac): 250 Intensidad In (A): 28 Temperature (°C): 120		



Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Terminal Blocks Nylon**  
 Subfamily **High Nylon terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MR25		1	1,89 €
	Terminal block OK200-2-FV-SP		100	1,66 €
			700	1,50 €
		Polyamide PA 6-6 with 25% fiber glass. Auto-extinguishing UL94V2 .Metallic inserts and screws zinc plated steel  Width (mm): 20,4 High (mm): 16,2 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw  Reference: 4194717		




 9911L62	9911L62		1	0,81 €
	Terminal block 1106 L 2 poles		100	0,5337 €
			1500	0,4447 €
		Natural polyamide 6-6 Auto-extinguishing UL94V2 AENOR=250V 2,5mm2-VDE-KEMA=380V.2,5mm2-UR300V.AWG14  Length (mm): 31 Width (mm): 16,5 High (mm): 21,5 Colour: White Voltage In (Vac): 750 Intensidad In (A): 41 Temperature (°C): 110 Connection: Screw		



Subfamily **High Nylon terminal blocks**

Picture	Article	Description	Lot	Price/Unit
 <p>9911L63</p>	9911L63		1	1,21 €
	Terminal block 1106 L 3 poles		50	0,81 €
	Natural polyamide 6-6 Auto-extinguishing UL94V2 AENOR=250V 2,5mm2-VDE-KEMA=380V.2,5mm2-UR300V.AWG15		750	0,67 €
		Length (mm): 31 Width (mm): 26,5 High (mm): 21,5 Colour: White Voltage In (Vac): 750 Intensidad In (A): 41 Temperature (°C): 110 Connection: Screw		
				
	9911L64		1	1,39 €
	Terminal block 1106 L 4 poles		100	0,92 €
	Natural polyamide 6-6 Auto-extinguishing UL94V2 AENOR=250V 2,5mm2-VDE-KEMA=380V.2,5mm2-UR300V.AWG17		500	0,77 €
		Length (mm): 31 Width (mm): 36,5 High (mm): 21,5 Colour: White Voltage In (Vac): 750 Intensidad In (A): 41 Temperature (°C): 110 Connection: Screw		
				

Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Terminal Blocks Nylon**  
 Subfamily **Nylon Fuse Holder terminal blocks**


Picture	Article	Description	Lot	Price/Unit
	491NRR2		1	1,68 €
		Terminal block with fuse holder OK133/2 4mm 2 poles	20	1,50 €
			100	1,24 €
			800	1,11 €
		Polyamide 6-8. Auto-extinguishing UL94V0 GWIT775 C(EN 60695-2-13) Metallic inserts in brass OT58 nickel plated. Screws in zinc plated steel.Fuse holder clip in phosphorous bronze. Fuse pole (5x20) 70° 2.5 mm2 6,3A/250V  Length (mm): 21 Width (mm): 28,5 High (mm): 20,4 Section (mm2): 4 Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 125 Connection: Screw  Reference: 4200262		






ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Terminal Blocks Nylon

Subfamily **Nylon Fuse Holder terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491NRR3		1	1,92 €
		Terminal block with fuse holder OK133/3 4mm 3 poles	20	1,72 €
		Polyamide 6-8. Auto-extinguishing UL94V0. GWIT775 C(EN 60695-2-13) Metallic inserts in brass OT58 nickel plated. Screws in zinc plated steel.Fuse holder clip in phosphorous bronze.Fuse pole (5x20) 70° 2.5 mm2 6,3A/250V	100	1,34 €
		Length (mm): 31 Width (mm): 28,5 High (mm): 20,4 Section (mm2): 4 Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 125 Connection: Screw	600	1,25 €
	Reference: 4200362			









Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Fiber Glass Terminal Blocks**  
 Subfamily **Fiberglass-24A 2.5 mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR17		1	0,2453 €
	Terminal block OK431-FV 2.5mm 2 poles high		50	0,2188 €
	temperature		100	0,1749 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel		3000	0,1590 €
		Length (mm): 14,5 Width (mm): 16,5 High (mm): 14,7 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
	Reference: 4140217			




Subfamily **Fiberglass-24A 2.5 mm<sup>2</sup> terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR18		1	0,3669 €
	Terminal block OK431-FV 2.5mm 3 poles high temperature		50	0,3270 €
			100	0,2617 €
			2500	0,2379 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 22,5 Width (mm): 16,5 High (mm): 14,7 Section (mm <sup>2</sup> ): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4140317			
				
				



	491MR19		1	1,47 €
	Terminal block OK431-FV 2.5mm 12 poles high temperature		20	1,31 €
			100	1,08 €
			1200	0,95 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 94,3 Width (mm): 16,5 High (mm): 14,7 Section (mm <sup>2</sup> ): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4140090			
				
				

Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Fiber Glass Terminal Blocks**  
 Subfamily **Fiberglass-32A 4mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR14		1	0,3383 €
	Terminal block OK433-FV 4mm 2 poles for high temperature		50	0,3015 €
			100	0,2412 €
			3000	0,2192 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel  Length (mm): 17 Width (mm): 20,5 High (mm): 17,9 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw  Reference: 4136217			




Subfamily **Fiberglass-32A 4mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR15		1	0,5060 €
	Terminal block OK433-FV 4mm 3 poles high temperature		50	0,4511 €
			100	0,3609 €
			2000	0,3281 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 27 Width (mm): 20,5 High (mm): 17,9 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw			
	Reference: 4136317			
				
				
	491MRH4		1	0,3384 €
	Terminal block OK433/2 FV-H		50	0,3016 €
			100	0,2412 €
			3000	0,2194 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 19,65 Width (mm): 20,5 High (mm): 19,4 Section (mm2): 4 Colour: Tile Voltage In (V): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw			
	Reference: 41422.17			
				
				






ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Fiber Glass Terminal Blocks



Subfamily **Fiberglass-32A 4mm2 terminal block**



Picture	Article	Description	Lot	Price/Unit
	491MRM4		1	0,3524 €
		Terminal block OK433-FV 4mm 2 poles marking L.N	50	0,3141 €
		high temperature	100	0,2510 €
		Polyamide PA 6-6 with 25% fiber	3000	0,2283 €
		glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel		
		Length (mm): 17 Width (mm): 20,5 High (mm): 17,4 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw		
		Reference: 4503017		





Catalogue **ELECTRICAL EQUIPMENT**  
Line **Terminal Blocks and Junction Boxes**  
FAMily **Fiber Glass Terminal Blocks**



Picture	Article	Description	Lot	Price/Unit
	B3RE802F		1	0,3173 €
	Terminal block female OK431 FV-SPF 2 poles 2,5mm2.		10	0,2115 €
			100	0,1763 €
			1500	0,1677 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 16 Width (mm): 16,3 High (mm): 15 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4170228			
				
	B3RE802M		1	0,68 €
	Terminal block male OK431 FV-SPM 2 poles 2,5mm2.		10	0,4529 €
			100	0,3774 €
			1500	0,3595 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 16 Width (mm): 16,3 High (mm): 15 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4170227			
				


Picture	Article	Description	Lot	Price/Unit
	B3RE803		1	1,72 €
	Terminal block male-female OK431 FV-SP 3 poles		10	1,14 €
	2.5mm2		100	0,95 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		1500	0,91 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 23,1 Width (mm): 32,8 High (mm): 14,7			
	Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450			
	Intensidad In (A): 24 Temperature (°C): 150			
	Connection: Screw			
				

	B3RE804		1	2,34 €
	Terminal block male-female OK431 FV-SP 4 poles		10	1,57 €
	2.5mm2		50	1,31 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		750	1,22 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 31,1 Width (mm): 32,8 High (mm): 14,7			
	Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450			
	Intensidad In (A): 24 Temperature (°C): 150			
	Connection: Screw			
				











Picture	Article	Description	Lot	Price/Unit
	B3RE902		1	1,43 €
	Terminal block male-female OK433 FV-SP 2 poles		10	0,95 €
	4mm2		100	0,79 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		1000	0,75 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 17,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
				

	B3RE903		1	2,18 €
	Terminal block male-female OK433 FV-SP 3 poles		10	1,46 €
	4mm2		100	1,21 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		700	1,13 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 27,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
				





Picture	Article	Description	Lot	Price/Unit
	B3RE904		1	2,86 €
	Terminal block male-female OK433 FV-SP 4 poles		10	1,90 €
	4mm <sup>2</sup>		100	1,57 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)		500	1,52 €
	Length (mm): 37,7 Width (mm): 40,2 High (mm): 16,6 Section (mm <sup>2</sup> ): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			



Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Terminal Blocks**  
 Subfamily **End Terminal Blocks**









Picture	Article	Description	Lot	Price/Unit
	491MR00		1	1,90 €
	Terminal block 2,5mm 10 poles		10	1,69 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		25	1,37 €
			450	1,21 €
	Length (mm): 109 Width (mm): 18 High (mm): 20 Diameter (mm): 4 Section (mm2): 2,5 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw			
				
	491MR01		1	2,64 €
	Terminal block 6mm 10 poles		10	2,35 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		25	1,89 €
			450	1,72 €
	Length (mm): 138 Width (mm): 22 High (mm): 25 Diameter (mm): 6 Section (mm2): 6 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw			
				

Subfamily **End Terminal Blocks**

Picture	Article	Description	Lot	Price/Unit
	491MR02		1	4,88 €
	Terminal block 10mm 10 poles		5	4,34 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		10	3,48 €
			300	3,17 €
	Length (mm): 158 Width (mm): 26 High (mm): 29 Diameter (mm): 7,5 Section (mm2): 10 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw			
				





	491MR03		1	0,1772 €
	Terminal block 1.5mm 1 pole		50	0,1580 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		100	0,1264 €
			2400	0,1149 €
	Width (mm): 16 High (mm): 15 Diameter (mm): 10 Section (mm2): 1,5 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw			
				

Subfamily **End Terminal Blocks**

Picture	Article	Description	Lot	Price/Unit
	491MR04		1	2,29 €
	Terminal block 4mm 10 poles		10	2,04 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		25	1,63 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		450	1,48 €
		Length (mm): 116 Width (mm): 20 High (mm): 22 Diameter (mm): 4,5 Section (mm2): 4 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw		
				
	491MR05		1	5,99 €
	Terminal block 16mm 5 poles		5	5,34 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		10	4,28 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		240	3,87 €
		Length (mm): 100 Width (mm): 31 High (mm): 35 Diameter (mm): 9,5 Section (mm2): 16 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw		
				


ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Terminal Blocks

Subfamily **End Terminal Blocks**


Picture	Article	Description	Lot	Price/Unit
	491MR06		1	1,56 €
	Terminal block 1.5mm 10 poles		10	1,38 €
	Transparent polycarbonate. Auto-extinguishing UL92V2		25	1,09 €
			450	1,01 €
		Length (mm): 90 Width (mm): 16 High (mm): 15 Diameter (mm): 3,2 Section (mm2): 1,5 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw		
		 		

	491MR07		1	3,73 €
	Terminal block 25mm 1 pole		10	3,33 €
	Transparent polycarbonate. Self-extinguishing UL92V3		50	2,65 €
			100	2,42 €
		Width (mm): 40 High (mm): 39 Diameter (mm): 12 Section (mm2): 25 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw		
		 		

Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Terminal Blocks Porcelain**  
 Subfamily **Porcelain Terminal Blocks**


Picture	Article	Description	Lot	Price/Unit
	491RP03		1	2,07 €
	Porcelain 3-pole terminal strip		10	1,73 €
			100	1,14 €
	Cable section 4mm. Temp. body 800°C. Temp. contacts 350°C. Galvanized steel screws		500	1,09 €
	Length (mm): 33 Width (mm): 18 High (mm): 16 Colour: White Voltage In (Vac): 450 Intensidad In (A): 5~32			




	AR7560010		1	0,96 €
	Porcelain terminal block 6001 1 pole		100	0,61 €
			1000	0,4672 €
	Soapstone insulating body. For cables up to 2.5mm <sup>2</sup>		2000	0,4540 €
	Length (mm): 10,5 Width (mm): 17,5 High (mm): 14,5 Section (mm <sup>2</sup> ): 2,5 Colour: White Connection: Screw Reference: 025716			

ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Terminal Blocks Porcelain

Subfamily **Porcelain Terminal Blocks**

Picture	Article	Description	Lot	Price/Unit
	AR7560020		1	1,74 €
	Porcelain terminal block 6002 2 poles		10	1,11 €
	Soapstone insulating body. For cables up to 2.5mm2		100	0,85 €
			1000	0,82 €
	Length (mm): 23 Width (mm): 17,5 High (mm): 15 Section (mm2): 2,5 Colour: White Connection: Screw  Reference: 025717			









	AR7560031		1	3,46 €
	Porcelain terminal block 6003-N 3 poles		10	2,16 €
	Soapstone insulating body. For cables up to 2.5mm2		100	1,64 €
			1000	1,63 €
	Length (mm): 34 Width (mm): 18,5 High (mm): 25 Connection: Screw  Reference: 036649			










Subfamily **Standard Junction Boxes**



Picture	Article	Description	Lot	Price/Unit
	4960001		1	1,05 €
		Connecting box 3 poles 1.5mm	100	0,64 €
		Nylon 6.6. PVC sleeve 75mm 100°. Closing by pressure. Terminals 1.5mm <sup>2</sup> mounted included cable clamp	1000	0,5574 €
			3000	0,5162 €
		Length (mm): 49 Width (mm): 26 High (mm): 12 Section (mm <sup>2</sup> ): 1,5 Colour: White Voltage In (Vac): 250 Intensidad In (A): 4 Temperature (°C): 140 Ingress Protection: IP20		
		 		
	4960002		1	0,78 €
		Connecting box 2 poles 1.5mm without sleeve	100	0,4745 €
		Nylon 6.6 without sleeve 100° Closing by pressure, terminals 1.5mm <sup>2</sup> mounted included cable clamp	1000	0,4126 €
			3000	0,3819 €
		Length (mm): 42 Width (mm): 24 High (mm): 12 Section (mm <sup>2</sup> ): 1,5 Colour: White Voltage In (Vac): 250 Intensidad In (A): 4 Temperature (°C): 110		
		 		

Subfamily **Standard Junction Boxes**









Picture	Article	Description	Lot	Price/Unit
	4960003		1	0,92 €
	Connecting box 3 poles 1.5mm without sleeve		100	0,5651 €
	Nylon 6.6. Closing by pressure. mounted terminals 1.5mm <sup>2</sup> included cable clamp		1000	0,4914 €
	Length (mm): 42 Width (mm): 24 High (mm): 12 Section (mm <sup>2</sup> ): 1,5 Colour: White Voltage In (Vac): 250 Intensidad In (A): 4 Temperature (°C): 110		3000	0,46 €
				

	4960004		1	0,1850 €
	Rubber tube for connection box		100	0,1028 €
	Rubber tube to incorporate in isolation box 2 - 3 poles		1000	0,0935 €
	Length (mm): 75 Colour: Black		3000	0,0889 €











Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Junction Boxes**  
 Subfamily **MATE-N-LOK Junction Boxes**

Picture	Article	Description	Lot	Price/Unit
	T340F00		1	0,3921 €
	CAJA PORTAHEMBRA 4 VIAS MATE-N-LOK		1000	0,3563 €
		Female Nylon Housing 4 ways and one row for Universal MATE-N-LOK contacts. Pitch 6.35mm. No contacts.  Length (mm): 27 Width (mm): 27,4 High (mm): 13,4 Colour: Natural Voltage In (V): 600 Temperature (°C): 125		
	T341F05		1	0,3934 €
	CAJA PORTAMACHO 4 VIAS MATE-N-LOK		1000	0,3575 €
		Female Nylon Housing 4 ways and one row for Universal MATE-N-LOK contacts. Pitch 6.35mm. No contacts.  Length (mm): 27,43 Width (mm): 26,6 High (mm): 14,7 Voltage In (V): 600 Temperature (°C): 125		







Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Junction Boxes**  
 Subfamily **Junction Boxes Ip44**

Picture	Article	Description	Lot	Price/Unit
	496008A		1	1,66 €
	Connection box OK603/2 2 poles 1.5mm. IP44 class II cable gland		10	1,14 €
			100	1,01 €
			300	0,96 €
	Class II PA66 Polyamide, Auto-extinguishing UL94V2. conection terminal included, cable clamp			
	Length (mm): 67 Width (mm): 40 High (mm): 13,4 Section (mm2): 1,5 Colour: White Voltage In (Vac): 450 Intensidad In (A): 17.5 Temperature (°C): 105 Connection: Screw Ingress Protection: IP44			
	Reference: 4617795			
	  			
	4960013		1	1,17 €
	Boîte de connexion OK603/3 3 pôles 1,5mm. IP44 classe II blanc pour câ		10	0,81 €
			100	0,70 €
			300	0,65 €
	Class II Polyamide PA66, self-extinguishing UL94V2. Includes connection strip. Without cable gland			
	Length (mm): 57,5 Width (mm): 31 High (mm): 13,4 Section (mm2): 1,5 Colour: White Voltage In (Vac): 450 Intensidad In (A): 17.5 Temperature (°C): 105 Ingress Protection: IP44			
	  			




Subfamily **Junction Boxes Ip44**




Picture	Article	Description	Lot	Price/Unit
 	4960014		1	2,46 €
	Connection box OK603/3 3 poles 1.5mm. IP44 classe II white cable plate		10	1,68 €
			100	1,46 €
			300	1,35 €
	Class II Polyamide PA66, self-extinguishing UL94V2. Includes connection strip. With 2 cable glands			
	Length (mm): 57,5 Width (mm): 31 High (mm): 13,4 Section (mm2): 1,5 Colour: White Voltage In (Vac): 450 Intensidad In (A): 17.5 Temperature (°C): 105 Ingress Protection: IP44			
	Reference: 4624694			
	  			
 	4960008		1	1,38 €
	Connection box OK603/2 2 poles 1.5mm. IP44 class II white		10	0,95 €
			100	0,85 €
			300	0,79 €
	Class II PA66 Polyamide Auto-extinguishing UL94V2. Terminal included, fixation with 4 screws M3			
	Length (mm): 57,5 Width (mm): 31 High (mm): 13,4 Section (mm2): 1,5 Colour: White Voltage In (Vac): 450 Intensidad In (A): 17.5 Temperature (°C): 105 Ingress Protection: IP44			
	Reference: 4619700			
	  			

Subfamily **Junction Boxes Ip44**

Picture	Article	Description	Lot	Price/Unit
  	4960009		1	1,43 €
		Connecting box OK603/3 3 poles 1.5mm IP44 white	10	0,99 €
		Polyamide PA66, self-extinguishing UL94V2. Includes 3-pole connection strip and rubbers for IP44. without cable gland	100	0,88 €
		Length (mm): 57,5 Width (mm): 31 High (mm): 13,4 Section (mm2): 1,5 Colour: White Voltage In (Vac): 450 Intensidad In (A): 17.5 Temperature (°C): 105 Ingress Protection: IP44  Reference: 4619600	300	0,82 €
		  		




Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **UL Connectors**  
 Subfamily **UL Connectors**

Picture	Article	Description	Lot	Price/Unit
	E50344Y		1	1,16 €
	Electrical UL connector yellow		100	0,76 €
	For cables : 5-8 AWG22, 4-6 AWG20, 2-5 AWG18 and 2-3 AWG16		1000	0,69 €
			2000	0,60 €
	Width (mm): 27 High (mm): 10 Colour: Yellow Voltage In (Vac): 600 Temperature (°C): 105			
	 			



	E50345R		1	1,20 €
	Electrical UL connector red		100	0,79 €
	For cables : 9AWG18, 4-6 AWG16, 2-5 AWG14, 2-5 AWG12 and 1-3 AWG10		500	0,72 €
			1000	0,64 €
	Width (mm): 30 High (mm): 14 Colour: Red Voltage In (Vac): 600 Temperature (°C): 105			
	 			






Subfamily **UL Connectors**




Picture	Article	Description	Lot	Price/Unit
	E50346G		1	1,73 €
	Electrical UL connector grey		100	1,16 €
	For cables : 3-7 AWG14, 2-6 AWG12, 2-4 AWG10 and 2AWG8		1000	1,05 €
			2000	0,92 €
	Width (mm): 33 High (mm): 18 Colour: Grey Voltage In (Vac): 600 Temperature (°C): 105			
	 			

Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 Family **Compact screwless connectors**  
 Subfamily **Compact screwless connectors**


Picture	Article	Description	Lot	Price/Unit
	4933901	Quick connector for double telephone connection	100 (Pedido mínimo)	0,1313 €
	Material: Polypropylene. Insert connection: Copper Internal diameter of the cable: From 0.4 to 0.7mm. Cable outer diameter: 1.5mm max. Insulation: 1x105 MO Dielectric: At 1400V for 60s (No arc)"  Length (mm): 15 High (mm): 8 Colour: Yellow			
	49B212411		1	1,29 €
		2-conductor connector for 4mm2 linear installation	60	0,83 €
		Width (mm): 8,1 High (mm): 8,9 Colour: Transparent	120	0,75 €
		Voltage In (V): 450 Intensidad In (A): 32 Temperature (°C): 85 Room Temperature (°C): -60~+105	600	0,72 €
				

Subfamily **Compact screwless connectors**


Picture	Article	Description	Lot	Price/Unit
	CDMOR412		1	0,75 €
		Universal terminal 2 poles Wago 221-412 Transparent	50	0,5187 €
		For rigid or flexible cables 0.2-4mm <sup>2</sup> ; 24-12AWG. T85°C	100	0,4232 €
		Length (mm): 18,6 Width (mm): 13,1 High (mm): 8,3 Voltage In (Vac): 450 Intensidad In (A): 32		
				

	CDMOR413		1	0,99 €
		Universal terminal 3 poles Wago 221-413 Transparent	50	0,68 €
		For rigid or flexible cables 0.2-4mm <sup>2</sup> ; 24-12AWG. T85°C	100	0,5324 €
		Length (mm): 18,6 Width (mm): 18,7 High (mm): 8,3 Voltage In (Vac): 450 Intensidad In (A): 32		
				

Subfamily **Compact screwless connectors**


Picture	Article	Description	Lot	Price/Unit
	CDMOR415		1	1,51 €
		Universal terminal 5 poles Wago 221-415 Transparent	50	1,05 €
		For rigid or flexible cables 0.2-4mm <sup>2</sup> ; 24-12AWG. T85°C	100	0,85 €
		Length (mm): 18,6 Width (mm): 29,9 High (mm): 8,3 Voltage In (Vac): 450 Intensidad In (A): 32		



	493Q008		1	1,77 €
		Compact screwless connector for rigid cable 1.5-2.5mm <sup>2</sup> -8 contacts	50	1,17 €
		For rigid cables of section 1.5-2.5mm <sup>2</sup> VDE 600V, 24A. UL 600V	100	1,03 €
		Length (mm): 20,5 Width (mm): 39,2 High (mm): 9,1 Colour: Green Voltage In (V): 300 Intensidad In (A): 20	500	0,99 €

ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Compact screwless connectors

Subfamily **Compact screwless connectors**

Picture	Article	Description	Lot	Price/Unit
	493W002		1	0,77 €
	Compact screwless connector for cable 0.20-2.5mm2		50	0,5106 €
	- 2 contacts		100	0,4441 €
	For rigid and flexible cables section 0.20-2.5mm (AWG 24-14). Rigid cables do not require the operation of the opening and closing lever. VDE 450V, 24A, T80. UL 600V, 20A, T105		500	0,4219 €
	Colour: Transparent			