


Catalogue **LED TECHNOLOGY**
 Line **Electronic Led Power Supplies**
 FAmily **Led Controllers**
 Subfamily **Control led mirrors**


Download [here](#) the **Catalogue of Led Components for Mirrors: Constant voltage cv12-24v led power supplies and dimmers for mirrors.**

Picture	Article	Description	Lot	Price/Unit
	G508TS01A		1	6,08 €
	Dimmer AEK-TS-01A 1 touch sensor for mirrors		5	5,07 €
	Recommended maximum mirror thickness 5mm. Install sensor before power up. 5 year warranty		10	4,68 €
			100	4,29 €
		Length (mm): 56 Width (mm): 67 High (mm): 11 Colour: White Voltage In (Vdc): 12~24 Voltage Out (Vdc): 12~24 Intensidad Out (A): 5 Power (W): 60~120 Room Temperature (°C): +35 Critical Temperature (°C): 45 Life (Hours): 50000 Ingress Protection: IP20		

LETARON




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G508TS02		1	8,58 €
	Dimmer AEK-TS-02 2 touch sensors for mirrors		5	7,15 €
	Recommended maximum mirror thickness 5mm. Install sensor before power up. 5 year warranty		10	6,50 €
			100	6,24 €
	Length (mm): 76 Width (mm): 40,7 High (mm): 11 Colour: White Voltage In (Vdc): 12~24 Voltage Out (Vdc): 12~24 Intensidad Out (A): 5 Power (W): 60~120 Room Temperature (°C): +35 Critical Temperature (°C): 45 Life (Hours): 50000 Ingress Protection: IP20			

LETARON




	G508TS03A		1	9,83 €
	Dimmer AEK-TS-03A 3 touch sensors for mirrors		5	8,19 €
	Recommended maximum mirror thickness 5mm. Install sensor before power up. 5 year warranty		10	7,41 €
			100	7,02 €
	Length (mm): 93 Width (mm): 67 High (mm): 11 Colour: White Voltage In (Vdc): 12~24 Voltage Out (Vdc): 12~24 Intensidad Out (A): 5 Power (W): 60~120 Room Temperature (°C): +35 Critical Temperature (°C): 45 Life (Hours): 50000 Ingress Protection: IP20			

LETARON





LED TECHNOLOGY > Electronic Led Power Supplies > Led Controllers

Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G508HC01		1	3,43 €
	Electronic relay AEK-HC-01 for On / Off anti-fog mirrors		10	2,86 €
			50	2,60 €
	5 year warranty		300	2,47 €
	Length (mm): 39 Width (mm): 22 High (mm): 14 Colour: White Voltage In (Vdc): 12~24 Voltage Out (Vac): 120~240 Intensidad In (A): 0.025 Intensidad Out (A): 1 Power (W): 120~240 Room Temperature (°C): +35 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20			

LETARON




	G5030015C		1	9,57 €
	Led Power Supply CV AED15-12VLSTB-IP44 12V 15W		5	7,94 €
			10	7,22 €
	ECO ERP design Constant voltage output 12Vdc		100	6,72 €
	Length (mm): 145 Width (mm): 41 High (mm): 13,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~15 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO			

LETARON




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031015C		1	10,27 €
	Led Power Supply CV AED15-24VLSTB-IP44 24V 15W		5	8,52 €
			10	7,74 €
			100	7,22 €
	ECO Design ERP. 24Vdc constant voltage output			
	Length (mm): 145 Width (mm): 41 High (mm): 13,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.625 Frecuency (Hz): 50~60 Power (W): 0~15 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO			

LETARON




	G5030020A		1	12,68 €
	Led Power Supply CV AED20-12VLSTB-IP44 12V 20W		5	10,56 €
			10	9,61 €
			100	8,97 €
	ECO Design ERP. 12Vdc constant voltage output			
	Length (mm): 145 Width (mm): 41 High (mm): 13,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 1.67 Frecuency (Hz): 50~60 Power (W): 0~20 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

LETARON



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030020B		1	22,02 €
	Led Power Supply CV AED20-12VIP44-3A-Q3 12V 20W		5	18,36 €
			10	16,69 €
			100	15,60 €
		Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.		
		Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 1.67 Frecuency (Hz): 50~60 Power (W): 0~20 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.85		

LETARON




	G5031020A		1	22,02 €
	Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W		5	18,36 €
			10	16,69 €
			100	15,60 €
		Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.		
		Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.83 Frecuency (Hz): 50~60 Power (W): 0~20 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.85		


LETARON



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030030E		1	13,56 €
	Led Power Supply CV AED30-12VLSTB-IP44 12V 30W		5	11,30 €
			10	10,27 €
			100	9,59 €
	ECO Design ERP. 12Vdc constant voltage output			
	Length (mm): 171 Width (mm): 54 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 2.5 Frequency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): +40 Critical Temperature (°C): 80 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			




	G5030030G		1	15,57 €
	Led power supply CV AED30-12VIP44-3A 12V 30W cable and relay		5	12,97 €
			10	11,79 €
			100	11,02 €
	ECO ERP Design. Constant voltage output 12Vdc. Cabling. Built-in relay			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 2.5 Frequency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			




LED TECHNOLOGY > Electronic Led Power Supplies > Led Controllers

Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030030H		1	14,11 €
	Led power supply CV AED30-12VIP44-3B 12V 30W		5	11,75 €
	wired		10	10,69 €
	ECO ERP Design. Constant voltage output 12Vdc.		100	9,98 €
	Cabling.			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5			
	Colour: White Voltage In (Vac): 220~240			
	Voltage Out (Vdc): 12 Intensidad Out (A): 2.5			
	Frecuency (Hz): 50~60 Power (W): 0~30			
	Room Temperature (°C): -20~+40			
	Critical Temperature (°C): 80 Life (Hours): 30000			
	Ingress Protection: IP44 Power factor: 0.9			

LETARON




	G5031030E		1	13,56 €
	Led Power Supply CV AED30-24VLSTB-IP44 24V		5	11,30 €
	30W		10	10,27 €
	ECO Design ERP.24Vdc constant voltage output		100	9,59 €
	Length (mm): 171 Width (mm): 54 High (mm): 16			
	Colour: White Voltage In (Vac): 220~240			
	Voltage Out (Vdc): 24 Intensidad Out (A): 1.25			
	Frecuency (Hz): 50~60 Power (W): 0~30			
	Room Temperature (°C): -20~+40			
	Critical Temperature (°C): 80 Ingress Protection: IP44			
	Dimmable: NO Power factor: 0.9			

LETARON




LED TECHNOLOGY > Electronic Led Power Supplies > Led Controllers

Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031030G		1	15,57 €
	Led power supply CV AED30-24VIP44-3A 24V 30W cable and relay		5	12,97 €
			10	11,79 €
			100	11,02 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling. Built-in relay.			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			

LETARON




	G5031030H		1	14,11 €
	Led power supply CV AED30-24V IP44-3B 24V 30W wired		5	11,75 €
			10	10,69 €
			100	9,98 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			

LETARON



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031036		1	16,93 €
	Led Power Supply CV AED36-24VLSTB-UL 24V 36W		5	15,39 €
			10	13,99 €
	24Vdc constant voltage output		50	13,08 €
	Length (mm): 220 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 108~132 Voltage Out (Vdc): 24 Intensidad Out (A): 1.5 Frecuency (Hz): 57~63 Power (W): 0~36 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Dimmable: NO			

LETARON




	G5030040A		1	18,17 €
	Led Power Supply AED40-12VLSTB-IP44 12V 40W		5	15,15 €
			10	13,77 €
	ECO Design ERP Compliant. 12Vdc constant voltage output		100	12,87 €
	Length (mm): 220 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Frecuency (Hz): 50~60 Power (W): 0~40 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

LETARON



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030040B		1	25,71 €
	Led Power Supply CV AED40-12VIP44-3A-Q3 12V 40W		5	21,42 €
			10	19,47 €
			100	18,20 €
	Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.			
	Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 3.33 Frecuency (Hz): 50~60 Power (W): 0~40 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.90			

LETARON




	G5031040B		1	25,71 €
	Led Power Supply CV AED40-24VIP44-3A-Q3 24V 40W		5	21,42 €
			10	19,47 €
			100	18,20 €
	Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.			
	Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.67 Frecuency (Hz): 50~60 Power (W): 0~40 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.90			

LETARON




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030060C		1	20,71 €
	Led Power Supply CV AED60-12VLSTB-IP44 12V 60W		5	18,82 €
			10	17,12 €
			50	16,00 €
	ECO Design ERP Compliant. 12Vdc constant voltage output			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 0~5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): +40 Critical Temperature (°C): 80 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

LETARON




	G5030060E		1	21,18 €
	Led Power Supply CV AED60-12VLSTB-UL 120Vac 12Vdc 60W		5	19,25 €
			10	17,50 €
			50	16,35 €
	Constant voltage output 12Vdc			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 108~135 Voltage Out (Vdc): 12 Intensidad Out (A): 5 Frecuency (Hz): 57~63 Power (W): 0~60 Room Temperature (°C): +40 Critical Temperature (°C): 80 Life (Hours): 30000 Dimmable: NO			

LETARON




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030060F		1	33,49 €
	Led Power Supply CV AED60-12VIP44-3A-Q3 12V 60W		5	27,91 €
			10	25,38 €
			100	23,71 €
	Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.			
		Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.90		

LETARON




	G5030060G		1	22,62 €
	Led power supply CV AED60-12VIP44-3A 12V 60W cable and relay		5	18,85 €
			10	17,13 €
			100	16,02 €
	ECO ERP Design. Constant voltage output 12Vdc. Cabling. Built-in relay			
		Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90		

LETARON



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030060H		1	21,15 €
	Led power supply CV AED60-12V IP44-3B 12V 60W wired		5	17,63 €
			10	16,03 €
			100	14,98 €
	ECO ERP Design. Constant voltage output 12Vdc. Cabling.			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

LETARON




	G5031060D		1	20,71 €
	Led Power Supply CV AED60-24VLSTB-IP44 24V 60W		5	18,82 €
			10	17,12 €
			50	16,00 €
	24Vdc constant voltage output			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

LETARON



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031060E		1	21,44 €
	Led Power Supply CV AED60-24VLSTB-UL 24V 60W		5	19,49 €
			10	17,71 €
	24Vdc constant voltage output		50	16,55 €
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 108~132 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 57~63 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Dimmable: NO			

LETARON




	G5031060H		1	33,49 €
	Led Power Supply CV AED60-24VIP44-3A-Q3 24V 60W		5	27,91 €
			10	25,38 €
	Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.		100	23,71 €
	Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.90			

LETARON




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031060J		1	22,62 €
	Led power supply CV AED60-24VIP44-3A 24V 60W cable and relay		5	18,85 €
			10	17,13 €
			100	16,02 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling. Built-in relay.			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

LETARON








	G5031060K		1	21,15 €
	Led power supply CV AED60-24V IP44-3B 24V 60W wired		5	17,63 €
			10	16,03 €
			100	14,98 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling.			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

LETARON



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G505609		1	22,45 €
	Tactile Sensor Mirror CM-BC KZQ-low voltage class III		5	20,41 €
			10	18,59 €
			50	17,88 €
	Use behind mirrors. Recommended thickness of the mirror less than 5mm. Memory function DC12V 2x30W. DC24V 2x60W. Optional use TS-002 in 12 or 24V to synchronize the On / Off of an anti-fog heater.			
	Length (mm): 98 Width (mm): 40 High (mm): 11 Voltage In (Vdc): 12~24 Power (W): 60~120 Room Temperature (°C): -20~+35 Critical Temperature (°C): 45 Ingress Protection: IP20			
	  			

	G505614		1	7,22 €
	Accessory TS-002 for KZQ-CM-BC 24VDC		5	6,02 €
			10	5,47 €
		Used with G505609 touch sensor for KZQ-CM-BC mirrors to synchronize the anti-fog On / Off	50	5,20 €
	Voltage In (Vdc): 24 Ingress Protection: IP20			
	 			



LED TECHNOLOGY > Electronic Led Power Supplies > Led Controllers

Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G505616		1	1,22 €
		0.325m cable with 3 pins Mini Plug for KZQ-CM-BC	10	1,01 €
		0.325 meter cable with 3 pins for Dimmer with Touch	20	0,94 €
		Sensor for mirrors KZQ-CM-BC	100	0,88 €

