


Catalogue **LED TECHNOLOGY**  
 Line **Electronic Led Power Supplies**  
 FAmily **Led Controllers**  
 Subfamily **Control led mirrors**


Download [here](#) the **Catalogue of Led Components for Mirrors: Constant voltage cv12-24v led power supplies and dimmers for mirrors.**

Picture	Article	Description	Lot	Price/Unit
	G508TS01A		1	6,08 €
	Dimmer AEK-TS-01A 1 touch sensor for mirrors		5	5,07 €
	Recommended maximum mirror thickness 5mm. Install sensor before power up. 5 year warranty		10	4,68 €
			100	4,29 €
		Length (mm): 56 Width (mm): 67 High (mm): 11 Colour: White Voltage In (Vdc): 12~24 Voltage Out (Vdc): 12~24 Intensidad Out (A): 5 Power (W): 60~120 Room Temperature (°C): +35 Critical Temperature (°C): 45 Life (Hours): 50000 Ingress Protection: IP20		

**LETARON**




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G508TS02		1	8,58 €
	Dimmer AEK-TS-02 2 touch sensors for mirrors		5	7,15 €
	Recommended maximum mirror thickness 5mm. Install sensor before power up. 5 year warranty		10	6,50 €
			100	6,24 €
	Length (mm): 76 Width (mm): 40,7 High (mm): 11 Colour: White Voltage In (Vdc): 12~24 Voltage Out (Vdc): 12~24 Intensidad Out (A): 5 Power (W): 60~120 Room Temperature (°C): +35 Critical Temperature (°C): 45 Life (Hours): 50000 Ingress Protection: IP20			

**LETARON**




	G508HC01		1	3,43 €
	Electronic relay AEK-HC-01 for On / Off anti-fog mirrors		10	2,86 €
			50	2,60 €
	5 year warranty		300	2,47 €
	Length (mm): 39 Width (mm): 22 High (mm): 14 Colour: White Voltage In (Vdc): 12~24 Voltage Out (Vac): 120~240 Intensidad In (A): 0.025 Intensidad Out (A): 1 Power (W): 120~240 Room Temperature (°C): +35 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20			

**LETARON**



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031015C		1	10,27 €
	Led Power Supply CV AED15-24VLSTB-IP44 24V 15W		5	8,52 €
			10	7,74 €
			100	7,22 €
	ECO Design ERP. 24Vdc constant voltage output			
	Length (mm): 145 Width (mm): 41 High (mm): 13,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.625 Frecuency (Hz): 50~60 Power (W): 0~15 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO			

**LETARON**




	G5031020A		1	22,02 €
	Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W		5	18,36 €
			10	16,69 €
			100	15,60 €
	Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.			
	Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.83 Frecuency (Hz): 50~60 Power (W): 0~20 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.85			


**LETARON**



Subfamily **Control led mirrors**


Picture	Article	Description	Lot	Price/Unit
	G5030030E		1	13,56 €
	Led Power Supply CV AED30-12VLSTB-IP44 12V 30W		5	11,30 €
			10	10,27 €
			100	9,59 €
	ECO Design ERP. 12Vdc constant voltage output			
	Length (mm): 171 Width (mm): 54 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 2.5 Frequency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): +40 Critical Temperature (°C): 80 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			



	G5030030G		1	15,57 €
	Led power supply CV AED30-12VIP44-3A 12V 30W cable and relay		5	12,97 €
			10	11,79 €
			100	11,02 €
	ECO ERP Design. Constant voltage output 12Vdc. Cabling. Built-in relay			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 2.5 Frequency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030030H		1	14,11 €
	Led power supply CV AED30-12VIP44-3B 12V 30W		5	11,75 €
	wired		10	10,69 €
	ECO ERP Design. Constant voltage output 12Vdc.		100	9,98 €
	Cabling.			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			

**LETARON**




	G5031030E		1	13,56 €
	Led Power Supply CV AED30-24VLSTB-IP44 24V		5	11,30 €
	30W		10	10,27 €
	ECO Design ERP.24Vdc constant voltage output		100	9,59 €
		Length (mm): 171 Width (mm): 54 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9		

**LETARON**




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031030G		1	15,57 €
	Led power supply CV AED30-24VIP44-3A 24V 30W cable and relay		5	12,97 €
			10	11,79 €
			100	11,02 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling. Built-in relay.			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			

**LETARON**




	G5031030H		1	14,11 €
	Led power supply CV AED30-24V IP44-3B 24V 30W wired		5	11,75 €
			10	10,69 €
			100	9,98 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			

**LETARON**



Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031036		1	16,93 €
	Led Power Supply CV AED36-24VLSTB-UL 24V 36W		5	15,39 €
			10	13,99 €
	24Vdc constant voltage output		50	13,08 €
	Length (mm): 220 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 108~132 Voltage Out (Vdc): 24 Intensidad Out (A): 1.5 Frecuency (Hz): 57~63 Power (W): 0~36 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Dimmable: NO			

**LETARON**




	G5030040B		1	25,71 €
	Led Power Supply CV AED40-12VIP44-3A-Q3 12V 40W		5	21,42 €
			10	19,47 €
	Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.		100	18,20 €
	Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 3.33 Frecuency (Hz): 50~60 Power (W): 0~40 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.90			

**LETARON**




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030060C		1	20,71 €
	Led Power Supply CV AED60-12VLSTB-IP44 12V 60W		5	18,82 €
			10	17,12 €
			50	16,00 €
	ECO Design ERP Compliant. 12Vdc constant voltage output			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 0~5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): +40 Critical Temperature (°C): 80 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

**LETARON**




	G5030060F		1	33,49 €
	Led Power Supply CV AED60-12VIP44-3A-Q3 12V 60W		5	27,91 €
			10	25,38 €
			100	23,71 €
	Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.			
	Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.90			

**LETARON**






Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5030060G		1	22,62 €
	Led power supply CV AED60-12VIP44-3A 12V 60W cable and relay		5	18,85 €
			10	17,13 €
			100	16,02 €
	ECO ERP Design. Constant voltage output 12Vdc. Cabling. Built-in relay			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

**LETARON**




	G5030060H		1	21,15 €
	Led power supply CV AED60-12V IP44-3B 12V 60W wired		5	17,63 €
			10	16,03 €
			100	14,98 €
	ECO ERP Design. Constant voltage output 12Vdc. Cabling.			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

**LETARON**




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031060D		1	20,71 €
	Led Power Supply CV AED60-24VLSTB-IP44 24V 60W		5	18,82 €
			10	17,12 €
			50	16,00 €
	24Vdc constant voltage output			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

**LETARON**




	G5031060E		1	21,44 €
	Led Power Supply CV AED60-24VLSTB-UL 24V 60W		5	19,49 €
			10	17,71 €
			50	16,55 €
	24Vdc constant voltage output			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 108~132 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 57~63 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Dimmable: NO			

**LETARON**




Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031060H		1	33,49 €
	Led Power Supply CV AED60-24VIP44-3A-Q3 24V 60W		5	27,91 €
			10	25,38 €
			100	23,71 €
		Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.		
		Length (mm): 228,2 Width (mm): 126,2 High (mm): 18 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: SI Power factor: 0.90		

**LETARON**




	G5031060J		1	22,62 €
	Led power supply CV AED60-24VIP44-3A 24V 60W cable and relay		5	18,85 €
			10	17,13 €
			100	16,02 €
		ECO ERP design. Constant voltage output 24Vdc. Cabling. Built-in relay.		
		Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90		

**LETARON**



LED TECHNOLOGY > Electronic Led Power Supplies > Led Controllers

Subfamily **Control led mirrors**

Picture	Article	Description	Lot	Price/Unit
	G5031060K		1	21,15 €
	Led power supply CV AED60-24V IP44-3B 24V 60W wired		5	17,63 €
			10	16,03 €
			100	14,98 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling.			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

**LETARON**

