








Catalogue **SMART LIGHTING**
Line **Lighting control by Nexta Tech**
FAMILY **Receivers**



Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Download Nexta Tech catalogue [here](#).












Picture	Article	Description	Lot	Price/Unit
	15MCU1224P		1	63,32 €
	Control unit MCU-1224P 12-24V	For dimmable drivers with PUSH. Normally open dry contact output max 1A. Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vdc/ac): 12~24 Intensidad Out (A): 1 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	60,31 €
	15MCUDMONE		1	57,47 €
	Control unit MCU-DM/ONE 4-150W 110-240V	Remote control via AppOneSmart Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Power (W): 4~150 Room Temperature (°C): -20~+55 Ingress Protection: IP20	10	54,73 €

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**






Picture	Article	Description	Lot	Price/Unit
	15MCUPUSH		1	63,32 €
	Control unit Interface radio MCU-PUSH exit Push-Dim. 110-240V. 5A.		10	60,31 €
		Radio frequency interface for the control of Led drivers with "push dim" input Length (mm): 52 Width (mm): 43 High (mm): 21 Voltage In (Vac): 110~240 Intensidad In (A): 5 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		



	15TOP0110		1	86,68 €
	Control unit interface TOP-0110 for drivers 0-1/10V 2000W		10	82,55 €
		Receiver for RF regulation or cable of devices with input 0-1 / 10V max 2000W Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Power (W): 2000 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**




Picture	Article	Description	Lot	Price/Unit
	15TOP0110ONE		1	100,40 €
	Control unit interface TOP-0110/ONE for drivers 0-1/10V 2000W		10	95,62 €
		For control of 0 / 1-10V Drivers		
		Length (mm): 176 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~230 Power (W): 2000 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		 		
	15TOPDL20		1	91,87 €
	Control unit interface TOP-DL20 for Drivers DALI		10	87,49 €
		Interphase receiver with dimmer function and DALI output for the control of up to 20 devices with DALI input. Power 110-240Vac. Departure BUS DALI		
		Length (mm): 174 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
		  		


Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15TOPDL20ONE		1	114,66 €
	Control unit interface TOP-DL20/ONE for Drivers DALI		10	109,20 €
		Interface for controlling DALI Drivers. Max 20 drivers		
		Length (mm): 176 Width (mm): 46 High (mm): 35 Voltage In (Vac): 110~240 Room Temperature (°C): -20~+55 Ingress Protection: IP20		
			 	

	15WITOP100		1	16,41 €
	Connection wire 1 m. RJ11 for TOP extender		10	15,63 €
		1 meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series		
		Length (mm): 1000		
				

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15WITOP1000		1	26,17 €
	Connection wire 10 m. RJ11 for TOP extender		10	24,92 €
		10-meter RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 10000		
				

	15WITOP30		1	13,10 €
	Connection wire 30 cm. RJ11 for TOP extender		10	12,48 €
		30 cm RJ11 connection cable with mounted connectors for the connection of the master control unit with the extension of the TOP series.		
		Length (mm): 300		
				

SMART LIGHTING > Lighting control by Nexta Tech > Receivers

Subfamily **Driver control 0-1/10V, dali, Push dim or phase cut**

Picture	Article	Description	Lot	Price/Unit
	15WITOP500		1	21,02 €
		Connection wire 5 m. RJ11 for TOP extender	10	20,02 €

5-meter RJ11 connection cable with mounted connectors for the connection of the master control panel with the extension of the TOP series.

Length (mm): 5000

