


Catalogue **LED TECHNOLOGY**

Line **Led modules**

FAMILY **Led Lumens Modules**

Subfamily **EggDrop F2-series Flicker Free**


COB Modules mains voltage. ECO desing according to ERP directives. Powers from 4 to 20W. Automatic connectors. Dimmable with leading and trailing edge dimmers.

| Picture | Article | Description | Lot | Price/Unit |
|--|----------------------------------|--|-----|------------|
|  | LUE47049272F2 | | 1 | 14,87 € |
| | Led Cob EDC/47C/4W/927/230V/F201 | | 9 | 12,39 € |
| | | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. | 90 | 11,26 € |
| | | | 180 | 10,73 € |
| | | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 316 Angle (°): 120 Energy efficiency: G CRI (≥): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95 | | |




LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**


| Picture | Article | Description | Lot | Price/Unit |
|---|--|-------------|-----|------------|
|  | LUE47049302F2 | | 1 | 14,87 € |
| | Led Cob EDC / 47C / 4W / 930 / 230V / F201 | | 9 | 12,39 € |
| | | | 90 | 11,26 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. | | 180 | 10,73 € |
| | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 344 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95 | | | |



Subfamily **EggDrop F2-series Flicker Free**


| Picture | Article | Description | Lot | Price/Unit |
|---|--|-------------|-----|------------|
|  | LUE47069272F2 | | 1 | 14,98 € |
| | Led Cob EDC / 47C / 6W / 927 / 230V / F201 | | 9 | 12,48 € |
| | | | 90 | 11,35 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. | | 180 | 10,80 € |
| | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 475 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




| | | | | |
|---|--|--|-----|---------|
|  | LUE47069302F2 | | 1 | 14,98 € |
| | Led Cob EDC / 47C / 6W / 930 / 230V / F201 | | 9 | 12,48 € |
| | | | 90 | 11,35 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. | | 180 | 10,80 € |
| | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 516 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |



Subfamily **EggDrop F2-series Flicker Free**

| Picture | Article | Description | Lot | Price/Unit |
|---|--|-------------|-----|------------|
|  | LUE47089272F2 | | 1 | 15,07 € |
| | Led Cob EDC / 47C / 8W / 927 / 230V / F201 | | 9 | 12,56 € |
| | | | 90 | 11,41 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 180 | 10,87 € |
| | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 665 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




| | | | | |
|---|--|--|-----|---------|
|  | LUE47089302F2 | | 1 | 15,07 € |
| | Led Cob EDC / 47C / 8W / 930 / 230V / F201 | | 9 | 12,56 € |
| | | | 90 | 11,41 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 180 | 10,87 € |
| | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 722 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**


| Picture | Article | Description | Lot | Price/Unit |
|---|---|-------------|-----|------------|
|  | LUE47109272F2 | | 1 | 15,20 € |
| | Led Cob EDC / 47C / 10W / 927 / 230V / F201 | | 9 | 12,66 € |
| | | | 90 | 11,51 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. | | 180 | 10,96 € |
| | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 831 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




| | | | | |
|---|---|--|-----|---------|
|  | LUE47109302F2 | | 1 | 15,20 € |
| | Led Cob EDC / 47C / 10W / 930 / 230V / F201 | | 9 | 12,66 € |
| | | | 90 | 11,51 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 180 | 10,96 € |
| | High (mm): 7,6 Diameter (mm): 47 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 903 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |



Subfamily **EggDrop F2-series Flicker Free**


| Picture | Article | Description | Lot | Price/Unit |
|---|--|-------------|-----|------------|
|  | LUE57089272F2 | | 1 | 15,44 € |
| | Led Cob EDC / 57C / 8W / 927 / 230V / F201 | | 5 | 12,87 € |
| | | | 50 | 11,70 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 100 | 11,14 € |
| | High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 696 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




| | | | | |
|---|---|--|-----|---------|
|  | LUE57109272F2 | | 1 | 15,56 € |
| | Led Cob EDC / 57C / 10W / 927 / 230V / F201 | | 5 | 12,97 € |
| | | | 50 | 11,79 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 100 | 11,23 € |
| | High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 870 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |



Subfamily **EggDrop F2-series Flicker Free**


| Picture | Article | Description | Lot | Price/Unit |
|---|---|-------------|-----|------------|
|  | LUE57109302F2 | | 1 | 15,56 € |
| | Led Cob EDC / 57C / 10W / 930 / 230V / F201 | | 5 | 12,97 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 50 | 11,79 € |
| | | | 100 | 11,23 € |
| | High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 10 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 946 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




| | | | | |
|---|---|--|-----|---------|
|  | LUE57129272F2 | | 1 | 15,68 € |
| | Led Cob EDC / 57C / 12W / 927 / 230V / F201 | | 5 | 13,07 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 50 | 11,88 € |
| | | | 100 | 11,31 € |
| | High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 12 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 997 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |



Subfamily **EggDrop F2-series Flicker Free**

| Picture | Article | Description | Lot | Price/Unit |
|---|--|-------------|-----|------------|
|  | LUE57159272F2 | | 1 | 15,83 € |
| | Led Cob EDC / 57C / 15W / 927 / 230V / F201 | | 5 | 13,20 € |
| | | | 50 | 12,00 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 100 | 11,43 € |
| | High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 15 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 1246 Angle (°): 120 Energy efficiency: G CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




| | | | | |
|---|--|--|-----|---------|
|  | LUE57159302F2 | | 1 | 15,83 € |
| | Led Cob EDC / 57C / 15W / 930 / 230V / F201 | | 5 | 13,20 € |
| | | | 50 | 12,00 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 100 | 11,43 € |
| | High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 15 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 1355 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |




LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**

| Picture | Article | Description | Lot | Price/Unit |
|---|--|-------------|-----|------------|
|  | LUE57159402F2 | | 1 | 15,83 € |
| | Led Cob EDC / 57C / 15W / 940 / 230V / F201 | | 5 | 13,20 € |
| | ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard | | 50 | 12,00 € |
| | | | 100 | 11,43 € |
| | High (mm): 7,6 Diameter (mm): 57 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 15 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 1409 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0,95 | | | |






| | | | | |
|---|---|--|-----|--------|
|  | LUEHL47F2 | | 1 | 1,01 € |
| | Holder D47 for EDC/47C F201 white | | 5 | 0,85 € |
| | Holder for EggDrop modules direct to the network of 47 mm in diameter series F201 | | 50 | 0,77 € |
| | | | 100 | 0,73 € |
| | High (mm): 8,4 Diameter (mm): 47 Colour: White | | | |



LED TECHNOLOGY > Led modules > Led Lumens Modules


Subfamily **EggDrop F2-series Flicker Free**

| Picture | Article | Description | Lot | Price/Unit |
|--|---|-------------|-----|------------|
|  | LUEHL57F2 | | 1 | 1,07 € |
| | Holder D60 for EDG/57C F201 white | | 5 | 0,88 € |
| | Zhaga standard. 5.5mm diameter fixing holes 35mm apart between centers. | | 50 | 0,81 € |
| | High (mm): 9 Diameter (mm): 60 Colour: White | | 100 | 0,77 € |
|   | | | | |

| | | | | |
|--|---|--|-----|--------|
|  | LUETT47F2 | | 1 | 0,72 € |
| | Thermal Tape for EDC/47C F201 | | 5 | 0,60 € |
| | Distributes the heat on the surface of the module. It should measure 6mm more in diameter than the module | | 50 | 0,55 € |
| | Diameter (mm): 53 | | 100 | 0,52 € |
|   | | | | |

LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F2-series Flicker Free**

| Picture | Article | Description | Lot | Price/Unit |
|---|--|-------------|-----|------------|
|  | LUETT57 | | 1 | 0,72 € |
| | Thermal Tape for EDC/57C | | 5 | 0,60 € |
| | UNTIL END OF STOCKS. Distributes the heat on the surface of the module. It should measure 6mm more in diameter than the module | | 50 | 0,55 € |
| | Diameter (mm): 63 | | 100 | 0,52 € |

LUMENS
 Leading the LED Revolution