


Catalogue **LED TECHNOLOGY**

Line **Led modules**

FAMILY **Led Lumens Modules**















Subfamily **EggDrop F3-series Flicker Free**

COB Modules mains voltage. ECO desing according to ERP directives. Diameter 38mm. Powers 4, 6, 8W.
Automatic connectors. Dimmable with leading and trailing edge dimmers.


Picture	Article	Description	Lot	Price/Unit
	LUE38049272F3		1	15,11 €
	Led Cob EDC/38C/4W/927/230V/F302		10	12,58 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		80	11,44 €
			160	10,89 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 365 Angle (°): 120 Energy efficiency: F CRI (≥): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			




Subfamily **EggDrop F3-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUE38049302F3	Led Cob EDC/38C/4W/930/230V/F302	1	15,11 €
			10	12,58 €
			80	11,44 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	10,89 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 370 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				
	LUE38049402F3	Led Cob EDC/38C/4W/940/230V/F302	1	15,11 €
			10	12,58 €
			80	11,44 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	10,89 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 4 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 395 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				

Subfamily **EggDrop F3-series Flicker Free**















Picture	Article	Description	Lot	Price/Unit
	LUE38069272F3		1	15,28 €
	Led Cob EDC/38C/6W/927/230V/F302		10	12,73 €
			100	11,57 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		200	11,02 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 560 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			

















	LUE38069302F3		1	15,28 €
	Led Cob EDC/38C/6W/930/230V/F302		10	12,73 €
			80	11,57 €
	ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.		160	11,02 €
	High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 570 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95			



Subfamily **EggDrop F3-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE38069402F3	Led Cob EDC/38C/6W/940/230V/F302	1	15,28 €
			10	12,73 €
			80	11,57 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	11,02 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 6 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 595 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				
	LUE38089272F3	Led Cob EDC/38C/8W/927/230V/F302	1	15,42 €
			10	12,84 €
			80	11,67 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	11,12 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 2700 Lumen: 745 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				

Subfamily **EggDrop F3-series Flicker Free**


Picture	Article	Description	Lot	Price/Unit
	LUE38089302F3	Led Cob EDC/38C/8W/930/230V/F302	1	15,42 €
			10	12,84 €
			80	11,67 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	11,12 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 3000 Lumen: 760 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				
	LUE38089402F3	Led Cob EDC/38C/8W/940/230V/F302	1	15,42 €
			10	12,84 €
			80	11,67 €
		ECO design according to ERP directives. Automatic connectors. Dimmable by cutting start or end of phase.	160	11,12 €
		High (mm): 7,15 Diameter (mm): 38 Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 8 Temperature (°C): -40+85 Room Temperature (°C): -40~+85 Critical Temperature (°C): 85 Colour Temperature (°K): 4000 Lumen: 790 Angle (°): 120 Energy efficiency: F CRI (?): 90 Life (Hours): 50000 Dimmable: Corte inicio o fin de fase Power factor: >0.95		
     				

LED TECHNOLOGY > Led modules > Led Lumens Modules

Subfamily **EggDrop F3-series Flicker Free**

Picture	Article	Description	Lot	Price/Unit
	LUEHL38F3		1	1,07 €
	Holder for EDC/38C F302		5	0,88 €
			50	0,81 €
	High (mm): 8,3 Diameter (mm): 40,7		100	0,77 €



	LUETT38F3		1	0,69 €
	Thermal Tape for EDC/38C F302		50	0,57 €
	Distributes the heat on the surface of the module. It must measure 6mm more in diameter than the module		100	0,52 €
	Diameter (mm): 44 Colour: Black		200	0,49 €

