



Catalogue **LED TECHNOLOGY**
 Line **Electronic Led Power Supplies**
 FAmily **LED power supplies constant voltage**
 Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031012A		1	8,31 €
	Led Power Supply dimmable CV IP65 Mini D 24V 12W		5	7,55 €
			10	6,86 €
			50	6,41 €
	ECO ERP Design. 24Vdc constant voltage output. Dimmable TRIAC. Wiring 20cm.			
	Length (mm): 50 Width (mm): 48 High (mm): 24 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.1~0.5 Frecuency (Hz): 50~60 Power (W): 0~12 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP65 Dimmable: Corte inicio o fin de fase Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031015E		1	32,45 €
	LED power supply CV SLD15-24VL-E 24V 15W		5	29,50 €
	Constant voltage output 24Vdc. Efficiency 78.5%. cabling. Dimmable by cutting start or end of phase		10	26,81 €
			30	25,06 €
	Length (mm): 84 Width (mm): 37 High (mm): 34 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Frecuency (Hz): 50~60 Room Temperature (°C): -10~+50 Critical Temperature (°C): 80 Ingress Protection: IP20 Power factor: 0.95			




	G5030030D		1	35,56 €
	Led Power Supply Dimmable CV SLD30-12VL-E 12V-30W		5	32,32 €
	ECO Design ERP Compliant. Output constant voltage 12Vdc. Efficiency 81%. Adjustable 5-100% by trailing edge or leading edge dimmers .Ripple free in all dimming range		10	29,38 €
			48	27,47 €
	Length (mm): 145 Width (mm): 50 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 0.42~2.5 Frecuency (Hz): 50~60 Power (W): 5~30 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: Corte inicio o fin de fase Power factor: 0.95			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage


Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G503131		1	35,56 €
	LED Power Supply Dimmable CV SLD30-24VL-E		5	32,32 €
	24V-30W		10	29,38 €
			48	27,47 €

Meets ECO Design ERP. 24Vdc constant voltage output. 83% efficiency. Dimmable 5-100% with leading and trailing edge dimmers. No flicker in the entire regulation range.

Length (mm): 145 Width (mm): 50 High (mm): 22
 Colour: White Voltage In (Vac): 220~240
 Voltage Out (Vdc): 24 Intensidad Out (A): 0.21~1.25
 Frequency (Hz): 50~60 Power (W): 5~30
 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 85 Ingress Protection: IP20
 Dimmable: Corte inicio o fin de fase
 Power factor: 0.95



	G5031050C		1	18,07 €
	CV Dimmable Led Power Supply DIM24-50 24V-50W		5	16,38 €
			10	14,90 €
			50	13,81 €


ECO Design ERP. 24Vdc constant voltage output. Dimmable by phase cut

Length (mm): 184 Width (mm): 61 High (mm): 32
 Colour: White Voltage In (Vac): 220~240
 Voltage Out (Vdc): 24 Intensidad Out (A): 0.5~2.08
 Frequency (Hz): 50~60 Power (W): 50
 Room Temperature (°C): -20~+50
 Critical Temperature (°C): 70 Life (Hours): 50000
 Ingress Protection: IP20
 Dimmable: Corte inicio o fin de fase
 Power factor: 0.95




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031050D		1	17,68 €
	CV Dimmable Led Power Supply DIM48-50 48V-50W		5	16,07 €
	ECO Design ERP. 48Vdc constant voltage output.		10	14,61 €
	Dimmable by phase cut		50	13,52 €
	Length (mm): 184 Width (mm): 61 High (mm): 32 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 48 Intensidad Out (A): 0~1.04 Frecuency (Hz): 50~60 Power (W): 0~50 Room Temperature (°C): -20~+50 Critical Temperature (°C): 70 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: Corte inicio o fin de fase Power factor: 0.95			




	G5031060G		1	23,75 €
	Dimable 1-10V Led Power Supply CV Q8H 24V 60W		5	21,59 €
	Meets ECO Design ERP. 24Vdc constant voltage output		10	19,63 €
			50	18,36 €
	Length (mm): 184 Width (mm): 61 High (mm): 32 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.2~2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: 1-10V Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5030075B		1	64,74 €
	LED Power Supply Dimmable CV SLD75-12VL-E		5	58,88 €
	12V-75W		10	53,52 €
	Meets ECO Design ERP. Dimmable 5-100% with leading or trailing edge dimmers. Output at constant voltage 12Vdc. Efficiency 85%		30	50,02 €
	Length (mm): 185 Width (mm): 60 High (mm): 31 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 1~6.25 Frecuency (Hz): 50~60 Power (W): 12~75 Room Temperature (°C): -10~+45 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: Corte inicio o fin de fase Power factor: 0.95			



	G5031075F		1	40,92 €
	Linear Led Driver CV Dimmable DALI LT-75-24D 24V		5	37,21 €
	75W		10	33,83 €
	ECO Design ERP. 24Vdc constant voltage output. Dimmable by DALI		50	31,62 €
	Length (mm): 400 Width (mm): 32 High (mm): 21,6 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~3.12 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): -20~+50 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G503175F		1	64,97 €
	LED Power Supply Dimmable CV SLD75-24VL-E 24V 75W		5	59,07 €
			10	53,69 €
			30	50,18 €
	Meets ECO Design ERP. 24Vdc constant voltage output. 86.5% efficiency. Dimmable 5-100% with leading and trailing edge dimmers. No flicker in the entire regulation range.			
	Length (mm): 185 Width (mm): 60 High (mm): 31 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.5~3.12 Frecuency (Hz): 50~60 Power (W): 12~75 Room Temperature (°C): -10~+45 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: Corte inicio o fin de fase Power factor: 0.95			




	G5031103		1	59,41 €
	Led Power supply CV MW ELG-24V IP67 DALI-3Y		5	58,28 €
			10	57,08 €
			20	55,99 €
	ECO Design ERP.IP67 LED power supply with 24Vdc constant voltage output. DALI regulation.			
	Length (mm): 199 Width (mm): 63 High (mm): 35,5 Voltage In (Vac): 100~305 Voltage Out (Vdc): 24 Intensidad Out (A): 4 Frecuency (Hz): 47~63 Power (W): 96 Room Temperature (°C): -40~+90 Critical Temperature (°C): 90 Ingress Protection: IP67 Dimmable: DALI Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**


Picture	Article	Description	Lot	Price/Unit
	G5031100E		1	35,33 €
	Dimable 1-10V Led Power Supply CV Q8H 24V 100W		5	32,12 €
	Meets ECO Design ERP. 24Vdc constant voltage output		10	29,22 €
			50	27,29 €
	Length (mm): 210 Width (mm): 67 High (mm): 34 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.2~4.17 Frequency (Hz): 50~60 Power (W): 0~100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: 1-10V Power factor: 0.95			




	G5031100H		1	48,78 €
	CV Dimmable Led Power Supply DIM24-100 24V-100W		5	44,34 €
	ECO Design ERP. 24Vdc constant voltage output. Dimmable by phase cut		10	40,31 €
			50	37,67 €
	Length (mm): 210 Width (mm): 67 High (mm): 34 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.4~4.2 Frequency (Hz): 50~60 Power (W): 100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: Corte inicio o fin de fase Power factor: 0.95			



Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031100J		1	48,17 €
	CV Dimmable Led Power Supply DIM48-100		5	43,78 €
	48V-100W		10	39,81 €
	ECO Design ERP. 48Vdc constant voltage output. Dimmable by phase cut		50	37,21 €
	Length (mm): 210 Width (mm): 67 High (mm): 34 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 48 Intensidad Out (A): 0~2.08 Frecuency (Hz): 50~60 Power (W): 33.6~100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: Corte inicio o fin de fase Power factor: 0.95			




	G5031100K		1	47,18 €
	Linear Led Driver CV Dimmable DALI LT-100-24D		5	42,89 €
	24V 100W		10	38,99 €
	ECO Design ERP. 24Vdc constant voltage output. Dimmable by DALI		50	36,44 €
	Length (mm): 400 Width (mm): 32 High (mm): 21,6 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~4.17 Frecuency (Hz): 50~60 Power (W): 0~100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage


Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031120		1	74,17 €
	LED Power Supply Dimmable CV SLD120-24VL-E		5	67,42 €
	24V 120W		10	61,30 €
			30	57,29 €

Meets ECO Design ERP. 24Vdc constant voltage output. Efficiency 90%. Dimmable 5-100% with leading and trailing edge dimmers. No flicker in the entire regulation range.

Length (mm): 223 Width (mm): 64 High (mm): 32
 Colour: White Voltage In (Vac): 220~240
 Voltage Out (Vdc): 24 Intensidad Out (A): 0.5~5
 Frecuency (Hz): 50~60 Power (W): 12~120
 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 85 Ingress Protection: IP20
 Dimmable: Corte inicio o fin de fase
 Power factor: 0.95



	G5031150E		1	38,19 €
	Dimmable 1-10V Led Power Supply CV Q8H 24V		5	34,71 €
	150W		10	31,55 €
			50	29,48 €


Meets ECO Design ERP. 24Vdc constant voltage output

Length (mm): 210 Width (mm): 67 High (mm): 34
 Colour: White Voltage In (Vac): 220~240
 Voltage Out (Vdc): 24 Intensidad Out (A): 0.2~6.25
 Frecuency (Hz): 50~60 Power (W): 0~150
 Room Temperature (°C): -20~+45
 Critical Temperature (°C): 90 Life (Hours): 30000
 Ingress Protection: IP20 Dimmable: 1-10V
 Power factor: 0.95




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031150G		1	115,35 €
	Led Power supply CV Dimmable DALI		5	96,12 €
	SLD150-24VFD-EU 24V 150W		10	87,39 €
	ECO Design ERP. 24Vdc constant voltage output. Efficiency >92.5%. Dimmable DALI2.		50	80,91 €
	Length (mm): 402 Width (mm): 30 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~6.25 Frecuency (Hz): 50~60 Power (W): 0~150 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			




	G5031150H		1	115,35 €
	Led Power supply CV Dimmable DALI		5	96,12 €
	SLD150-48VFD-EU 48V 150W		10	87,39 €
	ECO Design ERP. 48Vdc constant voltage output. Efficiency >93.5%. Dimmable DALI2.		50	80,91 €
	Length (mm): 402 Width (mm): 30 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 48 Intensidad Out (A): 0~4.16 Frecuency (Hz): 50~60 Power (W): 0~150 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031150M		1	50,67 €
	Linear Led Driver CV Dimmable DALI LT-150-24D		5	46,07 €
	24V 150W		10	41,89 €
	ECO Design ERP. 24Vdc constant voltage output. Dimmable by DALI		50	39,14 €
	Length (mm): 400 Width (mm): 32 High (mm): 21,6 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~6.25 Frecuency (Hz): 50~60 Power (W): 0~150 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			




	G5031200D		1	122,30 €
	Led Power supply CV Dimmable DALI		5	101,92 €
	SLD200-24VFD-EU 24V 200W		10	92,65 €
	ECO Design ERP. 24Vdc constant voltage output. Efficiency >92.5%. Dimmable DALI2.		50	85,79 €
	Length (mm): 402 Width (mm): 30 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~8.33 Frecuency (Hz): 50~60 Power (W): 0~200 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031200E		1	122,30 €
	Led Power supply CV Dimmable DALI		5	101,92 €
	SLD200-48VFD-EU 48V 200W		10	92,65 €
	ECO Design ERP. 48Vdc constant voltage output. Efficiency >93.5%. Dimmable DALI2.		50	85,79 €
	Length (mm): 402 Width (mm): 30 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 48 Intensidad Out (A): 0~4.16 Frecuency (Hz): 50~60 Power (W): 0~200 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			




	G5031200G		1	61,40 €
	Linear Led Driver CV Dimmable DALI LT-200-24D		5	55,82 €
	24V 200W		10	50,77 €
	ECO Design ERP. 24Vdc constant voltage output. Dimmable by DALI		50	46,98 €
	Length (mm): 450 Width (mm): 32 High (mm): 23 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~8.33 Frecuency (Hz): 50~60 Power (W): 0~200 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Dimmabel Led power Supplies constant voltage**

Picture	Article	Description	Lot	Price/Unit
	G5031202		1	85,18 €
	Led Power supply CV MW IP67 ELG 24V 200W		5	83,53 €
	DALI-3Y		10	81,87 €
			20	80,30 €
	ECO Design ERP.IP67 LED power supply with 24Vdc constant voltage output. DALI regulation.			
		Length (mm): 244 Width (mm): 71 High (mm): 37,5 Voltage In (Vac): 100~305 Voltage Out (Vdc): 24 Intensidad Out (A): 4.2~8.4 Frecuency (Hz): 47~63 Power (W): 200 Room Temperature (°C): -40~+90 Critical Temperature (°C): 90 Ingress Protection: IP67 Dimmable: DALI Power factor: 0.95		



	G5031240B		1	72,15 €
	Linear Led Driver CV Dimmable DALI LT-240-24D		5	65,59 €
	24V 240W		10	59,62 €
			50	55,72 €
	ECO Design ERP. 24Vdc constant voltage output. Dimmable by DALI			
		Length (mm): 450 Width (mm): 32 High (mm): 23 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~10 Frecuency (Hz): 50~60 Power (W): 0~240 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: DALI Power factor: 0.95		

