



Catalogue **LED TECHNOLOGY**
 Line **Electronic Led Power Supplies**
 FAmily **LED power supplies constant voltage**
 Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031004A		1	6,14 €
	Led Power Supply CV Mini IP65 24V 4W		5	5,11 €
	ECO ERP Design. 24Vdc constant voltage output.		10	4,64 €
	Wiring 18cm UL1007 18AWG		50	4,34 €
	Length (mm): 53 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~0.17 Frecuency (Hz): 50~60 Power (W): 0~4 Room Temperature (°C): -20~+60 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP65 Dimmable: NO Power factor: 0.55			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031006		1	8,72 €
	Led Power Supply CV UT 24V 6W		5	7,27 €
	Meets ECO Design ERP. Extra-flat. 24Vdc constant voltage output.		10	6,62 €
			50	6,19 €
	Length (mm): 98 Width (mm): 46 High (mm): 11 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad In (A): 0.07 Intensidad Out (A): 0~0.25 Frequency (Hz): 50~60 Power (W): 0~6 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.55			




	G503506J		1	11,10 €
	Led power supply CV CC SLT6-350IL-4 350mA (24Vdc) 6W		5	9,26 €
	Constant voltage 24VDC and constant current 350mA as identified by the load. Voltage range 100-240/24VDC. Class II.		10	8,41 €
			50	7,80 €
	Length (mm): 68 Width (mm): 35 High (mm): 20 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~22 Intensidad Out (A): 0~0.35 Frequency (Hz): 50~60 Power (W): 0~6 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.40			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5035081	Led Power Supply CV CC 350mA (24VDC) 8 W	1	12,81 €
			5	10,67 €
			10	9,71 €
		Power supply 24VDC or constant current 350mA depending on load	50	9,06 €
		Length (mm): 58 Width (mm): 35 High (mm): 21 Colour: White Voltage In (Vac): 110~240 Voltage Out (Vdc): 3~24 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 1.1~8.4 Room Temperature (°C): -25~+50 Critical Temperature (°C): 75 Ingress Protection: IP20 Dimmable: NO Power factor: 0.6		

Reference: 039121




	G5035081A	Led Power Supply CV CC AED08-350ILS 24Vdc 350mA 8 W	1	8,45 €
			10	7,05 €
			50	6,40 €
		ECO Design ERP Compliant. 24Vdc constant voltage LED power supply or 350mA constant current depending on load	200	5,98 €
		Length (mm): 79,5 Width (mm): 39 High (mm): 19 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 9~22 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 3~7.7 Room Temperature (°C): -20~+45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5		




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031012		1	8,06 €
	Led Power Supply CV Mini IP65 24V 12W		5	7,28 €
	ECO ERP Design. 24Vdc constant voltage output. wiring 20cm		10	6,63 €
			50	6,11 €
	Length (mm): 50 Width (mm): 48 High (mm): 24 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~0.5 Frecuency (Hz): 50~60 Power (W): 0~12 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP65 Dimmable: NO Power factor: 0.9			




	G5031015C		1	10,27 €
	Led Power Supply CV AED15-24VLSTB-IP44 24V 15W		5	8,52 €
	ECO Design ERP. 24Vdc constant voltage output		10	7,74 €
			100	7,22 €
	Length (mm): 145 Width (mm): 41 High (mm): 13,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.625 Frecuency (Hz): 50~60 Power (W): 0~15 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031015D		1	11,05 €
	Led Power Supply CV SLT15-24VF-2S 24V 15W		5	9,20 €
			10	8,37 €
	ECO design according to ERP directives. Ultra flat 16mm. 24Vdc constant voltage output. Full load efficiency >83%.		50	7,75 €
	Length (mm): 121 Width (mm): 45 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~0.625 Frecuency (Hz): 50~60 Power (W): 0~15 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.85			




	G5031015F		1	11,77 €
	Led power supply CV AED15-24VIP44-3A 24V 15W cable and relay		5	9,80 €
			10	8,91 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling. Built-in relay.		100	8,32 €
	Length (mm): 125 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0.625 Frecuency (Hz): 50~60 Power (W): 15 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**


Picture	Article	Description	Lot	Price/Unit
	G503120C		1	14,89 €
	LED Power supply CV SLT20-24VF-2S 24V 20W		5	12,40 €
	ECO Design according to ERP directives. Ultra-flat 16mm. Constant voltage output 24Vdc. Full load efficiency >83%		10	11,27 €
			50	10,44 €
	Length (mm): 121 Width (mm): 45 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~0.84 Frecuency (Hz): 50~60 Power (W): 0~20 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.85			




	G5031030A		1	19,07 €
	LED Power Supply CV SLT30-24VLG-Es 24V 30W		5	15,89 €
	Meets ECO Design ERP. 24Vdc constant voltage output. Efficiency 85.6%		10	14,44 €
			40	13,49 €
	Length (mm): 165 Width (mm): 40 High (mm): 30 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+50 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			



Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031030B		1	20,98 €
	LED Power Supply CV SLT30-24VFG 24V 30W		5	19,08 €
	ECO Design ERP. Ultra flat 16mm. Constant voltage output 24Vdc. Efficiency 84.5%		10	17,34 €
			100	16,21 €
	Length (mm): 246 Width (mm): 30 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~1.25 Frequency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	G5031030C		1	37,36 €
	LED Power Supply CV SLT30-24VFC-UN IP67 24V 30W		5	33,96 €
	ECO Design ERP. IP67. Extra flat. Constant voltage output 24Vdc. Efficiency 84.5%		10	30,89 €
			50	28,85 €
	Length (mm): 275 Width (mm): 30 High (mm): 16 Colour: Grey Voltage In (Vac): 120~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~1.25 Frequency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031030E		1	13,56 €
	Led Power Supply CV AED30-24VLSTB-IP44 24V 30W		5	11,30 €
			10	10,27 €
	ECO Design ERP.24Vdc constant voltage output		100	9,59 €
	Length (mm): 171 Width (mm): 54 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

LETARON




	G5031030F1		1	12,74 €
	Led Power Supply CV UTA IP44 24V 30W		5	11,57 €
			10	10,53 €
	ECO Design ERP.24Vdc constant voltage output		50	9,88 €
	Length (mm): 154 Width (mm): 54 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO Power factor: 0.95			

AcTEC




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031030G		1	15,57 €
	Led power supply CV AED30-24VIP44-3A 24V 30W cable and relay		5	12,97 €
			10	11,79 €
			100	11,02 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling. Built-in relay.			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			

LETARON




	G5031030H		1	14,11 €
	Led power supply CV AED30-24V IP44-3B 24V 30W wired		5	11,75 €
			10	10,69 €
			100	9,98 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling			
	Length (mm): 145 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.9			

LETARON




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	GTV024030		1	16,47 €
	Led Power Supply CV LCV 24V 30W		5	14,98 €
	ECO ERP directives. Constant Voltage Output 24Vdc		10	13,61 €
			25	12,61 €
	Length (mm): 153 Width (mm): 41 High (mm): 32 Voltage In (Vac): 220~240 Voltage Out (Vdc): 0~24 Intensidad Out (A): 1.25 Frecuency (Hz): 50~60 Power (W): 0~30 Room Temperature (°C): -15~+45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			
Reference: 127820				




	G5031036		1	16,93 €
	Led Power Supply CV AED36-24VLSTB-UL 24V 36W		5	15,39 €
	24Vdc constant voltage output		10	13,99 €
			50	13,08 €
	Length (mm): 220 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 108~132 Voltage Out (Vdc): 24 Intensidad Out (A): 1.5 Frecuency (Hz): 57~63 Power (W): 0~36 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Dimmable: NO			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031040A		1	17,38 €
	Led Power Supply CV Q8H 24V 40W		5	14,51 €
	Meets ECO Design ERP. 24Vdc constant voltage output		10	13,18 €
			50	12,32 €
	Length (mm): 166 Width (mm): 52 High (mm): 24 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~1.7 Frecuency (Hz): 50~60 Power (W): 0~40 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	G5031040C		1	18,17 €
	Led Power Supply CV AED40-24VLSTB-IP44 24V 40W		5	15,15 €
	ECO ERP Design. Constant voltage output 24Vdc		10	13,77 €
			100	13,77 €
	Length (mm): 220 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Frecuency (Hz): 50~60 Power (W): 40 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031050A		1	20,84 €
	Led Power Supply CV UT 24V 50W		5	18,94 €
	Meets ECO Design ERP. Extra-flat. 24Vdc constant voltage output.		10	17,21 €
			50	16,09 €
	Length (mm): 185 Width (mm): 62 High (mm): 22 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~2.1 Frecuency (Hz): 50~60 Power (W): 0~50 Room Temperature (°C): -20~+50 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	G5031050B		1	18,71 €
	Led Power Supply CV Q8H 24V 50W		5	16,99 €
	Meets ECO Design ERP. 24Vdc constant voltage output		10	15,47 €
			50	14,44 €
	Length (mm): 184 Width (mm): 61 High (mm): 32 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~2.1 Frecuency (Hz): 50~60 Power (W): 0~50 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031060A		1	29,30 €
	LED Power Supply CV SLT60-24VLG-E 24V 60W		5	26,17 €
	ECO Design ERP.Constant voltage output 24Vdc. Efficiency 89%		10	23,73 €
			100	22,15 €
	Length (mm): 188 Width (mm): 45 High (mm): 30 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	G5031060B		1	38,82 €
	LED Power Supply CV SLT60-24VFG-UN 24V 60W		5	35,30 €
	Meets ECO Design ERP. Ultra-flat 16mm. 24Vdc constant voltage output. Efficiency 91.6%		10	32,10 €
			100	29,99 €
	Length (mm): 298 Width (mm): 29,8 High (mm): 16 Colour: White Voltage In (Vac): 120~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031060D		1	20,71 €
	Led Power Supply CV AED60-24VLSTB-IP44 24V 60W		5	18,82 €
			10	17,12 €
			50	16,00 €
	24Vdc constant voltage output			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Dimmable: NO Power factor: 0.9			

LETARON




	G5031060E		1	21,44 €
	Led Power Supply CV AED60-24VLSTB-UL 24V 60W		5	19,49 €
			10	17,71 €
			50	16,55 €
	24Vdc constant voltage output			
	Length (mm): 238 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 108~132 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 57~63 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Dimmable: NO			

LETARON




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031060J		1	22,62 €
	Led power supply CV AED60-24VIP44-3A 24V 60W cable and relay		5	18,85 €
			10	17,13 €
			100	16,02 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling. Built-in relay.			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

LETARON




	G5031060K		1	21,15 €
	Led power supply CV AED60-24V IP44-3B 24V 60W wired		5	17,63 €
			10	16,03 €
			100	14,98 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling.			
	Length (mm): 184 Width (mm): 55 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP44 Power factor: 0.90			

LETARON




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031060L		1	20,45 €
	Led Power Supply CV PW60-24 24V 60W		5	18,59 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling.		10	16,90 €
			50	15,80 €
	Length (mm): 155 Width (mm): 45 High (mm): 32 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -40~+70 Critical Temperature (°C): 85 Life (Hours): 50000 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




	GTV024060		1	19,27 €
	Led Power Supply CV LCV 24V 60W		5	17,51 €
	ECO ERP directives. Constant Voltage Output 24Vdc		10	15,93 €
			25	14,74 €
	Length (mm): 180 Width (mm): 52 High (mm): 30 Voltage In (Vac): 220~240 Voltage Out (Vdc): 0~24 Intensidad Out (A): 2.5 Frecuency (Hz): 50~60 Power (W): 0~60 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95 Reference: 127821			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031075		1	36,45 €
		LED Power Supply CV SLT75-24VL-E 24V 75W	5	33,14 €
		Meets SLR-2021. 24Vdc constant voltage output. Efficiency 87.7%	10	30,13 €
			30	28,16 €
		Length (mm): 185 Width (mm): 60 High (mm): 31 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~3.125 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Power factor: 0,95		





	G5031075A		1	38,82 €
		LED Power Supply CV SLT75-24VFG 24V 75W	5	35,30 €
		Meets ECO Design ERP. Ultra-flat 16.5mm. 24Vdc constant voltage output. Efficiency 91.6%	10	32,10 €
			100	29,99 €
		Length (mm): 298 Width (mm): 30 High (mm): 16,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~3.125 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): -20~+50 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95		



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage


Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031075B		1	51,35 €
	LED Power Supply CV SLT75-24VFC-UN IP67 24V 75W		5	46,68 €
			10	42,45 €
			50	39,68 €
		Meets ECO Design ERP. IP67. Extra-flat. 24Vdc constant voltage output. 91.2% efficiency.		
		Length (mm): 333 Width (mm): 30 High (mm): 16 Colour: Grey Voltage In (Vac): 120~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~3.125 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95		
				


	G5031075C		1	22,89 €
	Led Power Supply CV Q8H 24V 75W		5	20,81 €
			10	18,92 €
			50	17,69 €
		Meets ECO Design ERP. 24Vdc constant voltage output		
		Length (mm): 184 Width (mm): 61 High (mm): 32 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~3.1 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95		
				

LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031075E		1	24,93 €
	Led Power Supply CV LT 24V 75W		5	22,66 €
	ECO ERP Design. 24 Vdc output voltage.		10	20,61 €
			50	19,25 €
	Length (mm): 305 Width (mm): 30 High (mm): 18,2 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~3.125 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): -20~+50 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			






	G503175E		1	30,78 €
	LED Power Supply CV 24V 75W		5	27,98 €
	ECO Design ERP.Constant voltage. Class II, IP20		10	25,44 €
			50	23,79 €
	Length (mm): 180 Width (mm): 52 High (mm): 30 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~3.1 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): +55 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.9 Reference: 401365			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage


Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G503175H		1	32,92 €
	Led Power supply CV CC MW XLG-75-24A IP67		5	32,27 €
	75W-24V		10	31,64 €
			20	31,02 €
	ECO Design ERP. 24V constant voltage output. Adjustable output intensity with potentiometer.			
	Length (mm): 140 Width (mm): 63 High (mm): 32 Voltage In (Vac): 100~350 Voltage Out (Vdc): 16.8~24 Intensidad Out (A): 1.55~3.1 Frecuency (Hz): 47~63 Power (W): 74.4 Room Temperature (°C): -40~+90 Critical Temperature (°C): 90 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			
				
				

	GTV024075		1	21,66 €
	Led Power Supply CV LCV 24V 75W		5	19,68 €
			10	17,90 €
			25	16,58 €
	ECO ERP directives. Constant Voltage Output 24Vdc			
	Length (mm): 180 Width (mm): 52 High (mm): 30 Voltage In (Vac): 220~240 Voltage Out (Vdc): 0~24 Intensidad Out (A): 3.125 Frecuency (Hz): 50~60 Power (W): 0~75 Room Temperature (°C): -15~+45 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			
	Reference: 127822			
				
				


LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	GTV024090		1	23,26 €
	Led Power Supply CV LCV 24V 90W		5	21,15 €
			10	19,21 €
	ECO ERP directives. Constant Voltage Output 24Vdc		25	17,81 €
	Length (mm): 300 Width (mm): 40 High (mm): 30 Voltage In (Vac): 220~240 Voltage Out (Vdc): 0~24 Intensidad Out (A): 3.75 Frecuency (Hz): 50~60 Power (W): 0~90 Room Temperature (°C): -15~+45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			

Reference: 127823




	G5031024		1	59,55 €
	LED Power Supply CV SLT96-24VLC-UN IP67 24V 96W		5	54,15 €
			10	49,21 €
	Meets ECO Design ERP. IP67. 24Vdc constant voltage output. Efficiency 92.5%.		40	45,98 €
	Length (mm): 262 Width (mm): 40 High (mm): 23 Colour: Grey Voltage In (Vac): 100~277 Voltage Out (Vdc): 24 Intensidad Out (A): 0~4 Frecuency (Hz): 50~60 Power (W): 0~96 Room Temperature (°C): -40~+60 Critical Temperature (°C): 85 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031100F		1	49,66 €
	Led Power supply CV CC MW XLG-100-24A IP67		5	48,70 €
	96W-24V		10	47,72 €
	ECO Design ERP. 24V constant voltage output.		20	46,80 €
	Adjustable output intensity with potentiometer.			
	Length (mm): 140 Width (mm): 63 High (mm): 32 Voltage In (Vac): 100~305 Voltage Out (Vdc): 16.8~24 Intensidad Out (A): 2~4 Frecuency (Hz): 47~63 Power (W): 96 Room Temperature (°C): -40~+90 Critical Temperature (°C): 90 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




	G5031100A		1	48,30 €
	LED Power Supply CV SLT100-24VL-E 24V 100W		5	43,90 €
	Meets SLR-2021. 24Vdc constant voltage output.		10	39,91 €
	Efficiency 91.7%		30	37,31 €
		Length (mm): 185 Width (mm): 60 High (mm): 31 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~4.2 Frecuency (Hz): 50~60 Power (W): 0~100 Room Temperature (°C): -20~+40 Critical Temperature (°C): 80 Ingress Protection: IP20 Power factor: 0,95		




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031100B		1	46,03 €
	LED Power Supply CV SLT100-24VFG-UN 24V 100W		5	41,83 €
			10	38,04 €
	Meets ECO Design ERP. Ultra-flat 16.5mm. 24Vdc constant voltage output. Efficiency 92.3%		50	35,56 €
	Length (mm): 298 Width (mm): 29,8 High (mm): 16 Colour: White Voltage In (Vac): 120~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~4.2 Frecuency (Hz): 50~60 Power (W): 0~100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	G5031100D		1	53,57 €
	LED Power Supply CV SLT100-24VFC-UN IP67 24V 100W		5	48,70 €
			10	44,28 €
	Meets ECO Design ERP. Ultra-flat 16.5mm. 24Vdc constant voltage output. Efficiency 92%		50	41,39 €
	Length (mm): 340 Width (mm): 30 High (mm): 16 Colour: White Voltage In (Vac): 120~240 Voltage Out (Vdc): 24 Frecuency (Hz): 50~60 Power (W): 0~100 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031100G		1	29,80 €
	Led Power Supply CV LT 24V 100W		5	27,11 €
	ECO ERP Design. 24 Vdc output voltage.		10	24,64 €
			50	23,01 €
	Length (mm): 320 Width (mm): 30 High (mm): 18,2 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~4.17 Frecuency (Hz): 50~60 Power (W): 0~100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			









	G5031100L		1	31,79 €
	Led Power Supply CV PW60-24 24V 100W		5	28,89 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling.		10	26,27 €
			50	24,54 €
	Length (mm): 165 Width (mm): 45 High (mm): 32 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~4.17 Frecuency (Hz): 50~60 Power (W): 0~100 Room Temperature (°C): -40~+45 Critical Temperature (°C): 85 Life (Hours): 50000 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage


Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031100M		1	40,37 €
	LED Power Supply CV SLT100-24VLG-E 24V 100W		5	36,70 €
	ECO ERP Design. Constant voltage output 24Vdc.		10	33,36 €
	Efficiency 92%		30	31,20 €
	Length (mm): 188 Width (mm): 45 High (mm): 30 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Frecuency (Hz): 50~60 Power (W): 100 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			
 				


	GTV024120		1	25,77 €
	Led Power Supply CV LCV 24V 120W		5	23,43 €
	ECO ERP directives. Constant Voltage Output 24Vdc		10	21,28 €
			25	19,71 €
	Length (mm): 300 Width (mm): 40 High (mm): 30 Voltage In (Vac): 220~240 Voltage Out (Vdc): 0~24 Intensidad Out (A): 5 Frecuency (Hz): 50~60 Power (W): 0~120 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			
Reference: 127824  				

LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031150B		1	54,25 €
	LED Power Supply CV SLT150-24VLG-E 24V 150W		5	49,32 €
	Meets ECO Design ERP. 24Vdc constant voltage output		10	44,85 €
			30	41,90 €
	Length (mm): 185 Width (mm): 60 High (mm): 31 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad In (A): 0.8 Frecuency (Hz): 50~60 Power (W): 0~150 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			






	G5031150D		1	38,10 €
	Led Power Supply CV Q8H 24V 150W		5	34,62 €
	Meets ECO Design ERP. 24Vdc constant voltage output		10	31,49 €
			50	29,42 €
	Length (mm): 210 Width (mm): 67 High (mm): 34 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~6.25 Frecuency (Hz): 50~60 Power (W): 0~150 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage


Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031150F		1	61,97 €
	Led Power supply CV CC MW XLG-150-24A IP67		5	60,74 €
	150W-24V		10	59,55 €
			20	58,40 €
	ECO Design ERP. 24V constant voltage output. Adjustable output intensity with potentiometer.			
	Length (mm): 180 Width (mm): 63 High (mm): 35,5 Voltage In (Vac): 100~305 Voltage Out (Vdc): 16.8~24 Intensidad Out (A): 3.2~6.25 Frecuency (Hz): 47~63 Power (W): 150 Room Temperature (°C): -40~+90 Critical Temperature (°C): 90 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			
				
				


	G5031150K		1	69,52 €
	Linear Led Power Supply CV SLT150-24VFG-UN 24V		5	63,21 €
	150W		10	57,46 €
			50	53,70 €
	ECO Design ERP. 24Vdc constant voltage output.			
	Length (mm): 384 Width (mm): 30 High (mm): 22 Colour: White Voltage In (Vac): 120~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~6.25 Frecuency (Hz): 50~60 Power (W): 0~150 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			
				
				

LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031150L		1	36,80 €
	Led Power Supply CV PW60-24 24V 150W		5	33,45 €
	ECO ERP design. Constant voltage output 24Vdc. Cabling.		10	30,41 €
			50	28,42 €
	Length (mm): 180 Width (mm): 52 High (mm): 32 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~6.15 Frecuency (Hz): 50~60 Power (W): 0~150 Room Temperature (°C): -40~+50 Critical Temperature (°C): 85 Life (Hours): 50000 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




	G5031150P		1	34,68 €
	Led Power Supply CV AW150-24 IP67 24V 150W		5	31,53 €
	ECO ERP design. Constant voltage output 24Vdc. Wiring.		10	28,67 €
			50	26,80 €
	Length (mm): 191 Width (mm): 58 High (mm): 38 Colour: Aluminium Voltage In (Vac): 100~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~6.25 Frecuency (Hz): 50~60 Power (W): 150 Room Temperature (°C): -40~+50 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	GTV024180		1	42,86 €
	Led Power Supply CV LCV 24V 180W		5	38,96 €
			10	35,44 €
	ECO ERP directives. Constant Voltage Output 24Vdc		20	32,80 €
	Length (mm): 345 Width (mm): 50 High (mm): 35 Voltage In (Vac): 220~240 Voltage Out (Vdc): 0~24 Intensidad Out (A): 7.5 Frecuency (Hz): 50~60 Power (W): 0~180 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			

Reference: 127825




	G5031200A		1	74,48 €
	LED power supply CV SLT200-24VFG-UN 24V 200W		5	67,69 €
			10	61,53 €
	ECO Design ERP.Ultra-flat 22mm. Constant voltage output 24Vdc. 94% efficiency		60	57,43 €
	Length (mm): 384 Width (mm): 30 High (mm): 22 Colour: White Voltage In (Vac): 120~240 Voltage Out (Vdc): 24 Frecuency (Hz): 50~60 Power (W): 0~200 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031200C		1	57,27 €
	Led Power supply CV CC MW XLG-200-24A IP67		5	56,15 €
	200W-24V		10	55,03 €
	ECO Design ERP. 24V constant voltage output. Adjustable output intensity with potentiometer.		20	53,96 €
	Length (mm): 199 Width (mm): 63 High (mm): 35,5 Voltage In (Vac): 100~305 Voltage Out (Vdc): 16.8~24 Intensidad Out (A): 4.15~8.3 Frecuency (Hz): 47~63 Power (W): 199.2 Room Temperature (°C): -40~+90 Critical Temperature (°C): 90 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




	G5031240C		1	44,07 €
	Led Power Supply CV AW240-24 IP67 24V 240W		5	40,07 €
	ECO ERP design. Constant voltage output 24Vdc. Wiring.		10	36,42 €
			50	34,04 €
	Length (mm): 250 Width (mm): 58 High (mm): 32 Colour: Aluminium Voltage In (Vac): 100~240 Intensidad Out (A): 0~10 Frecuency (Hz): 50~60 Power (W): 240 Room Temperature (°C): -40~+50 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP67 Dimmable: NO Power factor: 0.95			




LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies constant voltage

Subfamily **Led Power Supplies 24Vdc**


Picture	Article	Description	Lot	Price/Unit
	G5031250		1	76,54 €
	LED power supply CV SLT250-24VFG-EU 24V 250W		5	69,59 €
	ECO Design ERP.Ultra-flat 22mm. 24Vdc constant voltage output. Efficiency 94%		10	63,26 €
			60	59,12 €
	Length (mm): 384 Width (mm): 30 High (mm): 22 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~10.42 Frecuency (Hz): 50~60 Power (W): 30~250 Room Temperature (°C): -20~+40 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			



	G5031250C		1	64,91 €
	Led power supply CV SLT250-24VLG-E 48V 250W		5	59,01 €
	ECO Design ERP. 24Vdc constant voltage output.		10	53,65 €
			60	50,14 €
	Length (mm): 230 Width (mm): 64,5 High (mm): 32,5 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 24 Intensidad Out (A): 0~10.4 Frecuency (Hz): 50~60 Power (W): 0~250 Room Temperature (°C): -20~+40 Critical Temperature (°C): 90 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




Subfamily **Led Power Supplies 24Vdc**

Picture	Article	Description	Lot	Price/Unit
	G5031320		1	133,45 €
	Alimentador Led CV CC MW HLG 320 H IP65 320W-24V		5	130,86 €
			10	128,34 €
			20	125,83 €

ECO Design ERP.Voltage and current constante.IP 65.Ajuste manual voltage (21-26VDC) and current (6,67-13,34A).

Length (mm): 252,9 Width (mm): 90 High (mm): 43,8
 Colour: White Voltage In (Vac): 90~305
 Voltage Out (Vdc): 24 Intensidad Out (A): 6.67~13.34
 Frecuency (Hz): 47~63 Power (W): 320
 Room Temperature (°C): -40~+70
 Critical Temperature (°C): 70 Life (Hours): 62000
 Ingress Protection: IP65 Dimmable: NO
 Power factor: 0.95



	G5031600		1	290,34 €
	Led Power supply CV CC MW HLG-600H-24A IP65 600W- 24V		5	284,65 €
			10	279,08 €
			20	273,60 €

ECO Design ERP.Constant voltage and current. IP 65. Manual adjustment of voltage (20.4-25.2Vdc) and current (12.5-25A).

Length (mm): 280 Width (mm): 144 High (mm): 48,5
 Voltage In (Vac): 90~305 Voltage Out (Vdc): 24
 Intensidad Out (A): 12.5~25 Frecuency (Hz): 47~63
 Power (W): 600 Room Temperature (°C): -40~+70
 Critical Temperature (°C): 70 Ingress Protection: IP65
 Dimmable: NO Power factor: 0.95

