



Catalogue **LED TECHNOLOGY**
 Line **Electronic Led Power Supplies**
 Family **LED Power Supplies Constant Current**
 Subfamily **Electronic Led Power Supplies 350mA**

Picture	Article	Description	Lot	Price/Unit
	G503503		1	7,40 €
	LED Power Supply CC SLT3-350IS-1 350mA 3W		5	6,18 €
			20	5,60 €
	ECO Design ERP Compliant. Constant voltage. Class II 20cm cable in primary and secondary IP20		200	5,24 €
	Length (mm): 50 Width (mm): 30 High (mm): 20 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 3~9 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 1~3.2 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			








	G503503E		1	6,10 €
	Led Power Supply CC Mini-3.6-350 350mA 3.6W IP20		5	5,54 €
			10	5,03 €
	ECO ERP Design. IP20. Constant current output 350mA.		50	4,71 €
	Length (mm): 53 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 100~240 Voltage Out (V): 2.5~10 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 0.87~3.5 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.40			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 350mA**


Picture	Article	Description	Lot	Price/Unit
	G503503D		1	9,61 €
	LED Power Supply IP66 CC SLT3-350ISC		5	8,01 €
	350mA-4,2W		20	7,28 €
	ECO Design ERP Compliant. IP66.Constant current 350mA. Output voltage range 3-12Vdc. Class II Wiring with 15cm of cable in primary and secondary		200	6,80 €
	Length (mm): 52 Width (mm): 30 High (mm): 23 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~12 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 1.1~4.2 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP66 Dimmable: NO Power factor: 0.5			
				
				

	G503504A		1	6,29 €
	Led Power Supply CV CC AED04-350ILS 12Vdc		10	5,24 €
	350mA 4W		50	4,76 €
	ECO Design ERP Compliant. 12Vdc constant voltage LED power supply or 350mA constant current depending on load		200	4,45 €
	Length (mm): 51,5 Width (mm): 33 High (mm): 17 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~12 Intensidad Out (A): 0.3 Frecuency (Hz): 50~60 Power (W): 1.05~4.2 Room Temperature (°C): -10~+45 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			
				
				

Subfamily **Electronic Led Power Supplies 350mA**

Picture	Article	Description	Lot	Price/Unit
	G503504A2		1	6,37 €
	Led Power Supply CC Mini 350mA 4W		5	5,27 €
	ECO Design ERP. IP20. 350mA constant current output		10	4,78 €
			50	4,54 €
	Length (mm): 53 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 6~12 Intensidad In (A): 0.05 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 2.1~4.2 Room Temperature (°C): -20~+60 Critical Temperature (°C): 85 Life (Hours): 50000 Ingress Protection: IP65 Dimmable: NO Power factor: 0.60			




	G503506C1		1	6,47 €
	Led Power Supply CC Mini IP65 350mA 6W		5	5,54 €
	ECO ERP Design. IP65. Constant current output 350mA		10	5,03 €
			50	4,71 €
	Length (mm): 53 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 9~18 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 0~6 Room Temperature (°C): -20~+60 Critical Temperature (°C): 85 Ingress Protection: IP65 Dimmable: NO Power factor: 0.6			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 350mA**

Picture	Article	Description	Lot	Price/Unit
	G503506J		1	11,10 €
	Led power supply CV CC SLT6-350IL-4 350mA (24Vdc) 6W		5	9,26 €
			10	8,41 €
	Constant voltage 24VDC and constant current 350mA as identified by the load. Voltage range 100-240/24VDC. Class II.		50	7,80 €
	Length (mm): 68 Width (mm): 35 High (mm): 20 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~22 Intensidad Out (A): 0~0.35 Frecuency (Hz): 50~60 Power (W): 0~6 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.40			




	G5035081		1	12,81 €
	Led Power Supply CV CC 350mA (24VDC) 8 W		5	10,67 €
			10	9,71 €
	Power supply 24VDC or constant current 350mA depending on load		50	9,06 €
	Length (mm): 58 Width (mm): 35 High (mm): 21 Colour: White Voltage In (Vac): 110~240 Voltage Out (Vdc): 3~24 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 1.1~8.4 Room Temperature (°C): -25~+50 Critical Temperature (°C): 75 Ingress Protection: IP20 Dimmable: NO Power factor: 0.6 Reference: 039121			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 350mA**

Picture	Article	Description	Lot	Price/Unit
	G5035081A		1	8,45 €
	Led Power Supply CV CC AED08-350ILS 24Vdc		10	7,05 €
	350mA 8 W		50	6,40 €
	ECO Design ERP Compliant. 24Vdc constant voltage		200	5,98 €
	LED power supply or 350mA constant current depending on load			
	Length (mm): 79,5 Width (mm): 39 High (mm): 19 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 9~22 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 3~7.7 Room Temperature (°C): -20~+45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			

LETARON




	G503510B1		1	7,76 €
	Led Power Suply CC Mini IP65 350mA 10W		5	7,06 €
	ECO Design ERP. IP65. Constant current output		10	6,42 €
	350mA		50	6,01 €
	Length (mm): 58 Width (mm): 36 High (mm): 20 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 15~29 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 0~10 Room Temperature (°C): -20~+60 Critical Temperature (°C): 85 Ingress Protection: IP65 Dimmable: NO Power factor: 0.9			


ACTEC



Subfamily **Electronic Led Power Supplies 350mA**


Picture	Article	Description	Lot	Price/Unit
	G503512B		1	8,27 €
	Led Power Supply CC Mini IP65 350mA F 12W		5	7,51 €
	ECO ERP Design. IP65. Constant current output 350mA		10	6,83 €
			50	6,38 €
	Length (mm): 50 Width (mm): 48 High (mm): 24 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 17~34 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 0~12 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Ingress Protection: IP65 Dimmable: NO Power factor: 0.90			




	G503515H		1	7,25 €
	Led Power Supply CC V9 350mA 15W		5	6,03 €
	ECO Design ERP Compliant. 350mA constant current output		10	5,50 €
			50	5,14 €
	Length (mm): 100 Width (mm): 38,4 High (mm): 20 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 30~42 Intensidad In (A): 0.11 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 15 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.90			



Subfamily **Electronic Led Power Supplies 350mA**


Picture	Article	Description	Lot	Price/Unit
	G503515J		1	9,70 €
		DC Led Power Supply MINI-15-350mA 15W	5	8,81 €
			10	8,01 €
		ECO ERP Design. Constant current output 350mA	50	7,49 €
		Length (mm): 65 Width (mm): 43 High (mm): 24 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 14~42 Intensidad In (A): 0.35 Frecuency (Hz): 50~60 Power (W): 15 Room Temperature (°C): -20~+60 Critical Temperature (°C): 85 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.9		




	G503511A		1	18,30 €
		Led driver CC SLT20-350IF-2s 350mA 20W	5	15,25 €
			10	13,86 €
		ECO design ERP. Extra-flat.Constant current 350mA. Voltage range 220-240Vac/6-56Vdc. Class II	50	12,86 €
		Length (mm): 121 Width (mm): 45 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 6~56 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 2.1~19.6 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.85		



Subfamily **Electronic Led Power Supplies 350mA**

Picture	Article	Description	Lot	Price/Unit
	G503525A		1	9,22 €
	Led Power Supply CC V8 350mA 25W		5	7,67 €
	ECO Design ERP Compliant. 350mA constant current output		10	6,97 €
			50	6,51 €
	Length (mm): 127 Width (mm): 43 High (mm): 28 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 36~71 Intensidad In (A): 0.15 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 12.6~25 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			



	G503540E		1	11,57 €
	Led driver CC V8 350mA 40W		5	9,65 €
	ECO Design ERP Compliant. 350mA constant current output		10	8,76 €
			50	8,18 €
	Length (mm): 127 Width (mm): 43 High (mm): 28 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 57~114 Intensidad In (A): 0.23 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 20~40 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			

