



Catalogue **LED TECHNOLOGY**  
 Line **Electronic Led Power Supplies**  
 Family **LED Power Supplies Constant Current**  
 Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503703D		1	6,10 €
	Led Power Supply CC Mini-3.6-700 700mA 3.6W IP20		5	5,54 €
	ECO ERP Design. IP20. Constant current output 700mA.		10	5,03 €
			50	4,71 €
	Length (mm): 53 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 2.5~5 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 1.75~3.5 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.50			




	G503703		1	7,93 €
	LED Power Supply LED SLT3-700IS-1 700mA 1-3W		5	6,60 €
	ECO Design ERP Compliant. Constant current. Class II, 20cm cable in primary and secondary, IP20		20	6,01 €
			200	5,60 €
	Length (mm): 50 Width (mm): 30 High (mm): 20 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 2~4.2 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 1.4~2.9 Room Temperature (°C): -20~+45 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**


Picture	Article	Description	Lot	Price/Unit
	G503703B		1	10,44 €
	LED Power Supply IP66 CC 700mA 3W		5	8,70 €
	Constant current IP66, 20cm cable in primary and secondary		10	7,90 €
			50	7,38 €
	Length (mm): 38 Width (mm): 27 High (mm): 21,5 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~6 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 2.1~4.2 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP66 Dimmable: NO Power factor: 0.4  Reference: 401331			




	G503504C		1	6,29 €
	Led Power Supply CV CC AED04-700ILS 5Vdc 700mA 3,5W		10	5,24 €
	ECO Design ERP Compliant. LED power supply with constant voltage 5Vdc or constant current 700mA depending on load		50	4,76 €
			200	4,45 €
	Length (mm): 51,5 Width (mm): 32,8 High (mm): 17 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~5 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 2~3.5 Room Temperature (°C): +45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			



Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503504C1		1	5,30 €
	Led Power Supply CC Mini IP65 700mA 4W		5	4,42 €
	IP65. 700mA constant current output		10	4,03 €
			50	3,84 €
	Length (mm): 38 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 2.5~6 Intensidad In (A): 0.1 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 1.75~4 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP65 Dimmable: NO Power factor: 0.40			




	G503504C2		1	6,37 €
	DC Led Power Supply MINI-4-700mA 4W IP65		5	5,27 €
	ECO ERP Design. IP65. Constant current output 700mA		10	4,78 €
			50	4,54 €
	Length (mm): 48 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 2.5~6 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 2.1~4.2 Room Temperature (°C): -20~+60 Critical Temperature (°C): 85 Ingress Protection: IP65 Dimmable: NO Power factor: 0.60			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503706C		1	17,00 €
	Led Power Supply CV CC 700mA (12Vdc) 6W		5	14,16 €
	Power supply in voltage 12VDC and constant current 700mA according to identified load		10	12,88 €
			50	12,04 €
	Length (mm): 42,5 Width (mm): 41 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 0~6 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.6  Reference: 401244			




	G503706H		1	10,24 €
	LED Power Supply CV CC SLT6-700ISC-UN 700mA (12Vdc) 6W		5	8,54 €
	Constant voltage 12VDC and constant current 700mA as identified by the load. Voltage range 120-240 / 12VDC. Class II. Power factor: 0.90 @ 120V		20	7,76 €
			200	7,25 €
	Length (mm): 52 Width (mm): 30 High (mm): 23 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 2.7~9 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 2~6.3 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP66 Power factor: 0.80			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503706J		1	11,10 €
	LED power supply CV CC SLT6-700IL-4 700mA (12Vdc) 6W		5	9,26 €
			10	8,41 €
			50	7,80 €
	ECO design according to ERP directives. Led Power supply voltage 12VDC or constant current 700mA depending on load			
	Length (mm): 68 Width (mm): 35 High (mm): 20 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~8.4 Intensidad Out (A): 0~0.7 Frequency (Hz): 50~60 Power (W): 6 Room Temperature (°C): -20~+40 Critical Temperature (°C): 70 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0,40			




	G5035081B		1	8,45 €
	Led Power Supply CV CC AED08-700ILS 12Vdc 700mA 8 W		10	7,05 €
			50	6,40 €
			200	5,98 €
	ECO Design ERP Compliant. 12Vdc constant voltage LED power supply or 700mA constant current depending on load.			
	Length (mm): 79,5 Width (mm): 39 High (mm): 19 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 6~11 Intensidad Out (A): 0,625 Frequency (Hz): 50~60 Power (W): 4.2~7.7 Room Temperature (°C): -10~+45 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503717		1	22,01 €
	Led Power Supply CC 700mA 17W		5	20,01 €
			10	18,19 €
	UNTIL END OF STOCK		50	17,00 €

Length (mm): 125 Width (mm): 38 High (mm): 22  
 Colour: White Voltage In (Vac): 220~240  
 Voltage Out (Vdc): 3~24 Intensidad Out (A): 0.7  
 Frecuency (Hz): 50~60 Power (W): 17  
 Room Temperature (°C): -20~+50  
 Critical Temperature (°C): 75 Ingress Protection: IP20  
 Dimmable: NO Power factor: 0.6




	G503710B		1	16,61 €
	LED driver CC SLT20-700IL-E 700mA 20W		5	13,85 €
			10	12,60 €
	Constant current Class II. EMC EN61000-3-2 class C.		50	11,77 €


Length (mm): 162 Width (mm): 45 High (mm): 20  
 Colour: White Voltage In (Vac): 220~240  
 Voltage Out (Vdc): 9~30 Intensidad Out (A): 0.7  
 Frecuency (Hz): 50~60 Power (W): 6.3~20  
 Room Temperature (°C): -20~+50  
 Critical Temperature (°C): 80 Ingress Protection: IP20  
 Dimmable: NO Power factor: 0.8



Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503715		1	14,09 €
	Led Power Supply LED SLT20-700IFG 700mA 20W		5	11,74 €
	6-29V		10	10,67 €
	Constant current Class II. EMC EN61000-3-2 class C.		50	9,97 €
	Length (mm): 166 Width (mm): 40 High (mm): 14 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 6~29 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 4.2~20 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			




	G503715A		1	17,62 €
	Led Power Supply CC SLT20-700IF-2S 700mA 20W		5	14,68 €
	ECO design according to ERP directives. Ultra flat 16mm. Constant current 700mA. Voltage range 220-240/6-29VDC. Class II. Full load efficiency >80%		10	13,34 €
			50	12,35 €
	Length (mm): 121 Width (mm): 45 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 6~29 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 4.2~20.3 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.85			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503525B		1	9,22 €
	Led Power Supply CC V8 700mA 25W		5	7,67 €
	ECO Design ERP Compliant. 700mA constant current output		10	6,97 €
			50	6,51 €
	Length (mm): 127 Width (mm): 43 High (mm): 28 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 18~36 Intensidad In (A): 0.15 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 12.6~25 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	G5037025		1	34,24 €
	LED Driver CC MW PCD 700mA 25W		10	28,54 €
	Constant current. Class II. EMC EN61000-3-2 Class C. In 7.5 cm2x NISPT-1 Out: 15cm 2xAWG18		30	27,18 €
	Length (mm): 84 Width (mm): 57 High (mm): 29,5 Colour: White Voltage In (Vac): 180~295 Voltage Out (Vdc): 24~36 Intensidad Out (A): 0.7 Frecuency (Hz): 47~63 Power (W): 25 Temperature (°C): -30+60 Room Temperature (°C): -30~+60 Ingress Protection: IP30			






LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**


Picture	Article	Description	Lot	Price/Unit
	G503530C		1	8,83 €
	Led Power Supply CC V9 700mA 30W		5	7,35 €
	ECO Design ERP Compliant. 700mA constant current output		10	6,68 €
			50	6,25 €
	Length (mm): 116 Width (mm): 41 High (mm): 25 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 30~42 Intensidad In (A): 0.18 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 21~30 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	GTC30700		1	39,17 €
	Led CC power supply IPR2-30/700 700mA 30W		5	35,61 €
	ECO ERP design. 700mA constant current power supply.		10	32,37 €
			30	29,98 €
	Length (mm): 115 Width (mm): 53,5 High (mm): 26 Voltage In (Vac): 110~240 Voltage Out (Vdc): 5~43 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 3.5~30 Room Temperature (°C): -40~+60 Critical Temperature (°C): 90 Ingress Protection: IP68 Dimmable: NO Power factor: 0.97  Reference: 152014/700			



Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	GTC32700	Led Driver CC ECO 32-700-750mA 32W	1	10,96 €
			5	9,97 €
			10	9,06 €
		ECO ERP Directives. 700-750mA constant current power supply.	40	8,39 €
	Length (mm): 108 Width (mm): 68 High (mm): 32 Voltage In (Vac): 220~240 Voltage Out (Vdc): 30~42 Intensidad Out (A): 0.7~0.75 Frecuency (Hz): 50~60 Power (W): 21~32 Room Temperature (°C): 0~+50 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.92  Reference: 122293			



	G503540F	Led Power Supply CC V9 700mA 40W	1	11,57 €
			5	9,65 €
			10	8,76 €
		ECO Design ERP Compliant. 700mA constant current output	50	8,18 €
	Length (mm): 127 Width (mm): 43 High (mm): 28 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 29~57 Intensidad In (A): 0.23 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 20~40 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			

