



Catalogue **LED TECHNOLOGY**
 Line **Electronic Led Power Supplies**
 Family **LED Power Supplies Constant Current**
 Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503703D		1	6,10 €
	Led Power Supply CC Mini-3.6-700 700mA 3.6W IP20		5	5,54 €
	ECO ERP Design. IP20. Constant current output 700mA.		10	5,03 €
			50	4,71 €
	Length (mm): 53 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 2.5~5 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 1.75~3.5 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.50			




	G503703		1	7,93 €
	LED Power Supply LED SLT3-700IS-1 700mA 1-3W		5	6,60 €
	ECO Design ERP Compliant. Constant current. Class II, 20cm cable in primary and secondary, IP20		20	6,01 €
			200	5,60 €
	Length (mm): 50 Width (mm): 30 High (mm): 20 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 2~4.2 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 1.4~2.9 Room Temperature (°C): -20~+45 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503504C		1	6,29 €
	Led Power Supply CV CC AED04-700ILS 5Vdc		10	5,24 €
	700mA 3,5W		50	4,76 €
	ECO Design ERP Compliant. LED power supply with constant voltage 5Vdc or constant current 700mA depending on load		200	4,45 €
	Length (mm): 51,5 Width (mm): 32,8 High (mm): 17 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~5 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 2~3.5 Room Temperature (°C): +45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			




	G503504C2		1	6,37 €
	DC Led Power Supply MINI-4-700mA 4W IP65		5	5,27 €
	ECO ERP Design. IP65. Constant current output 700mA		10	4,78 €
			50	4,54 €
	Length (mm): 48 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 2.5~6 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 2.1~4.2 Room Temperature (°C): -20~+60 Critical Temperature (°C): 85 Ingress Protection: IP65 Dimmable: NO Power factor: 0.60			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**


Picture	Article	Description	Lot	Price/Unit
	G503706J		1	11,10 €
	LED power supply CV CC SLT6-700IL-4 700mA (12Vdc) 6W		5	9,26 €
			10	8,41 €
			50	7,80 €
	ECO design according to ERP directives. Led Power supply voltage 12VDC or constant current 700mA depending on load			
	Length (mm): 68 Width (mm): 35 High (mm): 20 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~8.4 Intensidad Out (A): 0~0.7 Frequency (Hz): 50~60 Power (W): 0~6 Room Temperature (°C): -20~+40 Critical Temperature (°C): 70 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.40			




	G5035081B		1	8,45 €
	Led Power Supply CV CC AED08-700ILS 12Vdc 700mA 8 W		10	7,05 €
			50	6,40 €
			200	5,98 €
	ECO Design ERP Compliant. 12Vdc constant voltage LED power supply or 700mA constant current depending on load.			
	Length (mm): 79,5 Width (mm): 39 High (mm): 19 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 6~11 Intensidad Out (A): 0.625 Frequency (Hz): 50~60 Power (W): 4.2~7.7 Room Temperature (°C): -10~+45 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			



Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503715		1	14,09 €
	Led Power Supply LED SLT20-700IFG 700mA 20W		5	11,74 €
	6-29V		10	10,67 €
	Constant current Class II. EMC EN61000-3-2 class C.		50	9,97 €
	Length (mm): 166 Width (mm): 40 High (mm): 14 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 6~29 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 4.2~20 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			




	G503715A		1	17,62 €
	Led Power Supply CC SLT20-700IF-2S 700mA 20W		5	14,68 €
	ECO design according to ERP directives. Ultra flat 16mm. Constant current 700mA. Voltage range 220-240/6-29VDC. Class II. Full load efficiency >80%		10	13,34 €
			50	12,35 €
	Length (mm): 121 Width (mm): 45 High (mm): 16 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 6~29 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 4.2~20.3 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.85			




LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**


Picture	Article	Description	Lot	Price/Unit
	G503525B		1	9,22 €
	Led Power Supply CC V8 700mA 25W		5	7,67 €
	ECO Design ERP Compliant. 700mA constant current output		10	6,97 €
			50	6,51 €
	Length (mm): 127 Width (mm): 43 High (mm): 28 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 18~36 Intensidad In (A): 0.15 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 12.6~25 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			




	G503530C		1	8,83 €
	Led Power Supply CC V9 700mA 30W		5	7,35 €
	ECO Design ERP Compliant. 700mA constant current output		10	6,68 €
			50	6,25 €
	Length (mm): 116 Width (mm): 41 High (mm): 25 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 30~42 Intensidad In (A): 0.18 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 21~30 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			



Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	GTC30700		1	39,17 €
	Led CC power supply IPR2-30/700 700mA 30W		5	35,61 €
	ECO ERP design. 700mA constant current power supply.		10	32,37 €
			30	29,98 €
	Length (mm): 115 Width (mm): 53,5 High (mm): 26 Voltage In (Vac): 110~240 Voltage Out (Vdc): 5~43 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 3.5~30 Room Temperature (°C): -40~+60 Critical Temperature (°C): 90 Ingress Protection: IP68 Dimmable: NO Power factor: 0.97			
Reference: 152014/700				




	GTC32700		1	10,96 €
	Led Driver CC ECO 32-700-750mA 32W		5	9,97 €
	ECO ERP Directives. 700-750mA constant current power supply.		10	9,06 €
			40	8,39 €
	Length (mm): 108 Width (mm): 68 High (mm): 32 Voltage In (Vac): 220~240 Voltage Out (Vdc): 30~42 Intensidad Out (A): 0.7~0.75 Frecuency (Hz): 50~60 Power (W): 21~32 Room Temperature (°C): 0~+50 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.92			
Reference: 122293				



LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current

Subfamily **Electronic Led Power Supplies 700mA-3000mA**

Picture	Article	Description	Lot	Price/Unit
	G503540F		1	11,57 €
	Led Power Supply CC V9 700mA 40W		5	9,65 €
	ECO Design ERP Compliant. 700mA constant current output		10	8,76 €
			50	8,18 €
	Length (mm): 127 Width (mm): 43 High (mm): 28 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 29~57 Intensidad In (A): 0.23 Intensidad Out (A): 0.7 Frecuency (Hz): 50~60 Power (W): 20~40 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.95			

