









Catalogue **ELECTRICAL EQUIPMENT**
 Line **Terminal Blocks and Junction Boxes**
 FAmily **Terminal Blocks**
 Subfamily **End Terminal Blocks**





| Picture | Article | Description | Lot | Price/Unit |
|---|--|--|-----|------------|
|  | 491MR00 | | 1 | 1,90 € |
| | Terminal block 2,5mm 10 poles | | 10 | 1,69 € |
| | Transparent polycarbonate. Auto-extinguishing UL92V2 | | 25 | 1,37 € |
| | | | 450 | 1,21 € |
| | | Length (mm): 109 Width (mm): 18 High (mm): 20 Diameter (mm): 4 Section (mm2): 2,5 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | |
|  | | | | |
| | | | | |
|  | 491MR01 | | 1 | 2,64 € |
| | Terminal block 6mm 10 poles | | 10 | 2,35 € |
| | Transparent polycarbonate. Auto-extinguishing UL92V2 | | 25 | 1,89 € |
| | | | 450 | 1,72 € |
| | | Length (mm): 138 Width (mm): 22 High (mm): 25 Diameter (mm): 6 Section (mm2): 6 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | |
|  | | | | |
| | | | | |





Subfamily **End Terminal Blocks**

| Picture | Article | Description | Lot | Price/Unit |
|---|---|---|-----|------------|
|  | 491MR02 | | 1 | 4,88 € |
| | Terminal block 10mm 10 poles | | 5 | 4,34 € |
| | Transparent polycarbonate. Auto-extinguishing UL92V2 | | 10 | 3,48 € |
| | | | 300 | 3,17 € |
| | Length (mm): 158 Width (mm): 26 High (mm): 29 Diameter (mm): 7,5 Section (mm2): 10 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | | |
|  |  |  | | |





| | | | | |
|---|---|---|------|----------|
|  | 491MR03 | | 1 | 0,1772 € |
| | Terminal block 1.5mm 1 pole | | 50 | 0,1580 € |
| | Transparent polycarbonate. Auto-extinguishing UL92V2 | | 100 | 0,1264 € |
| | | | 2400 | 0,1149 € |
| | Width (mm): 16 High (mm): 15 Diameter (mm): 10 Section (mm2): 1,5 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | | |
|  |  |  | | |

Subfamily **End Terminal Blocks**

| Picture | Article | Description | Lot | Price/Unit |
|---|---|--|-----|------------|
|  | 491MR04 | | 1 | 2,29 € |
| | Terminal block 4mm 10 poles | | 10 | 2,04 € |
| | Transparent polycarbonate. Auto-extinguishing UL92V2 | | 25 | 1,63 € |
| | | | 450 | 1,48 € |
| | | Length (mm): 116 Width (mm): 20 High (mm): 22 Diameter (mm): 4,5 Section (mm2): 4 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | |
|  |  |  | | |

| | | | | |
|---|---|---|-----|--------|
|  | 491MR05 | | 1 | 5,99 € |
| | Terminal block 16mm 5 poles | | 5 | 5,34 € |
| | Transparent polycarbonate. Auto-extinguishing UL92V2 | | 10 | 4,28 € |
| | | | 240 | 3,87 € |
| | | Length (mm): 100 Width (mm): 31 High (mm): 35 Diameter (mm): 9,5 Section (mm2): 16 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | |
|  |  |  | | |

Subfamily **End Terminal Blocks**

| Picture | Article | Description | Lot | Price/Unit |
|---|---|---|-----|------------|
|  | 491MR06 | | 1 | 1,56 € |
| | Terminal block 1.5mm 10 poles | | 10 | 1,38 € |
| | Transparent polycarbonate. Auto-extinguishing UL92V2 | | 25 | 1,09 € |
| | | | 450 | 1,01 € |
| | Length (mm): 90 Width (mm): 16 High (mm): 15 Diameter (mm): 3,2 Section (mm2): 1,5 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | | |
|  |  |  | | |

| | | | | |
|---|--|---|-----|--------|
|  | 491MR07 | | 1 | 3,73 € |
| | Terminal block 25mm 1 pole | | 10 | 3,33 € |
| | Transparent polycarbonate. Self-extinguishing UL92V3 | | 50 | 2,65 € |
| | | | 100 | 2,42 € |
| | Width (mm): 40 High (mm): 39 Diameter (mm): 12 Section (mm2): 25 Colour: Transparent Voltage In (Vac): 450 Intensidad In (A): 17.4 Temperature (°C): 85 Connection: Screw | | | |
|  |  |  | | |