






Catalogue **ELECTRICAL EQUIPMENT**
 Line **Terminal Blocks and Junction Boxes**
 FAmily **Fiber Glass Terminal Blocks**
 Subfamily **Fiberglass-24A 2.5 mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR17		1	0,2453 €
	Terminal block OK431-FV 2.5mm 2 poles high		50	0,2188 €
	temperature		100	0,1749 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel		3000	0,1590 €
		Length (mm): 14,5 Width (mm): 16,5 High (mm): 14,7 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
	Reference: 4140217			



Subfamily **Fiberglass-24A 2.5 mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR18		1	0,3669 €
	Terminal block OK431-FV 2.5mm 3 poles high		50	0,3270 €
	temperature		100	0,2617 €
	Polyamide PA 6-6 with 25% fiber		2500	0,2379 €
	glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 22,5 Width (mm): 16,5 High (mm): 14,7 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4140317			
				
				

	491MR19		1	1,47 €
	Terminal block OK431-FV 2.5mm 12 poles high		20	1,31 €
	temperature		100	1,08 €
	Polyamide PA 6-6 with 25% fiber		1200	0,95 €
	glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 94,3 Width (mm): 16,5 High (mm): 14,7 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
	Reference: 4140090			
