




Catalogue **ELECTRICAL EQUIPMENT**
 Line **Terminal Blocks and Junction Boxes**
 Family **Fiber Glass Terminal Blocks**
 Subfamily **Fiberglass-32A 4mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR14		1	0,3383 €
	Terminal block OK433-FV 4mm 2 poles for high temperature		50	0,3015 €
			100	0,2412 €
			3000	0,2192 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel Length (mm): 17 Width (mm): 20,5 High (mm): 17,9 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw Reference: 4136217			




Subfamily **Fiberglass-32A 4mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MR15		1	0,5060 €
	Terminal block OK433-FV 4mm 3 poles high temperature		50	0,4511 €
			100	0,3609 €
			2000	0,3281 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 27 Width (mm): 20,5 High (mm): 17,9 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw			
	Reference: 4136317			
				
				
	491MRH4		1	0,3384 €
	Terminal block OK433/2 FV-H		50	0,3016 €
			100	0,2412 €
			3000	0,2194 €
	Polyamide PA 6-6 with 25% fiber glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel			
	Length (mm): 19,65 Width (mm): 20,5 High (mm): 19,4 Section (mm2): 4 Colour: Tile Voltage In (V): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw			
	Reference: 41422.17			
				
				

ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Fiber Glass Terminal Blocks

Subfamily **Fiberglass-32A 4mm2 terminal block**

Picture	Article	Description	Lot	Price/Unit
	491MRM4		1	0,3524 €
		Terminal block OK433-FV 4mm 2 poles marking L.N	50	0,3141 €
		high temperature	100	0,2510 €
		Polyamide PA 6-6 with 25% fiber	3000	0,2283 €
		glass.Auto-extinguishing UL94V0 . GWIT775C(EN 60695-2-13) y GWT750C (EN 60695-2-11). Metallic inserts in brass IT58, nickel plated. Screws in zinc plated steel		
		Length (mm): 17 Width (mm): 20,5 High (mm): 17,4 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 150 Connection: Screw		
		Reference: 4503017		

