



Catalogue **LED TECHNOLOGY**
 Line **LED Lamps HALOTEC**
 Family **LED Lamps HALOTEC**
 Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2901047		1	1,96 €
	Lamp Candle E14 LED 4W 100-250V 3000K matted		10	1,45 €
	CRI>80 Average life 30.000h. For 230V			
	Length (mm): 107 Diameter (mm): 38			
	Colour: Warm White Voltage In (Vac): 230			
	Frecuency (Hz): 50~60 Power (W): 4			
	Colour Temperature (°K): 3000 Lumen: 320			
	Socket: E14 Energy efficiency: A+ Kwh/1000h: 4			
	Dimmable: NO Power factor: >0,4			
	Switching cycle (≥): 15000			
	Warm-up time up to 60% of the full light output (sec): <0,5			
	Lumen maintenance factor at the end of the nominal li			
	fe: 0,70 Starting time (seg): <0,5			
	Colour consistency: <6 sdcn			




LED TECHNOLOGY > LED Lamps HALOTEC > LED Lamps HALOTEC


Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2901063		1	1,32 €
	Bulb Candle TP E14 LED 6W 230V 4000K matte		10	1,10 €
	Thermoplastic body		50	1,05 €
	Length (mm): 105 Diameter (mm): 37 Colour: Natural White Voltage In (Vac): 220~240 Frecuency (Hz): 50~60 Power (W): 6 Colour Temperature (°K): 4000 Lumen: 480 Angle (°): 145 Socket: E14 Energy efficiency: A+ Kwh/1000h: 6 Incandescence equivalence (W): 40 CRI (?): 80 Life (Hours): 25000 Dimmable: NO Power factor: >0.4 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <0.5 Lumen maintenance factor at the end of the nominal li fe: 0.7 Starting time (seg): <0.5 Colour consistency: <6 sdcm			




Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2911068		1	1,33 €
	Spherical bulb TP E14 LED 6W 230V 270K matt		10	1,11 €
	Thermoplastic body		50	1,05 €
	Length (mm): 80 Diameter (mm): 45 Colour: Warm White Voltage In (Vac): 220~240 Frecuency (Hz): 50~60 Power (W): 6 Colour Temperature (°K): 2700 Lumen: 480 Angle (°): 145 Socket: E14 Energy efficiency: A+ Kwh/1000h: 6 Incandescence equivalence (W): 40 CRI (?): 80 Life (Hours): 25000 Dimmable: NO Power factor: >0.4 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <0.5 Lumen maintenance factor at the end of the nominal life: 0.7 Starting time (seg): <0.5 Colour consistency: <6 sdcn			




LED TECHNOLOGY > LED Lamps HALOTEC > LED Lamps HALOTEC

Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2901053D		1	2,46 €
	Pack 2 units	Candle lamp LED TP E14 5W 230V	10	1,99 €
		4000K matt	20	1,90 €
	Thermoplastic body and matt glass			
	Length (mm): 113 Diameter (mm): 37			
	Colour: Natural White Voltage In (Vac): 230			
	Frecuency (Hz): 50~60 Power (W): 5			
	Colour Temperature (°K): 4000 Lumen: 400			
	Socket: E14 Energy efficiency: A+ Kwh/1000h: 5			
	Incandescence equivalence (W): 40 CRI (?): 80			
	Life (Hours): 25000 Dimmable: NO Power factor: >0.4			
	Switching cycle (?): 15000			
	Warm-up time up to 60% of the full light output (sec): <0.5			
	Lumen maintenance factor at the end of the nominal li			
	fe: 0.70 Starting time (seg): <0.5			
	Colour consistency: <6 sdcm			




Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2901058D		1	2,46 €
	Pack 2 units LED Bulb TP E14 LED 5W 230V 2700K matte		10	1,99 €
			20	1,90 €
	Thermoplastic body and matt glass Length (mm): 113 Diameter (mm): 37 Colour: Warm White Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 5 Colour Temperature (°K): 2700 Lumen: 400 Angle (°): 200 Socket: E14 Energy efficiency: A+ Kwh/1000h: 5 Incandescence equivalence (W): 40 CRI (?): 80 Life (Hours): 25000 Dimmable: NO Power factor: >0.4 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <0.5 Lumen maintenance factor at the end of the nominal life: 0.70 Starting time (seg): <0.5 Colour consistency: <6 sdcn			



LED TECHNOLOGY > LED Lamps HALOTEC > LED Lamps HALOTEC


Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2901057		1	1,96 €
	Candle lamp LED E14 5W 230V 3000°K matt		10	1,45 €
	CRI>80 Average life 30.000h. Equivalent to 40W incandescence		20	1,40 €
	Length (mm): 107 Diameter (mm): 38 Colour: Warm White Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 5 Colour Temperature (°K): 3000 Lumen: 400 Angle (°): 200 Socket: E14 Energy efficiency: A+ Kwh/1000h: 5 Incandescence equivalence (W): 40 CRI (?): 80 Life (Hours): 30000 Dimmable: NO Power factor: >0.4 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <0.5 Lumen maintenance factor at the end of the nominal li fe: 0.70 Starting time (seg): <0.5 Colour consistency: <6 sdcn			



LED TECHNOLOGY > LED Lamps HALOTEC > LED Lamps HALOTEC


Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2911053D		1	2,46 €
	Pack 2 units Spherical lamp LED E14 TP 5W 230V 4000K matt		10	1,99 €
			20	1,90 €
	<p>CRI>80 Average life 30.000h. Equivalent to 40W incandescence</p> <p>Length (mm): 80 Diameter (mm): 45 Colour: Natural White Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 5 Colour Temperature (°K): 4000 Lumen: 400 Angle (°): 145 Socket: E14 Energy efficiency: A+ Kwh/1000h: 5 Incandescence equivalence (W): 40 CRI (?): 80 Life (Hours): 25000 Dimmable: NO Power factor: >0.4 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <0.5 Lumen maintenance factor at the end of the nominal li fe: 0.70 Starting time (seg): <0.5 Colour consistency: <6 sdcn</p>			



LED TECHNOLOGY > LED Lamps HALOTEC > LED Lamps HALOTEC

Subfamily **Led Lamps E14**

Picture	Article	Description	Lot	Price/Unit
	E2911057		1	1,96 €
		Spherical lamp LED E14 5W 230V 3000°K matt	10	1,45 €
		CRI>80 Average life 30.000h. Equivalent to 40W incandescence	20	1,40 €
		Length (mm): 78 Diameter (mm): 45 Colour: Warm White Voltage In (Vac): 230 Frecuency (Hz): 50~60 Power (W): 5 Colour Temperature (°K): 3000 Lumen: 400 Socket: E14 Energy efficiency: A+ Kwh/1000h: 5 Incandescence equivalence (W): 40 CRI (?): 80 Life (Hours): 30000 Dimmable: NO Power factor: >0,4 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <0,5 Lumen maintenance factor at the end of the nominal life: 0,70 Starting time (seg): <0,5 Colour consistency: <6 sdcm		

