


Catalogue **LED TECHNOLOGY**
Line **Electronic Led Power Supplies**
FAMILY **LED Power Supplies Constant Current**
Subfamily **Led Power Supplies 500mA-600mA**


Picture	Article	Description	Lot	Price/Unit
	G503603A		1	6,10 €
	Led Power Supply CC Miniu-3.6-500 500mA 3.6W		5	5,54 €
	IP20		10	5,03 €
	ECO ERP Design. IP20. Constant current output 500mA.		50	4,71 €
	Length (mm): 53 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 2.5~7 Intensidad Out (A): 0.5 Frecuency (Hz): 50~60 Power (W): 1.25~3.5 Room Temperature (°C): -20~+50 Critical Temperature (°C): 80 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.50			




	G503504B		1	6,29 €
	Led Power Supply CC AED04-500ILS 500mA 4W		5	5,24 €
	ECO Design ERP Compliant. Constant current 500mA		10	4,76 €
			50	4,45 €
	Length (mm): 51,5 Width (mm): 32,8 High (mm): 17 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~10.5 Intensidad Out (A): 0.5 Frecuency (Hz): 50~60 Power (W): 1.5~5.2 Room Temperature (°C): +45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5			



Subfamily **Led Power Supplies 500mA-600mA**


Picture	Article	Description	Lot	Price/Unit
	G503504B3		1	6,37 €
	DC Led Power Supply MINI-4-500mA 4W IP65		5	5,27 €
	ECO ERP Design. IP65. Constant current output 500mA		10	4,78 €
			50	4,54 €
	Length (mm): 48 Width (mm): 27 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 4~8 Intensidad Out (A): 0.5 Frecuency (Hz): 50~60 Power (W): 2.1~4.2 Room Temperature (°C): -20~+60 Critical Temperature (°C): 85 Ingress Protection: IP65 Dimmable: NO Power factor: 0.60			



	G503606B		1	11,10 €
	Led Power Supply CC SLT6-500IL-4 500mA 6W		5	9,26 €
	ECO design according ERP directives. Constant current 500mA. Output voltage range 3-12dc. Class II.		10	8,41 €
			50	7,80 €
	Length (mm): 68 Width (mm): 35 High (mm): 20 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~12 Intensidad Out (A): 0~0.5 Frecuency (Hz): 50~60 Power (W): 1.5~6 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.40			



Subfamily **Led Power Supplies 500mA-600mA**

Picture	Article	Description	Lot	Price/Unit
	GTC21500		1	6,90 €
	Led Driver CC ECO 21-500 500mA 21W		5	6,28 €
	ECO ERP Directives. 500mA constant current power supply.		10	5,71 €
			50	5,28 €
	Length (mm): 115 Width (mm): 45 High (mm): 29 Voltage In (Vac): 220~240 Voltage Out (Vdc): 32~42 Intensidad Out (A): 0.5 Frecuency (Hz): 50~60 Power (W): 16~21 Room Temperature (°C): 0~+50 Critical Temperature (°C): 75 Ingress Protection: IP20 Dimmable: NO Power factor: 0.9 Reference: 122291			

