


Catalogue **HALOTEC HARDWARE**

Line **Halotec Lamps**

FAMILY **LED Lamps HALOTEC**


Subfamily **Led Tubes T8**

Led tubes T8

Picture	Article	Description	Lot	Price/Unit
	E282091		1	3,00 €
	T8 LED Tube 60cm 9W 700lm 4000K Neutral white		10	2,45 €
		Integrated electronics. Simple and direct to the phase and neutral connection without any additional element. Its angle of 270 degrees does not require rotary lampholder		30
		Length (mm): 602 Diameter (mm): 30 Colour: Natural White Voltage In (Vac): 180~264 Frecuency (Hz): 50~60 Power (W): 9 Room Temperature (°C): -20~+70 Colour Temperature (°K): 4000 Lumen: 700 Angle (°): 270 Socket: G13 Energy efficiency: A+ Kwh/1000h: 9 CRI (≥): 80 Life (Hours): 25000 Dimmable: NO Power factor: >0.9 Switching cycle (≥): 15000 Warm-up time up to 60% of the full light output (sec): <2.0 Lumen maintenance factor at the end of the nominal life: 0.70 Starting time (seg): <0.5 Colour consistency: <6 sdcn		




Subfamily **Led Tubes T8**

Picture	Article	Description	Lot	Price/Unit
	E282092		1	3,30 €
	T8 LED Tube 60cm 9W 750lm 6500K cool white		10	2,45 €
		Integrated electronics. Simple and direct to the phase and neutral connection without any additional element. Its angle of 270 degrees does not require rotary lampholder		30
		Length (mm): 602 Diameter (mm): 30 Colour: Cool white Voltage In (Vac): 180~264 Frecuency (Hz): 50~60 Power (W): 9 Room Temperature (°C): -20~+70 Colour Temperature (°K): 6500 Lumen: 750 Angle (°): 270 Socket: G13 Energy efficiency: A++ Kwh/1000h: 9 CRI (?): 80 Life (Hours): 25000 Dimmable: NO Power factor: >0.9 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <2.0 Lumen maintenance factor at the end of the nominal life: 0.70 Starting time (seg): <0.5 Colour consistency: <6 sdcn		



Subfamily **Led Tubes T8**



Picture	Article	Description	Lot	Price/Unit
	E282241		1	5,70 €
	Tube LED T8 150cm 24W 2300lm 4000K neutral		10	4,30 €
	white 		30	4,10 €

Integrated electronics. Simple and direct to the phase and neutral connection without any additional element. Its angle of 270 degrees does not require rotary lampholder

Length (mm): 1512 Diameter (mm): 30
 Colour: Natural White Voltage In (Vac): 180~264
 Frecuency (Hz): 50~60 Power (W): 24
 Room Temperature (°C): -20~+70
 Colour Temperature (°K): 4000 Lumen: 2300
 Angle (°): 270 Socket: G13 Energy efficiency: A+
 Kwh/1000h: 24 CRI (?): 80 Life (Hours): 25000
 Dimmable: NO Power factor: >0.9
 Switching cycle (?): 15000
 Warm-up time up to 60% of the full light output (sec): <2.0
 Lumen maintenance factor at the end of the nominal life: 0.70 Starting time (seg): <0.5
 Colour consistency: <6 sdcm



Subfamily **Led Tubes T8**

Picture	Article	Description	Lot	Price/Unit
	E282242		1	5,70 €
	T8 LED Tube 150cm 24W 2400lm 6500K cool white		10	4,30 €
		Integrated electronics. Simple and direct to the phase and neutral connection without any additional element. Its angle of 270 degrees does not require rotary lampholder	30	4,10 €
		Length (mm): 1512 Diameter (mm): 30 Colour: Cool white Voltage In (Vac): 180~264 Frecuency (Hz): 50~60 Power (W): 24 Room Temperature (°C): -20~+70 Colour Temperature (°K): 6500 Lumen: 2400 Angle (°): 270 Socket: G13 Energy efficiency: A+ Kwh/1000h: 24 CRI (?): 80 Life (Hours): 25000 Dimmable: NO Power factor: >0.9 Switching cycle (?): 15000 Warm-up time up to 60% of the full light output (sec): <2.0 Lumen maintenance factor at the end of the nominal li fe: 0.70 Starting time (seg): <0.5 Colour consistency: <6 sdcn		

