



Catalogue **ELECTRICAL EQUIPMENT**
 Line **Terminal Blocks and Junction Boxes**
 FAmily **Terminal Blocks Nylon**
 Subfamily **Nylon 4mm2-32A terminal blocks**


Picture	Article	Description	Lot	Price/Unit
	491MRS4		1	0,3114 €
	Terminal block OK433-NY 4mm 2 poles		50	0,2774 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	0,2219 €
			3000	0,2018 €
		Length (mm): 17 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw		
	Reference: 4111707			



Subfamily **Nylon 4mm2-32A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MRS5		1	0,4667 €
	Terminal block OK433-NY 4mm 3 poles		50	0,4161 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	0,3328 €
			2000	0,3028 €
	Length (mm): 27 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw			
	Reference: 4111807			




	491MRS6		1	1,87 €
	Terminal block OK433-NY 4mm 12 poles		20	1,66 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2. Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		100	1,37 €
			450	1,21 €
	Length (mm): 116,7 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw			
	Reference: 4111590			



ELECTRICAL EQUIPMENT > Terminal Blocks and Junction Boxes > Terminal Blocks Nylon

Subfamily **Nylon 4mm2-32A terminal blocks**

Picture	Article	Description	Lot	Price/Unit
	491MRT4		1	0,3271 €
	Terminal block OK433-NY 4mm 2 poles marking L.N		50	0,2915 €
	Natural polyamide 6-6, Auto-extinguishing UL94V2.		100	0,2332 €
	Working temperature of T110 C GWIT775 C (EN 60695-2-13). Metallic inserts in brass OT58 nickel plated. Crews in zinc plated steel		3000	0,2120 €
	Length (mm): 17 Width (mm): 20,2 High (mm): 17,3 Section (mm2): 4 Colour: Neutral Voltage In (Vac): 450 Intensidad In (A): 32 Temperature (°C): 110 Connection: Screw Reference: 4503007			

