
















Catalogue **ELECTRICAL EQUIPMENT**  
 Line **Terminal Blocks and Junction Boxes**  
 FAmily **Fiber Glass Terminal Blocks**  
 Subfamily **Fiberglass Plug-in Power Strips**



Picture	Article	Description	Lot	Price/Unit
	B3RE802F		1	0,3173 €
	Terminal block female OK431 FV-SPF 2 poles 2,5mm2.		10	0,2115 €
			100	0,1763 €
			1500	0,1677 €
		Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)		
		Length (mm): 16 Width (mm): 16,3 High (mm): 15 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
		Reference: 4170228		
				
	B3RE802M		1	0,68 €
	Terminal block male OK431 FV-SPM 2 poles 2,5mm2.		10	0,4529 €
			100	0,3774 €
			1500	0,3595 €
		Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)		
		Length (mm): 16 Width (mm): 16,3 High (mm): 15 Section (mm2): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
		Reference: 4170227		
				



Subfamily **Fiberglass Plug-in Power Strips**

Picture	Article	Description	Lot	Price/Unit
	B3RE803		1	1,72 €
	Terminal block male-female OK431 FV-SP 3 poles		10	1,14 €
	2.5mm <sup>2</sup>		100	0,95 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		1500	0,91 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
		Length (mm): 23,1 Width (mm): 32,8 High (mm): 14,7 Section (mm <sup>2</sup> ): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
				

	B3RE804		1	2,34 €
	Terminal block male-female OK431 FV-SP 4 poles		10	1,57 €
	2.5mm <sup>2</sup>		50	1,31 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		750	1,22 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
		Length (mm): 31,1 Width (mm): 32,8 High (mm): 14,7 Section (mm <sup>2</sup> ): 2,5 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw		
				


Subfamily **Fiberglass Plug-in Power Strips**

Picture	Article	Description	Lot	Price/Unit
	B3RE902		1	1,43 €
	Terminal block male-female OK433 FV-SP 2 poles		10	0,95 €
	4mm2		100	0,79 €
			1000	0,75 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 17,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
				

	B3RE903		1	2,18 €
	Terminal block male-female OK433 FV-SP 3 poles		10	1,46 €
	4mm2		100	1,21 €
			700	1,13 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 27,7 Width (mm): 40,2 High (mm): 16,6 Section (mm2): 4 Colour: Tile Voltage In (Vac): 450 Intensidad In (A): 24 Temperature (°C): 150 Connection: Screw			
				

ELECTRICAL EQUIPMENT &gt; Terminal Blocks and Junction Boxes &gt; Fiber Glass Terminal Blocks

Subfamily **Fiberglass Plug-in Power Strips**

Picture	Article	Description	Lot	Price/Unit
	B3RE904		1	2,86 €
	Terminal block male-female OK433 FV-SP 4 poles		10	1,90 €
	4mm <sup>2</sup>		100	1,57 €
	Polyamid PA6-6 with 25 % fiber glass auto-extinguible		500	1,52 €
	UL94V0 T150 C GWT750 C (EN60695-2-11)			
	Length (mm): 37,7 Width (mm): 40,2 High (mm): 16,6			
	Section (mm <sup>2</sup> ): 4 Colour: Tile Voltage In (Vac): 450			
	Intensidad In (A): 24 Temperature (°C): 150			
	Connection: Screw			

