

STEAB ACCESORIES > STEAB insulating fittings > STEAB Lighting
Junction Boxes For Class I and II

16559303

5593/4 /// 122 3x1.5 3-pole connection box with Nylon66-AE sleeve

December 03rd, 2024, 18:36



DESCRIPTION

Caja de conexión tripolar aislante de 9 mm de espesor con cierre a presión. Se suministra montada con manguito de goma. Para luminarias en clase I. Conexión 3x1,5mm². Usando el manguito para cables unipolares de 1,5mm² máximo. Sin el uso del manguito para cables manguera hasta máximo 6,5mm de diámetro. Material autoextinguible V-O. Resistente a la prueba del hilo incandescente 850°.

PRICE

	Lot	P.V.P. excluding VAT
	1	1,38€
	50	0,92€
	250	0,63€
	1250	0,5816€



Continued on next page >>

16559303

5593/4 /// 122 3x1.5 3-pole connection box with Nylon66-AE sleeve

TECHNICAL SPECIFICATIONS

CERTIFICADOS



Weight: 11 Grams

NOTES

For class I. With rubber tube and assembled connectors, wire test resistant 850h

OTHER FEATURES

Length (mm): 132

Width (mm): 30

High (mm): 9

Colour: White

Voltage In (Vac): 250

Intensidad In (A): 4

Ingress Protection: IP20

DOCUMENTS

 [Mounting instructions](#)

 [5593/4 /// 122 3x1.5 3-pole connection box with Nylon66-AE sleeve](#)

 [SEMKO \(Sweden\)](#)