

16559303

5593/4 /// 122 3x1.5 3-pole connection box with Nylon66-AE sleeve

April 04th, 2025, 14:33



## DESCRIPTION

Caja de conexión tripolar aislante de 9 mm de espesor con cierre a presión. Se suministra montada con manguito de goma. Para luminarias en clase I. Conexión 3x1,5mm<sup>2</sup>. Usando el manguito para cables unipolares de 1,5mm<sup>2</sup> máximo. Sin el uso del manguito para cables manguera hasta máximo 6,5mm de diámetro. Material autoextinguible V-O. Resistente a la prueba del hilo incandescente 850°.

## PRICE

	Lot	P.V.P. excluding VAT
	1	1,42€
	50	0,95€
	250	0,65€
	1250	0,5984€



Continued on next page >>

16559303

5593/4 /// 122 3x1.5 3-pole connection box with Nylon66-AE sleeve

## TECHNICAL SPECIFICATIONS

---

### CERTIFICADOS



Weight: 11 Grams

## NOTES

---

For class I. With rubber tube and assembled connectors, wire test resistant 850h

## OTHER FEATURES

---

Length (mm): 132

Width (mm): 30

High (mm): 9

Colour: White

Voltage In (Vac): 250

Intensidad In (A): 4

Ingress Protection: IP20

## DOCUMENTS

---

 [Mounting instructions](#)

 [5593/4 /// 122 3x1.5 3-pole connection box with Nylon66-AE sleeve](#)

 [SEMKO \(Sweden\)](#)