

16562508

Junction box IP68 5625 Paguro with 4 exits and 3 poles black

January 31st, 2025, 05:16



DESCRIPTION

Caja de conexión estanca provista de regleta 3x4mm² y gel aislante en su interior que una vez cerrada garantiza la máxima estanqueidad IP68 (totalmente estanco a la inmersión prolongada a profundidad de hasta 1.3 metros) La instalación de las Cajas Paguro es muy sencilla y hay que seguir las instrucciones de montaje y esquemas de conexión que en cada caso da el fabricante. Las cajas están fabricadas en Nylon PA66 con 25% de aditivo de fibra de vidrio, autoextingible V0 , resistente a los rayos UV y a T120°C en uso continuo
El gel de silicona es transparente, no toxico, ligero, sin latex y con retardador de llama. Es estable entre -30°C y 130°C

PRICE

Lot	P.V.P. excluding VAT
1	14,08€
10	10,43€
50	9,66€



16562508

Junction box IP68 5625 Paguro with 4 exits and 3 poles black

TECHNICAL SPECIFICATIONS

SYMBOLS



Weight: 94 Grams

CERTIFICADOS



Packging: Box 10 Units

NOTES

For neoprene or PVC cables from 6.5 to 12mm external diameter. 3x2.5mm² terminal block. With internal gel for IP68.

OTHER FEATURES

Length (mm): 105

Width (mm): 44

High (mm): 24

Colour: Black

Voltage In (Vac): 250

Intensidad In (A): 16

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [Mounting instructions](#)

 [Junction box IP68 5625 Paguro with 4 exits and 3 poles black](#)

 [SEMKO \(Sweden\)](#)