

16563302

5633/6////86 Junction device IP68 Paguro for LED RGB 2 exits 4/6 poles

December 22nd, 2024, 03:49



DESCRIPTION

IP 68 connection box (1.3 meters deep) with gel to ensure total insulation, provided with 1 connection strip of 4x 2.5 mm² and cable holder for welding of 6x0,50mm². For neoprene cables with external diameter 8 to 10 mm, closing by self-tapping stainless steel screw. Built-in presacable. Packed with all its components including instruction manual in a single bag.

PRICE

	Lot	P.V.P. excluding VAT
	1	12,01€
	10	8,91€
	50	8,24€



Continued on next page >>

16563302

5633/6////86 Junction device IP68 Paguro for LED RGB 2 exits 4/6 poles

TECHNICAL SPECIFICATIONS

SYMBOLS



Weight: 44 Grams

Packging: Box 10 Units

NOTES

For double insulation round cable 4 or 6 conductors min 5.8 max 10.5mm

OTHER FEATURES

Length (mm): 38

Width (mm): 42,5

High (mm): 29,5

Colour: Grey

Voltage In (Vdc/ac): 12~24

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [Mounting instructions](#)

 [5633/6////86 Junction device IP68 Paguro for LED RGB 2 exits 4/6 poles](#)