

16565001

Junction device IP68 Paguro 5650 2 exits 3poles Nylon66-RV-AE

November 23rd, 2024, 09:15



DESCRIPTION

Connection box provided with 3x2.5mm² strip and insulating gel inside which, once closed, guarantees maximum IP68 tightness (totally sealed to prolonged immersion at depths of up to 1.3 meters). The installation of the Paguro Boxes is very simple and follow the assembly instructions and connection diagrams given by the manufacturer in each case. The boxes are made of PA66 Nylon with 25% glass fiber additive, self-extinguishing V0, resistant to UV rays and T120°C in continuous use

PRICE

Lot	P.V.P. excluding VAT
1	12,14€
10	9,01€
50	8,32€



Continued on next page >>

16565001

Junction device IP68 Paguro 5650 2 exits 3poles Nylon66-RV-AE

TECHNICAL SPECIFICATIONS

SYMBOLS



Weight: 70 Grams

CERTIFICADOS



Packging: Box 10 Units

NOTES

For Neopren or PVC cable. Connecting block 3x2,5mm². With interior gel for IP68

OTHER FEATURES

Length (mm): 100

Diameter (mm): 29

Colour: Black

Voltage In (Vac): 250

Intensidad In (A): 16

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [Mounting instructions](#)

 [Junction device IP68 Paguro 5650 2 exits 3poles Nylon66-RV-AE](#)

 [Video](#)

 [SEMKO \(Sweden\)](#)