

STEAB ACCESORIES > PAGURO IP68 > Junction Boxes Micro Paguro IP68
Junction Boxes Micro Paguro IP68 4 ways

16566402

5664/20/221 parallel connection box IP68 Paguro 4 outputs

February 01st, 2025, 20:36



DESCRIPTION

IP 68 connection box (1.3 meters deep) with gel to ensure total insulation, provided with 2 1.5 mm² double metal connectors installed in the box, For bipolar round cable hose with external diameter 4.5 a 8.5 mm, closing with 3 self-tapping stainless steel screws. With presacables. For connection of led spotlights in parallel to the feeder. see assembly diagram of up to 5 led to the feeder using 2 boxes in attached technical sheet. According to standard EN60998-2-1: 2004. Packed with all its components including instruction manual in a single bag.

PRICE

	Lot	P.V.P. excluding VAT
	1	13,90€
	10	10,31€
	100	9,54€



Continued on next page >>

16566402

5664/20/221 parallel connection box IP68 Paguro 4 outputs

TECHNICAL SPECIFICATIONS

SYMBOLS



Weight: 53 Grams

CERTIFICADOS



Packging: Box 10 Units

NOTES

Cable outer diameter of 4.5 to 7.5 mm. 2x1mm² connection. Gel contains inside IP68. 2x1.5 double connection terminals. LED bulbs for parallel connection with feeder. with presacable

OTHER FEATURES

Length (mm): 80

Width (mm): 39,5

High (mm): 19,5

Colour: Black

Voltage In (Vac): 250

Intensidad In (A): 6

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [Mounting instructions](#)

 [5664/20/221 parallel connection box IP68 Paguro 4 outputs](#)

 [SEMKO \(Sweden\)](#)