

16566501

**Junction device 5665 micro IP68 Paguro 2 exits 2 poles**

December 22nd, 2024, 04:04



**DESCRIPTION**

Connection box provided with metallic terminals of 2x0.75mm<sup>2</sup> and insulating gel inside which, once closed, guarantees the maximum IP68 tightness (totally watertight at prolonged immersion depth up to 1.3 meters). The installation of the Paguro Boxes is very simple and it is necessary to follow the assembly instructions and connection diagrams that the manufacturer gives in each case. The boxes are manufactured in Nylon PA66 with 25% glass fiber additive, self-extinguishing V0, resistant to UV rays and to T120°C in continuous use

**PRICE**

	Lot	P.V.P. excluding VAT
	1	7,53€
	20	5,58€
	100	5,16€



Continued on next page >>

16566501

Junction device 5665 micro IP68 Paguro 2 exits 2 poles

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



### CERTIFICADOS



Weight: 21 Grams

Packging: Box 20 Units

## NOTES

---

For Neopren cable. Connecting block 2x2,5mm<sup>2</sup>. With interior gel for IP68

## OTHER FEATURES

---

Length (mm): 44

Width (mm): 27

High (mm): 17,5

Colour: Black

Voltage In (Vac): 250

Intensidad In (A): 6

Ingress Protection: IP68

## DOCUMENTS

---

 [Data Sheet](#)

 [Mounting instructions](#)

 [Junction device 5665 micro IP68 Paguro 2 exits 2 poles](#)

 [SEMKO \(Sweden\)](#)