

G5K000P1

Battery 805050 with 10cm AWG22 cable and connector

April 05th, 2025, 07:33



DESCRIPTION

Lithium Polymer Battery with 10cm cable and connector to the control board. Capacity 2500mAh. 3.7Vdc.9.25Wh. Life cycles 400-500.

Charge via USB and charger with 5Vdc output. With charging current limiter. Approximate charging time 5 hours. Certified US7217127901 to UL1642:2012 R6.15.

It is advisable to charge the batteries at least every 3 months.

During storage. "First IN, first OUT" is recommended. The storage time of batteries in the warehouse is around 12 months.

PRICE

Lot	P.V.P. excluding VAT
1	8,42€
10	7,67€
50	6,98€
100	6,64€



G5K000P1

Battery 805050 with 10cm AWG22 cable and connector

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 49 Grams

Packaging: Box 1 Unit

NOTES

With AWG22 cable and connector. Battery compatible with the G5K000P0 and G5K000P02 modules. The battery must be connected after connecting the touch control. "

OTHER FEATURES

Length (mm): 50

Width (mm): 50

High (mm): 8

Voltage In (Vdc): 3.7

Ingress Protection: IP20

DOCUMENTS

 [Data Sheet](#)

 [Battery Data Sheet](#)

 [CE](#)