

4960008 - 4619700

Connection box OK603/2 2 poles 1.5mm. IP44 class II white

February 22nd, 2025, 07:41



DESCRIPTION

Two-pole connection box IP44 with double insulation in Polyamide PA6.6 UL94V2 for operating temperature 105°C for appliances with class II insulation. Fixation with 4 holes diam. 3.2mm for M3 screws (not included). For H05VV-F and H05SS-F 2x1.5mm² cables with a diameter of 6 to 8.5mm. Without cable clamp. Complete protection against dust and water. IP68 can be obtained with the use of a sealing gel.

PRICE

| | Lot | P.V.P. excluding VAT |
|--|-----|----------------------|
| | 1 | 1,38€ |
| | 10 | 0,95€ |
| | 100 | 0,85€ |
| | 300 | 0,79€ |



Continued on next page >>

4960008 - 4619700

Connection box OK603/2 2 poles 1.5mm. IP44 class II white

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 10 Grams

NOTES

Class II PA66 Polyamide Auto-extinguishing UL94V2. Terminal included, fixation with 4 screws M3

OTHER FEATURES

Length (mm): 57,5

Width (mm): 31

High (mm): 13,4

Section (mm²): 1,5

Colour: White

Voltage In (Vac): 450

Intensidad In (A): 17.5

Temperature (°C): 105

Ingress Protection: IP44

DOCUMENTS

 [Data Sheet](#)

 [IMQ \(Italy\)](#)

 [VDE \(Germany\)](#)