

4960008 - 4619700

Connection box OK603/2 2 poles 1.5mm. IP44 class II white

December 22nd, 2024, 02:56



DESCRIPTION

Two-pole connection box IP44 with double insulation in Polyamide PA6.6 UL94V2 for operating temperature 105°C for appliances with class II insulation. Fixation with 4 holes diam. 3.2mm for M3 screws (not included). For H05VV-F and H05SS-F 2x1.5mm² cables with a diameter of 6 to 8.5mm. Without cable clamp. Complete protection against dust and water. IP68 can be obtained with the use of a sealing gel.

PRICE

	Lot	P.V.P. excluding VAT
	1	1,38€
	10	0,95€
	100	0,85€
	300	0,79€



Continued on next page >>

4960008 - 4619700

Connection box OK603/2 2 poles 1.5mm. IP44 class II white

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 10 Grams

NOTES

Class II PA66 Polyamide Auto-extinguishing UL94V2. Terminal included, fixation with 4 screws M3

OTHER FEATURES

Length (mm): 57,5

Width (mm): 31

High (mm): 13,4

Section (mm²): 1,5

Colour: White

Voltage In (Vac): 450

Intensidad In (A): 17.5

Temperature (°C): 105

Ingress Protection: IP44

DOCUMENTS

 [Data Sheet](#)

 [IMQ \(Italy\)](#)

 [VDE \(Germany\)](#)