

4960008A - 4617795

Connection box OK603/2 2 poles 1.5mm. IP44 class II cable gland

February 22nd, 2025, 07:22



DESCRIPTION

Two-pole connection box IP44 with double insulation in Polyamide PA6.6 UL94V2 for operating temperature 105°C for appliances with class II insulation. Fixation with 4 holes diam. 3.2mm for M3 screws (not included). For H05VV-F and H05SS-F 2x1.5mm² cables with a diameter of 6 to 8.5mm. With cable clamp. Complete protection against dust and water. IP68 can be obtained with the use of a sealing gel.

PRICE

Lot	P.V.P. excluding VAT
1	1,66€
10	1,14€
100	1,01€
300	0,96€



Continued on next page >>

4960008A - 4617795

Connection box OK603/2 2 poles 1.5mm. IP44 class II cable gland

TECHNICAL SPECIFICATIONS

SYMBOLS



Weight: 10 Grams

CERTIFICADOS



Packging: Box 300 Units

NOTES

Class II PA66 Polyamide, Auto-extinguishing UL94V2. conection terminal included, cable clamp

OTHER FEATURES

Length (mm): 67

Width (mm): 40

High (mm): 13,4

Section (mm²): 1,5

Colour: White

Voltage In (Vac): 450

Intensidad In (A): 17.5

Temperature (°C): 105

Connection: Screw

Ingress Protection: IP44

DOCUMENTS

 [Data Sheet](#)

 [IMQ](#)

 [VDE \(Germany\)](#)