

4960013

Boîte de connexion OK603/3 3 pôles 1,5mm. IP44 classe II blanc pour câ

January 03rd, 2025, 05:52



DESCRIPTION

Two-pole IP44 double-insulated junction box made of Polyamide PA6.6 UL94V2 for operating temperature 105°C for devices with class II insulation. Fixing with 4 holes diam. 3.2mm for M3 screws (not included). For H05VV-F and H05SS-F 2x1.5mm² cables with diameter from 6 to 8.5mm. Without cable gland. Complete protection against dust and water. IP68 can be obtained with the use of a sealing gel.

PRICE

	Lot	P.V.P. excluding VAT
	1	1,17€
	10	0,81€
	100	0,70€
	300	0,65€

Continued on next page >>

4960013

Boîte de connexion OK603/3 3 pôles 1,5mm. IP44 classe II blanc pour câ

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 13 Grams

NOTES

Class II Polyamide PA66, self-extinguishing UL94V2. Includes connection strip. Without cable gland

OTHER FEATURES

Length (mm): 57,5

Width (mm): 31

High (mm): 13,4

Section (mm²): 1,5

Colour: White

Voltage In (Vac): 450

Intensidad In (A): 17.5

Temperature (°C): 105

Ingress Protection: IP44

DOCUMENTS

 [Data Sheet](#)

 [IMQ](#)

 [VDE \(Germany\)](#)