

4960013

Boîte de connexion OK603/3 3 pôles 1,5mm. IP44 classe II blanc pour câ

November 23rd, 2024, 10:31



## DESCRIPTION

Two-pole IP44 double-insulated junction box made of Polyamide PA6.6 UL94V2 for operating temperature 105°C for devices with class II insulation. Fixing with 4 holes diam. 3.2mm for M3 screws (not included). For H05VV-F and H05SS-F 2x1.5mm<sup>2</sup> cables with diameter from 6 to 8.5mm. Without cable gland. Complete protection against dust and water. IP68 can be obtained with the use of a sealing gel.

## PRICE

|  | Lot | P.V.P. excluding VAT |
|--|-----|----------------------|
|  | 1   | 1,17€                |
|  | 10  | 0,81€                |
|  | 100 | 0,70€                |
|  | 300 | 0,65€                |

Continued on next page >>

4960013

Boîte de connexion OK603/3 3 pôles 1,5mm. IP44 classe II blanc pour câ

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



### CERTIFICADOS



Weight: 13 Grams

## NOTES

---

Class II Polyamide PA66, self-extinguishing UL94V2. Includes connection strip. Without cable gland

## OTHER FEATURES

---

Length (mm): 57,5

Width (mm): 31

High (mm): 13,4

Section (mm<sup>2</sup>): 1,5

Colour: White

Voltage In (Vac): 450

Intensidad In (A): 17.5

Temperature (°C): 105

Ingress Protection: IP44

## DOCUMENTS

---

 [Data Sheet](#)

 [IMQ](#)

 [VDE \(Germany\)](#)