

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations
Derivations with screw IP68 cable section 2.5mm² 24A -400V

498M20T3 - 4533300

Connector Bypass with screws IP68 OK-M20T 3 poles 2,5mm²

December 22nd, 2024, 03:15



DESCRIPTION

3-pole connector. Black PA6.6 polyamide. Self-extinguishing UL.94V0-GWIT775°C. Operating temperature T105°C. Nickel-plated OT58 brass terminals, galvanized steel screws and silicone gasket.

PRICE

	Lot	P.V.P. excluding VAT
	1	8,26€
	5	6,60€
	25	6,29€
	75	5,99€

Continued on next page >>

498M20T3 - 4533300

Connector Bypass with screws IP68 OK-M20T 3 poles 2,5mm²

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 70 Grams

NOTES

Cable section 2.5mm²- 24A-400V and AWG14-15A-300V

OTHER FEATURES

Length (mm): 68

Width (mm): 104

Section (mm²): 2,5

Colour: Black

Voltage In (Vac): 400

Intensidad In (A): 24

Temperature (°C): 105

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic compatibility TÜV SÜD](#)