

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations
Derivations with screw IP68 cable section 6mm² 41A -400V

498M25X3 - 4534800

Connector Bypass with screws IP68 OK-M25X 3 poles 6mm²

December 03rd, 2024, 18:41



DESCRIPTION

3-pole connector. Black PA6.6 polyamide. Self-extinguishing UL.94V0-GWIT775°C. Operating temperature T105°C. Nickel-plated OT58 brass terminals, galvanized steel screws and silicone gasket.

PRICE

	Lot	P.V.P. excluding VAT
	1	17,64€
	5	14,11€
	10	13,44€
	30	12,80€

Continued on next page >>

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations
Derivations with screw IP68 cable section 6mm² 41A -400V

498M25X3 - 4534800

Connector Bypass with screws IP68 OK-M25X 3 poles 6mm²

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 80 Grams

NOTES

Cable section 6mm²- 41A-400V and AWG10-30A-300V

OTHER FEATURES

Length (mm): 131

Width (mm): 126

Section (mm²): 6

Colour: Black

Voltage In (Vac): 400

Intensidad In (A): 41

Temperature (°C): 105

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic compatibility TÜV SÜD](#)