

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations
Derivations with screw IP68 cable section 4mm² 32A -400V

498M25Y2 - 4535200

Connector Bypass with screws IP68 OK-M25Y 2 poles 4mm²

March 13th, 2025, 11:36



DESCRIPTION

2-pole connector. Black PA6.6 polyamide. Self-extinguishing UL.94V0-GWIT775°C. Operating temperature T105°C. Nickel-plated OT58 brass terminals, galvanized steel screws and silicone gasket.

PRICE

	Lot	P.V.P. excluding VAT
	1	6,95€
	5	5,55€
	15	5,29€
	45	5,04€

Continued on next page >>

ELECTRICAL EQUIPMENT > Korner IP68 Connectors > IP68 Screw derivations
Derivations with screw IP68 cable section 4mm² 32A -400V

498M25Y2 - 4535200

Connector Bypass with screws IP68 OK-M25Y 2 poles 4mm²

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 84 Grams

NOTES

Cable section 4mm²- 32A-400V and AWG12-30A-300V

OTHER FEATURES

Length (mm): 155

Width (mm): 83

Section (mm²): 4

Colour: Black

Voltage In (Vac): 400

Intensidad In (A): 32

Temperature (°C): 105

Ingress Protection: IP68

DOCUMENTS

 [Data Sheet](#)

 [C UR U.S. \(USA-Canada\)](#)

 [Electromagnetic compatibility TÜV SÜD](#)