

15MCUSEN4

Control Unit MCU-SEN4 4 exits 12-24Vdc

August 24th, 2024, 14:36



DESCRIPTION

Receiving control unit of 4 outputs with dimmer function for control, via radio 433.92MHz of led feeders at constant voltage of 12 and 24VDC. For single color led strips. Maximum power 60W (24VDC) I max 2,5A. by exit. Regulacion wide and precise and time of ascent and gradual descent (FADE) adjustable from 0 to 10 seconds. Simple programming by dip-switch, reduced dimensions with fastening by fins with screw.

PRICE

Lot	P.V.P. excluding VAT
1	58,11€
10	55,12€
30	52,39€

Continued on next page >>

15MCUSEN4

Control Unit MCU-SEN4 4 exits 12-24Vdc

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 79 Grams

NOTES

Intensity regulator for LEDs of constant tension at 12-24Vdc. 4 outputs 2.5A per output

OTHER FEATURES

Length (mm): 52

Width (mm): 42

High (mm): 21

Voltage In (Vdc): 12~24

Ingress Protection: IP20

DOCUMENTS

 [Quick start guide](#)

 [Mounting instructions](#)

 [CE](#)