

LED TECHNOLOGY > Led modules > Battery Led Modules Configurable Led battery modules

G5K000P1C

Cylindrical battery Li-Ion 18650 2600mAh 10cm AWG22 cable and connecto

April 05th, 2025, 18:59



DESCRIPTION

Lithium-Ion battery with 10cm cable and connector to the control board. Capacity 2600mAh. 3.7Vdc. 9.62Wh. Life cycles 400-500.

Charge via USB and charger with 5Vdc output. With charging current limiter. Approximate charging time 5 hours. It is advisable to charge the batteries at least every 3 months.

During storage. "First IN, first OUT" is recommended. The storage time of batteries in the warehouse is around 12 months.

PRICE

Lot	P.V.P. excluding VAT
1	6,45€
10	5,86€
50	5,33€
100	5,07€





LED TECHNOLOGY > Led modules > Battery Led Modules Configurable Led battery modules

G5K000P1C

Cylindrical battery Li-Ion 18650 2600mAh 10cm AWG22 cable and connecto

TECHNICAL SPECIFICATIONS

Image: Weight: 51 GramsImage: Weight: 51 GramsImage: Packging: Box 1 UnitMotesNOTESWith AWG22 cable and connectorOTHER FEATURESDiameter (mm): 65Diameter (mm): 18Notage In (Vdc): 3.7Diameter (mm): 18Diameter (mm): 18DOCUMENTS	SYMBOLS	CERTIFICADOS
NOTES With AWG22 cable and connector OTHER FEATURES Length (mm): 65 Diameter (mm): 18 Voltage In (Vdc): 3.7 Ingress Protection: IP20 DOCUMENTS	X X	ROHS CE
With AWG22 cable and connector OTHER FEATURES Length (mm): 65 Diameter (mm): 18 Voltage In (Vdc): 3.7 Ingress Protection: IP20 DOCUMENTS	Weight: 51 Grams	Packging: Box 1 Unit
OTHER FEATURES Length (mm): 65 Diameter (mm): 18 Voltage In (Vdc): 3.7 Ingress Protection: IP20 DOCUMENTS Jacoba State Sta	NOTES	
Length (mm): 65 Diameter (mm): 18 Voltage In (Vdc): 3.7 Ingress Protection: IP20	With AWG22 cable and connector	
Voltage In (Vdc): 3.7 Ingress Protection: IP20 DOCUMENTS	OTHER FEATURES	
DOCUMENTS	Length (mm): 65	Diameter (mm): 18
	Voltage In (Vdc): 3.7	Ingress Protection: IP20

Data Sheet