

G503503E

Led Power Supply CC Mini-3.6-350 350mA 3.6W IP20

February 01st, 2025, 20:38



DESCRIPTION

Led power supply to incorporate with 350mA constant current output. Universal input voltage 100-240Vac. Output voltage from 2.5 to 10Vdc. Power range from 0.87 to 3.5W. Primary wiring with 18cm VDE 7726 0.5mm² cable and secondary wiring with 18cm UL1007 18AWG cable. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

Lot	P.V.P. excluding VAT
1	6,10€
5	5,54€
10	5,03€
50	4,71€



Continued on next page >>

G503503E

Led Power Supply CC Mini-3.6-350 350mA 3.6W IP20

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CERTIFICADOS



CB



Weight: 48 Grams

Packging: Box 1 Unit

NOTES

ECO ERP Design. IP20. Constant current output 350mA.

OTHER FEATURES

Length (mm): 53

High (mm): 21

Voltage In (Vac): 100~240

Intensidad Out (A): 0.35

Power (W): 0.87~3.5

Critical Temperature (°C): 80

Ingress Protection: IP20

Power factor: 0.40

Width (mm): 27

Colour: White

Voltage Out (V): 2.5~10

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+50

Life (Hours): 50000

Dimmable: NO

DOCUMENTS

 [Data Sheet](#)

 [Led Power Supply CC Mini-3.6-350 350mA 3.6W IP20](#)

 [CB](#)

 [Electromagnetic compatibility TÜV SÜD](#)

 [Safety TUV CERTIFIED](#)