

G503503E

**Led Power Supply CC Mini-3.6-350 350mA 3.6W IP20**

November 21st, 2024, 14:27



## DESCRIPTION

Led power supply to incorporate with 350mA constant current output. Universal input voltage 100-240Vac. Output voltage from 2.5 to 10Vdc. Power range from 0.87 to 3.5W. Primary wiring with 18cm VDE 7726 0.5mm<sup>2</sup> cable and secondary wiring with 18cm UL1007 18AWG cable. Class II. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

## PRICE

Lot	P.V.P. excluding VAT
1	6,10€
5	5,54€
10	5,03€
50	4,71€



Continued on next page >>

G503503E

Led Power Supply CC Mini-3.6-350 350mA 3.6W IP20

## TECHNICAL SPECIFICATIONS

---

### SYMBOLS



**SELV**



**CB**



Weight: 48 Grams

Packging: Box 1 Unit

### NOTES

---

ECO ERP Design. IP20. Constant current output 350mA.

### OTHER FEATURES

---

Length (mm): 53

Width (mm): 27

High (mm): 21

Colour: White

Voltage In (Vac): 100~240

Voltage Out (V): 2.5~10

Intensidad Out (A): 0.35

Frecuency (Hz): 50~60

Power (W): 0.87~3.5

Room Temperature (°C): -20~+50

Critical Temperature (°C): 80

Life (Hours): 50000

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.40

### DOCUMENTS

---

 [Data Sheet](#)

 [Led Power Supply CC Mini-3.6-350 350mA 3.6W IP20](#)

 [CB](#)

 [Electromagnetic compatibility TÜV SÜD](#)

 [Safety TUV CERTIFIED](#)